Product ID:VIZZENE A MSDS Date:10/16/1989 FSC:9160 NIIN:00-316-5255 **MSDS Number: BMDQQ** === Responsible Party === Company Name: CLARK-RELIANCE CORP Address:16633 FOLTZ INDUSTRIAL PKY City:STRONGSVILLE State:OH ZIP:44136 Country:US Info Phone Num:216-267-4367 Emergency Phone Num:800-424-9300(CHEMTREC) CAGE:12665 === Contractor Identification === Company Name: CLARK-RELIANCE COR Ρ Address:16633 FOLTZ INDUSTRIAL PKY Box:City:STRONGSVILLE State:OH ZIP:44136 Country:US Phone:216-572-1500 CAGE:12665

Ingred Name:BROMOBENZENE CAS:108-86-1 RTECS #:CY9000000 Fraction by Wt: 99.8% Other REC Limits:NONE SPECIFIED

Ingred Name:UVINUL D-49 CAS:131-54-4 Fraction by Wt: 0.2% Other REC Limits:NONE SPECIFIED

Ingred Name:ATLASOL GREEN 4BL Fraction by Wt: 0.01% Other REC Limits:NONE SPECIFIED

\_\_\_\_\_

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-EYE, SKIN & MUCOUS MEMBRANE IRRITANT. SLIGHTLY TOXIC BY INHALATION & INGESTION. CHRONIC-THIS SOLVENT BASED PRODUCT MAY CAUSE DERMATITIS. THIS PRODUCT CONTAINS BROMOBEZENE WHICH HAS BEEN SHOWN TO CAUSE LIVER DAMAGE IN EXPERIMENTAL ANIMALS AT HIGH DOSE LEVELS. AVOID INTENSE, PROLONGED

OR REPEATED CONTACT.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:INHALE-SLIGHT INHALATION HAZARD. EYE-MODERATE EYE IRRITANT. SKIN-SLIGHT TO MODERATE SKIN IRRITANT. INGEST-SLIGHTLY TOXIC ORALLY.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:INHALE-REM

OVE TO FRESH AIR. GIVE OXYGEN OR CPR AS NEEDED.

CALL DOCTOR. EYE-IMMEDIATELY RINSE WITH WATER FOR 20-30 MINUTES. RETRACT EYELIDS OFTEN. CALL DOCTOR. SKIN-IMMEDIATELY REMOVE CONTAMINATED CLOT HING. WASH SKIN WITH MILD SOAP/WATER. FLUSH W/LUKEWARM WATER FOR 15 MIN. IF STICKY, USE WATERLESS CLEANER FIRST. CALL DOCTOR. INGEST-GIVE LUKEWARM WATRE (PINT) IF VICTIM IS ALERT. INDUCE VOMITING.

Flash Point Metho d:CC
Flash Point:124F,51C
Autoignition Temp:Autoignition Temp Text:1051F
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:DO NOT ENTER FIRE AREA WITHOUT PROPER PROTECTION. FIGHT FIRE FROM SAFE DISTANCE. DO NOT USE SOLID WATER STREAM/MAY SPREAD FIRE. USE WATER SPRAY/FOG FOR COOLING.
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID. HEAT MAY BUILD PRESSURE/RUPTURE CLOSED CONTAINER, SPREADING FIRE. AVOID FROTHING/STEAM EXPLOSION. BURNING LIQUID WILL FLOAT ON WATER.

Spill Release Procedures:RELEASE CAN CAUSE FIRE/EXPLOSION. LIQUIDS/VAPORS MAY IGNITE. EVACUATE/LIMIT ACCESS. EQUIP RESPONDER WITH PROPER PROTECTION. KILL ALL IGNITION SOURCES. STOP RELEASE. PREVENT FLOW TO SEWERS/PUBLIC WATER S. SOAK UP SMALL SPILL WITH INERT SOLIDS.

Handling and Storage Precautions: KEEP C ONTAINERS CLOSED WHEN NOT IN

USE. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAMES, STRONG OXIDIZING AGENTS & DIRECT SUNLIGHT. KEEP AWAY FRM CHILDREN. Other Precautions: HANDLE "EMPTY CONTAINERS WITH ACARE/RESIDUE MAY BE

COMBUSTIBLE & BURN IF EXPOSED TO HEAT/SPARKS/OPEN FLAME. IN ADDITION TO FIRE/EXPLOSION HAZARD, RESIDUAL VAPOR & LIQUID MAY ALSO BE TOXIC.

Respiratory Protection:NO OCCUPATIONAL EXPOSURE STANDARD HAV E BEEN

DEVELOPED FOR THIS MATERIAL. WHERE EXPOSURE THROUGH INHALATION MAY OCCUR FROM USE, NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT IS RECOMMENDED.

Ventilation:LOCAL EXHAUST VENTILATION MAY BE REQUIRED IN ADDITION TO GENERAL ROOM VENTILATION.

Protective Gloves:WEAR PROTECTIVE GLOVES.

Eye Protection: CHEMICAL SPLASH GOGGLES/FACE SHIELD.

Other Protective Equipment: USE APRON, SLEEVES, BOOTS, HEAD & FACE PROTECTION IF NEEDED. HAVE EMERGENCY EYE WASH AND SAFETY SHOWER

AVAILABLE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MIST. DO NOT INGEST. READ PRECAUTIONS ON LABEL BEFORE USE.

HCC:F4 Melt/Freeze Pt:M.P/F.P Text: