GC ELECTRONICS CO.; SUB OF HOUSEHOLD INTERN. CORP. -- PRINT KOTE CONFORMAL COATING 22-204 -- 3439-00-986-2582

============= Product Identification ========================

Product ID:PRINT KOTE CONFORMAL COATING 22-204

MSDS Date:07/01/1991

FSC:3439

NIIN:00-986-2582

MSDS Number: BMDTK === Responsible Party ===

Company Name: GC ELECTRONICS CO.; SUB OF HOUSEHOLD INTERN. CORP.

Address:1801 MORGAN ST

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209 Country:US

Info Phone Num:815-968-9661

Emergen

cy Phone Num:815-968-9661 Preparer's Name:V. HAGEMAN

CAGE:EO032

=== Contractor Identification ===

Company Name: GC ELECTRONICS CO, SUB OF HOUSEHOLD INTERNATIONAL C

Address:1801 MORGAN ST

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Phone:815-968-9661

CAGE:EO032

Company Name:GC THORSEN Address:1801 MORGAN STREET

Box:City:ROCKFORD

State:IL ZIP:61105 Country:US

Phone:815-968-9661

CAGE:72653

====== Composition/Information on Ingredients ========

Ingred Name: TOLUENE (SARA

III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 52%

Other REC Limits: NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: SILICONE RUBBER

Fraction by Wt: 18%

Other REC Limits: NONE SPECIFIED

Ingred Name: ISOBUTANE

CAS:75-28-5

RTECS #:TZ4300000 Fraction by Wt: 30%

Other REC Limits: NONE SPECIFIED

OSHA PEL:1000 PPM ACGIH TLV:1000 PPM

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000 Fraction by Wt: BALANCE Other REC Limits:NONE S

PECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:ASPHYXIANT; 9192

============== Hazards Identification =======================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION- CNS DEPRESSION. EYE- IRRITATION. SKIN- DRYING, IRRITATION. CHRONIC: UNKNOWN.

Explanation of Carcinogenicity: BENZENE, A MINOR COMPONENT (1

Spec Gravity:0.6

Evaporation Rate & Dr. Reference: 1.5 (METHOD: UKNOWN

) Solubility in Water:NEGLIGIBLE Appearance and Odor:AEROSOL: CLEAR,COLORLESS; TOLUENE ODOR Percent Volatiles by Volume:91
========= Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OPEN FLAMES AND

OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:OXIDES OF CARBON

======= Disposal Considerations ============

Waste Dis

posal Methods:CONTACT LOCAL ENVIRONMENTAL MANAGER. DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. DO NOT FLUSH TO DRAIN/STORM SEWER. INCINERATE UNDER CONTRO LLED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informat ion to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.