

RICOH CORPORATION -- SP-35 TONER, SAVIN TONER TYPE L1, 9350 TONE -- 6850-01-343-2257
===== Product Identification =====

Product ID:SP-35 TONER, SAVIN TONER TYPE L1, 9350 TONE

MSDS Date:10/19/1990

FSC:6850

NIIN:01-343-2257

MSDS Number: BMTBF

=== Responsible Party ===

Company Name:RICOH CORPORATION

Address:5 DEDRICK PLACE

City:WEST CALDWELL

State:NJ

ZIP:07006

Country:US

Info Phone Num:201-882-2000

E

mergency Phone Num:800-336-6737

Preparer's Name:KRISTINA SAGE

CAGE:54726

=== Contractor Identification ===

Company Name:RICOH CORPORATION

Address:5 DEDRICK PLACE

City:WEST CALDWELL

State:NJ

ZIP:07006-6304

Country:US

Phone:800-336-6737

CAGE:54726

Company Name:SAVIN CORPORATION

Address:30 W GUDE DRIVE SUITE 350

Box:12070

City:ROCKVILLE

State:MD

ZIP:20850-4015

Country:US

Phone:301-517-4272 FAX 301-517-4269

CAGE:4M009

===== Composition/Information on Ingredients =====

Ingred Nam

e:HYDROTREATED HEAVY NAPHTHA
CAS:64742-48-9
Fraction by Wt: 78%
Other REC Limits:NONE SPECIFIED

Ingred Name:ACRYLIC POLYMER
CAS:25068-63-7
Fraction by Wt: 8%
Other REC Limits:NONE SPECIFIED

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:WAX
CAS:8002-74-2
RTECS #:RV0350000
Fraction by Wt: 10%
Other REC Limits:NONE SPECIFIED

Ingred Name:WAX
CAS:8015-86-9
Fraction by Wt: 3%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL RAT LD50 IS >12400 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:PRODUCT IS PRACTICALLY NON-TOXIC. IT
PRODUCES PHYSICAL IRRITATION OF BODY TISSUES. NO CHRONIC EFFECTS
ARE KNOWN.
Explanation of Carcinogenicity:MFR SHOWS THAT CARBON BLACK IS LISTED
BY IARC AS I

NADEQUATE EVIDENCE.

Effects of Overexposure:HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO EYES AND RESPIRATORY TRACT. MAY CAUSE HEADACHE, DIZZINESS, OR HAVE OTHER CEENTRAL NERVOUS SYSTEM EFFECTS.

Medical Cond Aggravated by Exposure:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE.

INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:DO NOT INDUCE VOMITING. GIVE 2 LARGE GLASSES OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE,SEE A DOCTOR.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:142F,61C

Lower Limits:0.7

Upper Limits:6.5

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fi

re Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDENTS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES AND VENTILATE AREA. RECOVER FREE PRODUCT AND ABSORB REMAINDER. KEEP OUT OF SEWERS AND WATERCOURSES BY DIKING.

Neutralizing Age

nt:NONE

===== Handling and Storage =====

Handling and Storage Precautions:*COMBUSTIBLE LIQUID!* STORE IN A COOL, DRY, DARK AREA. KEEP AWAY FROM IGNITION SOURCES. KEEP OUT OF REACH OF CHILDREN

Other Precautions:'EMPTY' CONTAINERS MAY CONTAIN RESIDUE OR VAPOR. TREAT THEM WITH THE RESPECT DUE FULL ONES. DO NOT CUT,WELD,ETC. ON THEM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR WILL NOT N

ORMALLY BE NECESSARY. USE
NIOSH/MSHA APPROVED RESPIRATOR FOR DUST IF EXPOSURE IS ABOVE THE
TLV/PEL FOR NUISANCE DUST.
Ventilation:NOT NORMALLY REQUIRED.
Protective Gloves:NONE
Eye Protection:NONE
Other Protective Equipment:NONE REQUIRED
Work Hygienic Practices:USE OF GOOD PERSONAL HYGIENE PRACTICES,
MINIMIZE ANY CONTACT. WASH AFTER USING AND BEFORE EATING, DRINKING
OR SMOKING.
Supplemental Safety and Health
FOR USE WITH COPIER/SORTER NSN 3610-01-195-4587.

=====
Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:349F,176C
Vapor Pres:5 MM
Vapor Density:>5.9
Spec Gravity:0.8
Evaporation Rate & Reference:0.04 (N-BUTYL ACETATE = 1
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK LIQUID, NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:NO INFORMATION GIVEN ON MSDS BY SUPPLIER
Hazardous Decompositi
on Products:CARBON MONOXIDE AND OTHER PRODUCTS OF
INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL
REGULATIONS. MANUFACTURER MAKES NO SUGGESTIONS AS TO METHOD OF
DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatso

ever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.