

NASHUA CORPORATION -- XEROX FUSER LUBRICANT FL-45,FL-75 -- 6850-01-164-5738

===== Product Identification =====

Product ID:XEROX FUSER LUBRICANT FL-45,FL-75

MSDS Date:06/28/1990

FSC:6850

NIIN:01-164-5738

MSDS Number: BMZZQ

=== Responsible Party ===

Company Name:NASHUA CORPORATION

Address:44 FRANKLIN STREET

City:NASHUA

State:NH

ZIP:03061

Country:US

Info Phone Num:800-258-1370

Emergency Phone Num:603

-880-5555

Preparer's Name:R.L. SEVIGNY

CAGE:0EK44

=== Contractor Identification ===

Company Name:NASHUA CORP OFFICE PRODUCTS DIV.

Address:44 FRANKLIN ST

Box:City:NASHUA

State:NH

ZIP:03060

Country:US

Phone:603-880-2323

CAGE:34936

Company Name:NASHUA CORPORATION

Address:44 FRANKLIN STREET

City:NASHUA

State:NH

ZIP:03061

Country:US

Phone:603-880-5555

CAGE:0EK44

===== Composition/Information on Ingredients =====

Ingred Name:POLYDIMETHYLSILOXANE

CAS:63148-62-9

RTECS #:JT6485000

Fra

ction by Wt: 100.0%

===== Hazards Identification =====

Routes of Entry: Inhalation:UNKNOWN Skin:UNKNOWN Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NO KNOWN CHRONIC OR CACUTE HAZARDS
WHEN USED AS INTENDED.
Explanation of Carcinogenicity:NOT RELAVENT
Effects of Overexposure:MAY CAUSE TEMPORARY DISCOMFORT TO EYES;HAS A
LAXATIVE EFFECT UPON INGESTION.
Medical Cond Aggravated by Exposure:NONE KNOWN
TO MFR

===== First Aid Measures =====

First Aid:SKIN:WASH WITH SOAP & WATER. EYES:FLUSH EYES WITH WATER FOR
15 MINUTES,CALL A PHYSICIAN. INGESTED:DRINK WATER AND CALL POISON
CONTROL CENTER.

===== Fire Fighting Measures =====

Flash Point Method:OC
Flash Point:600F/316C
Extinguishing Media:WATERFOG,CO*2,DRY CHEMICAL,FOAM.
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS, PROTECTIVE
CLOTHING.
Unusual
Fire/Explosion Hazard:NONE KNOWN TO MFR.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTROL
SP[ILLAGE.
Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

===== Handling and Storage =====

Handling and Storage Precautions:AVOID RUBBING EYES WITH HANDS WHILE
USING THIS MATERIAL.CLEAN UP SPILLS COMPLETELY AS RESIDUE IS
SLIPPERY.
Other Precautions:CLEAN U

P SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.

UPON EYE CONTACT, REMOVE AND CLEAN CONTACT LENSES PRIOR TO REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED.

Ventilation:NONE REQUIRED.

Protective Gloves:NONE REQUIRED

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE REQUIRED.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. WASH
AFTER USING THE PRODUCT AND BEFORE EATING, DRINKING, ETC.

Supplemental Safety and Health

MSDS RECEIVED FROM NAVY (FOCAL POINT N). NAVY IDENTIFIED NSN.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>600F/316C

Vapor Pressure: