

POWER-SONIC CORP -- RECHARGEABLE BATTERIES -- 6140-01-174-7249

===== Product Identification =====

Product ID:RECHARGEABLE BATTERIES

MSDS Date:01/14/1990

FSC:6140

NIIN:01-174-7249

MSDS Number: BNCLD

=== Responsible Party ===

Company Name:POWER-SONIC CORP

Address:3106 SPRING ST

Box:5242

City:REDWOOD CITY

State:CA

ZIP:94063-3929

Country:US

Info Phone Num:415-364-5001/FAX 415-366-3662

Emergency Phone Num:415-364-5001/FAX 415-366-3662

CAGE:56309

=== Contractor Iden

tification ===

Company Name:BATTERY OUTLET INC

Address:1608 CAMPOSTELLA RD

Box:City:CHESAPEAKE

State:VA

ZIP:23324

Country:US

Phone:757-545-4442

CAGE:0FGN2

Company Name:POWER-SONIC CORP

Address:3106 SPRING ST

Box:5242

City:REDWOOD CITY

State:CA

ZIP:94063-3929

Country:US

Phone:650-364-5001

CAGE:56309

Company Name:PRECISION CABLE MFG CO INC

Address:1290 E I 30

Box:1448

City:ROCKWALL

State:TX

ZIP:75087-1448

Country:US

Phone:972-771-1233

CAGE:54840

===== Composition/Information on Ingredien

ts =====

Ingred Name:SULFURIC ACID (SARA III)
CAS:7664-93-9
RTECS #:WS5600000
Fraction by Wt: 17% %
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 60% %
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:LEAD PEROXIDE
CAS:1309-60-0
RTECS #:OG0700000
Fracti
on by Wt: 20% %
Other REC Limits:NONE SPECIFIED

Ingred Name:NON HAZARDOUS INGREDIENT
Fraction by Wt: BALANCE
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES?SKIN: AVOID CONTACT WITH
ELECTROLYTE FROM SPILLED OR BROKEN BATTERY. ELECTROLYTE IS SU

LFURIC

ACID - CORROSIVE. BATTERY UNIT IS CONSIDERED NON-SPILLABLE AND CONTAINS ELECTROLYTE IN A NON- CONDUCTI VE POLYSTYRENE CASING WHICH SHOULD NOT PRESENT UNDUE HEALTH OR CONTACT HAZARDS UNLESS CASING LEAKS OR IS BREACHED.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:BURNING OR IRRITAION OF EYES/SKIN IF ELECTROLYTE ESCAPES AND IS CONTACTED.

Medical Cond Aggravated by Exp
osure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTED: DRINK WATER OR MILK OF MAGNESIA AND GET IM MEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE
Lower Limits:NONFLAMMABLE
Upper Limits:NONFLA
MMABLE

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM OR DRY CHEMICAL AS APPROPRIATE FOR SURROUNDINGS

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY FIRE-EXPOSED CONTAINERS

Unusual Fire/Explosion Hazard:KEEP AWAY FROM OPEN FLAME AND SPARKS. IMPROPER CHARGING MAAAY RESULT IN THE BUILD UP OF EXPLOSIVE GASES .

===== Accidental Release Measures === =====

Spill Release Procedures:MOP OR WIPE UP SPILLED ELECTROLYTE CAREFULLY. AVOID SKIN CONTACT.

Neutralizing Agent:SODIUM BICARBONATE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY AREA. PROTECT BATTERY FROM PHYSICAL DAMAGE. DO NOT INCINERATE.

Other Precautions:NO SPECIAL PRECAUTIONS UNLESS BATTERY IS BROKEN OR IS LEAKING.

===== Exposure Controls/Personal Protection =====

Res

piratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS USUALLY ADEQUATE.

Protective Gloves:RUBBER GLOVES

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EMERGENCY EYEWASH STATION. RUBBER APRON.

Work Hygienic Practices:WASH WITH SOAP AND WATER AFTER HANDLING PRODUCT AND BEFORE EATING DRINKING OR SMOKING.

Supplemental Safety and Health

MATERIAL IS A NON-SPILLABLE BATTERY WITH 17% SULFURIC ACID ELECTROLYTE.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:NOT GIVEN

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor Pres:NOT GIVEN

Vapor Density:NOT GIVEN

Spec Gravity:NOT GIVEN

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:NOT GIVEN

Appearance and Odor:RECTANGUL

AR SQUARE IN SHAPE, ORANGE IN COLOR, NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

SOLVENTS MAY DISSOLVE CASE MATERIAL.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:SEVERE OVERCHARGING AND OVERHEATING MAY CAUSE HYDROGEN, OXYGEN, AND SULFUR OXIDE FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE

E WITH ALL APPLICABLE

FEDERAL, STATE AND LOCAL REGULATIONS. SEND TO BATTERY RECYCLER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.