View NSN Online: https://aerobasegroup.jp/nsn/2530-01-003-5190

## ALLIED SIGNAL AUTOMOTIVE OF CANADA -- ORGANIC DISC PAD -- 2530-01-003-5190

Product ID:ORGANIC DISC PAD

MSDS Date:11/30/1988

FSC:2530

NIIN:01-003-5190

MSDS Number: BNWQS === Responsible Party ===

Company Name: ALLIED SIGNAL AUTOMOTIVE OF CANADA

Address:7311 KIMBEL STREET

City:MISSISSAUGA

State:ON Country:CA

Info Phone Num:416-671-3700 EXT. 260

Emergency Phone Num:4 16-671-3700 EXT. 260

Preparer's Name: TIM CURTIS

CAGE:08472

=== Contractor Identification ===

Company Name: ALLIED-SIGNAL AUTOMOTIVE OF CANADA INC

Address:305 ROMEO ST S

Box:F

City:STRATFORD N5A 6V4

State:ON Country:CA

Phone:519-271-3470

CAGE:08472

Company Name: WHEELER BROTHERS INC Address: INDUSTRIAL PARK, DRUM AVE

Box:737

City:SOMERSET

State:PA

ZIP:15501-2136 Country:US

Phone:814-445-9641

CAGE:2B144

======= Composition/Information on Ingredients ========

Ingred Name: ASBESTOS (FRIAB

LE) (SARA III) CAS:1332-21-4

RTECS #:CI6425000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2.0 FIBERS/CC

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: CHROMIUM OXIDE

CAS:1308-38-9

RTECS #:GB6475000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:C, 0.1 MG/M3 ACGIH TLV:0.05 MG/M3

Ingred Name: COPPER (SARA III)

CAS:7440-50-8

RTECS #:GL5325000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.1MG/M3 FUME/1 DUST

ACGIH TLV:0.2MG/M3 FUME; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9293

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

Other REC Limits:NONE RECOMMENDED OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name: ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS

FORMS) (SARA III)

CAS:1344-28-1


RTECS #:BD1200000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MICA - SILICATES (< 1% CRYSTALLINE SILICA) CAS:12001-26-2 RTECS #:VV8760000 Other REC Limits:NONE RECOMMENDED OSHA PEL:20 MPPCF ACGIH TLV:3 MG/M3 RDUST; 9293
======================================
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:ACUTE: PHENOLIC/CASHEW RESINS MAY CAUSE DERMATITIS. METAL DUSTS CAN IRRITATE EYES AND UPPER RESPIRATORY S
YSTEM. CHRONIC: ASBESTOS FIBERS FROM ABRASIVE ACTIONS MAY LEAD TO ASBESTOSIS AND MESOTHELIOMA. SMOKING COMBINED WITH FIBER INHALATION GREATLY INCREASES LUNG CANCER RISK. Explanation of Carcinogenicity: ASBESTOS IS LISTED BY IARC, NTP AND
OSHA. CHROMIUM IS LISTED BY IARC AND NTP.  Effects of Overexposure:INHALATION: UPPER RESPIRATORY SYSTEM  IRRITATION, COUGHING, WHEEZING. SKIN: UNKNOWN. EYES: POTENTIAL  IRRITATION FROM AIRBORNE DUST. INGESTION: UNKNOWN.
Medical Cond Aggravated b y Exposure:INDIVIDUALS WITH PRE-EXISTING RESPIRATORY CONDITIONS, MAY BE MORE AT RISK FROM EXPOSURE.
======================================
First Aid:INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE. SKIN: WASH EXPOSED AREA WITH SOAP AND WATER. EYES: FLOOD WITH WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION. INGESTION: DRINK WATER. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN. OTHER: CHANGE CLOTHING AS REQUIRED TO AVOID CARRYING DUST P ARTICLES INTO OTHER AREAS.
======================================
Flash Point:NONE Extinguishing Media:MATERIAL IS NOT FLAMMABLE; USE MEDIA APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE A SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES INVOLVING CHEMCIAL PRODUCTS. Unusual Fire/Explosion Hazard:NONE KNOWN
========== Accidental Release Measures ===========



====== Disposal Considerations ===========

Waste Disposal Methods:DUST SHOULD BE HANDLED AS A HAZARDOUS AIR POLLUTANT I/A/W 40CFR61 SUBPART "M" PERTAINING TO ASBESTOS. USE LANDFILLS APPROVED FOR ASBESTOS DISPOSAL. NOTE IF ITEM UNDER CONSIDERATION FOR DISPOSAL IS "FR IABLE OR NON-FRIABLE".

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The Unit ed States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.