

PLASTODENT INC -- METHYL METHACRYLATE MONOMER (MMA), INHIBITE -- 6520-01-020-8270
===== Product Identification =====

Product ID:METHYL METHACRYLATE MONOMER (MMA), INHIBITE

MSDS Date:01/01/1989

FSC:6520

NIIN:01-020-8270

MSDS Number: BNWRH

=== Responsible Party ===

Company Name:PLASTODENT INC

Address:2881 MIDDLETOWN RD

City:BRONX

State:NY

ZIP:10461

Country:US

Info Phone Num:212-792-3554

Emergency Ph

one Num:212-792-3554

Preparer's Name:NONE

CAGE:GO326

=== Contractor Identification ===

Company Name:PLASTODENT INC

Address:2881 MIDDLETOWN RD

City:BRONX

State:NY

ZIP:10461-5306

Country:US

Phone:609-893-1100

CAGE:GO326

Company Name:PLASTODENT INC.

Address:2881 MIDDLETON ROAD

Box:City:BRONX

State:NY

ZIP:10461-3306

Country:US

Phone:212-792-3554

CAGE:8P273

===== Composition/Information on Ingredients =====

Ingred Name:METHYL METHACRYLATE (SARA III)

CAS:80-62-6

RTECS #:OZ5075000

F

reaction by Wt: 100%
Other REC Limits:NONE DETERMINED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION-MAY CAUSE NOSE & THROAT IRRITATION. MAY CAUSE NERVOUS SYSTEM DEPRESSION. REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. SKIN OR EYE-MAY CAUSE IRRITATION OR BURNING OF THE EYES. REPEATED OR PROLONGED LIQUID CONTACT MAY IRRITATE THE SKIN.
Effects of Overexposure:INHALATION-HEADACHE, DIZZINESS, NAUSEA, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS. SKIN/EYE-BURNING OF THE EYES. SKIN DERMATITIS. OTHER POTENTIAL HAZARDS: IRRITATION OF THE MUCOUS MEMBRANES, SKIN BURNS, ALLERGIC SKIN RASH, ITCHING, SWELLING, CAUSES EYE CORROSION AND PERMANENT INJURY, ABNORMAL LIVER & KIDNEY FUNCTION.
Medical Condition Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. IF NOT BREATHING GIVE CPR; IF BREATHING DIFFICULTY PERSISTS CONSULT A PHYSICIAN. EYE:IMMEDIATELY FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MIN. CALL A PHYSICIAN. SKIN: WASH W/SOAP & WATER. IF IRRITATION OCCURS,CONSULT PHYSICIAN. INGESTION-GASTRO-INTESTINAL DISTRESS. IN THE UNLIKELY EVENT OF INGESTION, CALL A PHYSICIAN IMMEDIATELY & KNOW NAME OF INGREDIENTS.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:51.0F,10.6C
Lower Limits:1.8%
Upper Limits:8.2%
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATERFOG (BY TRAINED PERSONNEL).
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT, INCLUDING SELF-CONTAINED BREATHING APPARATUS, IS RECOMMENDED. WATER FROM FOG NOZZLE MAY BE USED TO PREVENT PRESSURE BUILD-UP.
Unusual Fire

re/Explosion Hazard:WHEN HEATED ABOVE FLASHPOINT, EMITS
FLAMMABLE VAPORS, WHEN MIXED WITH AIR, CAN BURN OR EXPLODE. FINE
MIST/SPRAYS MAY BE FLAMMABLE BELOW FLASH. VAPORS FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. REMOVE SOURCES OF
IGNITION.PREVENT SKIN CONTACT AMD BREATHING OF VAPORS. CONFINE AND
REMOVE WITH INERT ABSORBENT. DO NOT ALLOW MATERIAL TO CONTAMINATE
GROUND WATER SYSTEMS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, FLAME,
DIRECT SUNLIGHT & ELEVATED TEMPERATURES. CLOSE CONTAINERS AFTER
EACH USE. GROUND CONTAINER WHEN POURING.

Other Precautions:PERMIT AIR SPACE TO EXIST INSIDE STORAGE CONTAINERS.
MATERIAL STORED MORE THAN 3 MONTHS SHOULD HAVE INHIBITOR LEVEL
CHECKED AND MAINTAINED AT ORIGINAL LEVELS.

===== Exposure Controls/Personal Protection =====

Respirat
ory Protection:DO NOT BREATH VAPORS OR MISTS. WHEN LEVELS
EXCEED 100 PPM, WEAR SELF-CONTAINED BREATHING APPARATUS. FOLLOW THE
RESPIRATOR MANUFACTURERS DIRECTIONS FOR RESPIRATOR USE.

Ventilation:SUFFICIENT VENTILATION IN VOLUME & PATTERN TO KEEP
CONTAMINANTS BELOW APPLICABLE OSHA REQUIREMENTS/OTHER EXPOSURE
LIMIT.

Protective Gloves:NEOPRENE GLOVES.

Eye Protection:GOGGLES, SAFETY GLASSES W/SPLASH GUARDS.

Other Protective Equipment:EYEWASH, SAFETY SHOWER, COVERALLS, AND BOOTS
AR
E RECOMMENDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING OR SMOKING.

Supplemental Safety and Health

PROTECTIVE CREAMS: DO NOT USE FOR PROTECTION. MAY BE USED FOR EASE OF
CLEANUP. AQUATIC TOXICITY: ESTIMATE OF 96 HR. MEDIAN THRESHOLD
LIMIT: 100-1000 PPM.***THIS MATERIAL IS A TWO PART KIT. THIS IS PAR
T "B" OF THE KIT.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:214F,101C

Vapor Density:3.46 @60F

S

pec Gravity:0.950 GR/CC
Solubility in Water:1.6 GR/100GR WATER
Appearance and Odor:LIQUID.
Percent Volatiles by Volume:100%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
REDUCING & OXIDIZING AGENTS. MATERIAL HAS STRONG SOLVENT ACTION & CAN
SOFTEN PAINT & RUBBER.
Stability Condition to Avoid:HEAT AND IGNITION SOURCES; CONTAMINATION.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
SMOKE.

=====
=== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN A FACILITY WHICH COMPLIES WITH
FEDERAL, STATE AND LOCAL REQUIREMENTS. DO NOT INCINERATE IN CLOSED
CONTAINERS. EPA LISTED HAZARDOUS WASTE UNDER RCRA(U-162).

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this
information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.