View NSN Online: https://aerobasegroup.jp/nsn/9140-01-079-5805

Product ID:DFW GAS OIL LO PR

MSDS Date:07/18/1992

FSC:9140

NIIN:01-079-5805

MSDS Number: BPCCF === Responsible Party ===

Company Name: HONAM OIL REFINERY LTD Address: 20 YOIDO-DONG YONGDUNGPO-KU

City:SEOUL CAGE:5W181

=== Contractor Identification ===

Company Name: HONAM OIL REFINERY LTD

Address:20 YOIDO

-DONG YONGDUNGPO-KU

Box:City:SEOUL KOREA

CAGE:5W181

======= Composition/Information on Ingredients ========

Ingred Name: PETROLEUM OIL (NO. 2 DIESEL)

CAS:68334-30-5 Fraction by Wt: 100%

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification ==============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: ACUTE- MAY CAUSE SLIGHT EYE


IRRITATION. MAY HAVE

SLIGHT TOXICITY BY INGESTION BUT HAS

ASPIRATION HAZARD CAUSING PNEUMONITIS. INHALATION MAY CAUSE DROWSINESS OR NARCOSIS. PRIMARY SKIN IRRITANT. MAY CAU SE BURNS & BLISTERING. CHRONIC- MAY CAUSE DERMATITIS.

Explanation of Carcinogenicity:NIOSH RECOMMENDS THAT WHOLE DIESEL EXHAUST BE REGARDED AS A "POTENTIAL OCCUPATIONAL CARCINOGEN".

Effects of Overexposure:MAY CAUSE SLIGHT EYE IRRITATION. MAY HAVE SLIGHT TOXICITY BY INGESTION BUT HAS ASPIRATION HAZARD CAUSING PNEUMONITIS.



== Exposure Controls/Personal Protection ======== Respiratory Protection: USE APPROVED RESPIRATORY PROTECTIVE EQUIPMENT FOR CLEANING LARGE SPILLS OR ENTRY INTO LARGE TANKS, VESSELS OR OTHER CONFINED SPACES. Ventilation: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves: IMPERVIOUS Eve Protection: CHEMICAL SAFETY GLASSES/GOGGLES Other Protective Equipment: REMOVE CONTACT LENSES AND WEAR CHEMICAL SAFETY GLASSES WHERE CONTACT WITH LIQUID MAY OCCUR. Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER HANDLING THIS PRODUCT. Supplemental Safety and Health ======== Physical/Chemical Properties ============ HCC:V4 Boiling Pt:B.P. Text:392F,200C Vapor Pres:LOW Spec Gravity:0.85 Solubility in Water:NIL Appearance and Odor:LIQUID- PETROLEUM ODOR ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stabil ity Condition to Avoid:HIGH HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION Hazardous Decomposition Products: NONE KNOWN.

======= Disposal Considerations ============

Waste Disposal Methods:PLACE CONTAMINATED MATERIALS IN DISPOSABLE CONTAINERS AND DISPOSE OF IN A MANNER CONSISTENT WITH APPLICABLE REGULATIONS. CONTACT LOCAL ENVIRONMENTAL OR HEALTH AUTHORITIES FOR APPROVED DISPOSAL OF THIS MATERIAL.

Disclaimer (provided with this information by th

e compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.