

FARWEST PAINT MFG CO -- YELLOW AIRFIELD & TRAFFIC MARKING PAINT -- 8010-00-082-2598

=====
Product Identification
=====

Product ID:YELLOW AIRFIELD & TRAFFIC MARKING PAINT

MSDS Date:09/24/1990

FSC:8010

NIIN:00-082-2598

MSDS Number: BPKJS

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8

844

Emergency Phone Num:206-941-1619

Preparer's Name:MIKE L. HARRIS

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:VM&P NAPTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 23-28%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:TOLUENE

(SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 4-9%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 50.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CHROMIC ACID
CAS:1333-82-0
RTECS #:GB6650000
Fraction by Wt: 25.5%
Other REC Limits:NONE
RECOMMENDED
OSHA PEL:100 MICRO GRAMS/M3
ACGIH TLV:50 MICRO GRAMS/M3

Ingred Name:LEAD SULFOCHROME (CHROME YELLOW PIGMENT)
CAS:1344-37-2
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE-EYES/SKIN:IRRITATION.
INHALATION: IRRITATION TO THE RESPIRATORY TRACT, DIZZINE

SS,
HEADACHE, UNCONSCIOUSNESS. INGESTION: INTESTINAL DISORDERS, NAUSEA,
VOMITING, ASPIRATION INTO LUNGS MAY CAUSE CHEMICAL PNEUMONITIS
WHICH CAN BE FATAL. CHRONIC-DERMATITIS, LIVER AND KIDNEY DAMAGE.
Explanation of Carcinogenicity:LEAD AND CHROMATE ARE LISTED
CARCINOGENIC.

Effects of Overexposure:INGESTION:SEVERE GASTROINTESTINAL IRRITATION,
NAUSEA, VOMITING & DIARRHEA. IRRITATION EYES AND SKIN. LOSS OF
APPETITE, LEAD LINES AROUND GUMS, CNS EFFECT, FATIGUE, WEAKNESS.

Medi
cal Cond Aggravated by Exposure:LIVER, KIDNEY AND PREVIOUS EXPOSURE
TO LEAD.

=====
===== First Aid Measures =====

First Aid:EYES AND SKIN: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15
MINUTES. INHALATION: REMOVE TO FRESH AIR. INGESTION: DRINK 1 TO 2
GLASSES OF WATER. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR
POISON CONTROL CENTER IMMEDIATELY. FOR EXCESSIVE EXPOSURE OR IF
SYMPTOMS PERSIST, ALWAYS CONSULT A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:45.0F,7.2C
Autoignition Temp:Autoignition Temp Text:420 F
Lower Limits:1.0%
Extinguishing Media:DRY CHEMICAL, CHEMICAL FOAM, CO2.
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS WITH FULL
FACE PROTECTION AND POSITIVE PRESSURE.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL
ALONG GROUND & BE IGNITED BY IGNITION SOURCES. UNOPENED CONTAINERS
EXPOSED TO INTENSE HEAT MAY EXPLODE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL WITH DIKES. REMOVE IGNITION
SOURCES. PREVENT ENTRY INTO BODIES OF WATER OR SEWERS. REMOVE BY
VACUUM OR ABSORB IN SAND OR VERMICULITE AND SAVE IN CONTAINERS FOR
DISPOSAL.
Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT OR OPEN FLAME AND
OTHER IGNITION SOURCES.
Other P

recautions:KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED OR WHEN SPRAYING OR USING IN CONFINED SPACES.

Ventilation:USE IN WELL VENTILATED AREAS. AVOID BREATHING FUMES.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:OSHA APPR'D CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:EYE WASH EQUIPMENT SHOULD BE AVAILABLE.

Work Hygienic Practices

:DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH THIS PRODUCT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:300F,149C

Vapor Density:>1

Spec Gravity:3.47 LBS/GAL

Viscosity:73 KU

Evaporation Rate & Reference: