

EXXON CO USA, A DIV OF EXXON CORP. -- JOBBER REGULAR GASOLINE -- 9130-00-148-7103
===== Product Identification =====

Product ID: JOBBER REGULAR GASOLINE
MSDS Date: 12/02/1991
FSC: 9130
NIIN: 00-148-7103
MSDS Number: BPRCR
=== Responsible Party ===
Company Name: EXXON CO USA, A DIV OF EXXON CORP.
Address: 800 BELL ST
Box: 2180
City: HOUSTON
State: TX
ZIP: 77252-2180
Country: US
Info Phone Num: 713-656-2443
E-mail:
Agency Phone Num: 713-656-3424
CAGE: 29700
=== Contractor Identification ===
Company Name: EXXON COMPANY U.S.A.
Box: 2180
City: HOUSTON
State: TX
ZIP: 77252-2180
Country: US
Phone: 713-656-5949 / 713-656-3424
CAGE: 29700
Company Name: ROGERS R T OIL CO INC
Address: 300 GRACE ST
Box: 160
City: HINTON
State: WV
ZIP: 25951
Country: US
CAGE: 0A889

===== Composition/Information on Ingredients =====

Ingredient Name: NAPHTHA, LIGHT CATALYTIC CRACKED
CAS: 64741-55-5
Other REC Limits: NONE RECOMMENDED

Ingredient

Name:NAPHTHA, HEAVY CATALYTIC CRACKED

CAS:64741-54-4

Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA, FULL-RANGE REFORMED

CAS:68919-37-9

Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA, FULL-RANGE ALKYLATE

CAS:64741-64-6

Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA, SWEETENED

CAS:64741-87-3

Other REC Limits:NONE RECOMMENDED

Ingred Name:BUTANE

CAS:106-97-8

RTECS #:EJ4200000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:800 PPM

ACGIH TLV:800 PPM; 9293

=====

Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5 G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:PROLONGED/REPEATED SKIN CONTACT TENDS TO REMOVE SKIN OILS, POSSIBLY LEADING TO IRRITATION & DERMATITIS. PRODUCT HAS A LOW ORDER OF ACUTE & DERMAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION/VOMITING MAY CAUSE MILD TO

SEVERE PULMONARY INJURY & POSSIBLY DEATH.

Explanation of Carcinogenicity:THIS PRODUCT MAY CONTAIN UP TO A MAX OF 4.9% BENZENE. BENZENE IS LISTED AS A CARCINOGEN BY NTP, IARC, OSHA AND EPA.

Effects of Overexposure:HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES & THE RESPIRATORY TRACT, AND MAY CAUSE HEADACHES, DIZZINESS, ANESTHESIA, DROWSINESS, UNCONSCIOUSNESS, AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DEATH.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH

LIVER DISEASE

(BENZENE), NEUROLOGICAL (HEXANE) AND SKIN DISORDER SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

===== First Aid Measures =====

First Aid: EYE-FLUSH WITH CLEAR WATER FOR 15 MIN OR UNTIL IRRITATION STOPS. SKIN-WASH SKIN WITH SOAP & WATER. IF INJECTED UNDER THE SKIN, THE INDIVIDUAL SHOULD BE EVALUATED IMMEDIATELY BY A PHYSICIAN. INHALATION -IF OVERCOME BY VAPOR, REMOVE FROM EXPOSURE & CALL PHYSICIAN. IF BREATHING IS IRREGULAR OR STOPS, START RESUSCITATION, ADMINISTER OXYGEN, IF AVAILABLE. INGEST-DO NOT INDUCE VOMITING; CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: