

LHB INDUSTRIES -- SO SURE WHITE 37875 54-370

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 00-878-5761  
MSDS Date: 05/13/1992  
MSDS Num: BPRKV  
Product ID: SO SURE WHITE 37875 54-370  
MFN: 03  
Responsible Party  
Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Info Phone Number: 314-522-3141  
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141  
Preparer's Name: RUDOLF OPPENHEIM  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134

=====  
Contractor Summary  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Phone: 314-522-3141

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: ENAMEL  
Unit of Issue: PT  
UI Container Qty: 0

=====  
Ingredients  
=====

Cas: 108-88-3

RTECS #: XS5250000  
Name: TOLUENE (SARA III)  
% Wt: 16.44  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 200 PPM/150 STEL  
ACGIH TLV: 50 PPM; 9293  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----  
Cas: 67-64-1  
RTECS #: AL3150000  
Name: ACETONE (SARA III)  
% Wt: 25.42  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 1000PPM  
ACGIH TLV: 750PPM/1000STEL;9293  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS

-----  
Cas: 1330-20-7  
RTECS #: ZE2100000  
Name: XYLENE (SARA III  
)  
% Wt: 3.55  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----  
Cas: 74-98-6  
RTECS #: TX2275000  
Name: PROPANE  
% Wt: 14.91  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: 1000 PPM  
ACGIH TLV: 1000 PPM

-----  
Cas: 75-28-5  
RTECS #: TZ4300000  
Name: ISOBUTANE  
% Wt: 5.87  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 800 PPM

-----  
Cas:

106-97-8

RTECS #: EJ4200000

Name: N-BUTANE

% Wt: 3.67

Other REC Limits: NONE SPECIFIED

OSHA PEL: 800 PPM

ACGIH TLV: 800 PPM

-----  
Cas: 100-41-4

RTECS #: DA0700000

Name: ETHYLBENZENE (SARA III)

% Wt: &lt;1.77

Other REC Limits: NONE SPECIFIED

OSHA PEL: 100 PPM

ACGIH TLV: 100 PPM

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

-----  
Cas: 8032-32-4

RTECS #: OI6180000

Name: PETROLEUM HYDROCARBON MIX LIGROIN

% Wt: 8.87

Other REC Limits: NONE SPECIFIED

OSH

A PEL: 100 PPM

ACGIH TLV: 100 PPM

-----  
RTECS #: 9999999VO

Name: VOC: 81% 669 G/L

Other REC Limits: NONE SPECIFIED

=====  
Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: CONCENTRATING & INHALING MAY BE HARMFUL/FATAL.

REPEATED/PROLONGED OVEREXPOSURE TO SOLVEN

TS: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. IN CONFINED AREAS VAPOR IN HIGH CONCENTRATIONS ARE ANESTHETIC. IRRIT TO SKIN & RESP TRACT. LIGHT HEADEDNESS, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.  
Signs And Symptions Of Overexposure: IRRIT TO EYES, THROAT & RESP TRACT. MAY CAUSE HEADACHES, NAUSEA & VOMITING.  
Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.  
First Aid: FOR CONTACT WITH SKIN OR CLOTHES WASH WITH SOAP & WATER; WASH

CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES & CONTACT PHYSICIAN/OPHTHAMOLOGIST IMMEDIATELY. IF SWALLOWED, DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL AID. IF INHALED, REMOVE TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION IF NECESSARY AND GET MED AID. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

=====  
Handling and Disposal  
=====

Spill Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.

USE MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS. DO NOT PUNCTURE, INCINERATE OR STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING. DISCARD EMPTY CAN IN TASH PICK-UP. DON'T PLACE IN HOME TRASHCOMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN!

CAUTION-CONTENTS UNDER

PRESSURE. DO NOT STORE ABOVE 120F. AVOID BREATHING SPRAY, MIST OR VAPOR.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION.

READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING OR SWALLOWING CONTENTS MAY BE HARMFUL OR FATAL.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Text:

Text: NR

Autoignition Temp Text: 874 F

Lower Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CO2, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO KEEP FIRE EXPOSED CONTAINER COOL. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING OF CONTAINERS.

Unusual Fire/Explosion Hazard: DON'T SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPERATURES (OVER 120F) CONTAINERS MAY VENT

RUPTURE OR BURST. AEROSOL  
CONTAINERS; DO NOT EXPOSE TO TEMPS ABOVE 120F.

=====  
Control Measures  
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.  
Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT  
POINT OF MIST OR SPRAY RELEASE.  
Protective Gloves: TO PROTECT SKIN.  
Eye Protection: CHEMICAL SPLASH GOGGLES.  
Other Protective Equipment:  
IMPERVIOUS CLOTHING TO PROTECT SKIN. EYE WASH  
STATION.  
Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK OR SMOKE  
WHILE USING PRODUCT.

=====  
Physical/Chemical Properties  
=====

HCC: V3  
Vapor Pres: 60 @ 68F  
Vapor Density: >1.5  
Spec Gravity: 1.007 (WATER=1)  
Solubility in Water: INSOLUBLE  
Appearance and Odor: WHITE / PAINT

=====  
Reactivity Data  
=====

Stability Indicator: YES  
Stability Condition To Avoid: EXTREME HEAT.  
Hazardous Decomposition Products: CARBON MONOXIDE, AND POSSIBLE HYDROGEN  
CHLORIDE.  
Hazardous Polymerization Indicator: NO

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

=====

Transportation Information

=====

Responsible Party Cage: 0FTT5  
Trans ID NO: 89716  
Product ID: SO SURE WHITE 37875 54-370  
MSDS Prepared Date: 05/13/1992  
Review Date: 09/14/1992  
MFN: 3  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: PT  
Container QTY: 0

=====

Detail DOT Information

=====

DOT PSN Code: DTJ  
Symbols: D  
DOT Proper Shipping  
Name: CONSUMER COMMODITY  
Hazard Class: ORM-D  
Label: NONE  
Non Bulk Pack: 156,306  
Bulk Pack: NONE  
Max Qty Pass: 30KGGROSS  
Max Qty Cargo: 30KGGROSS  
Vessel Stow Req: A

=====

Detail IMO Information

=====

IMO PSN Code: AKH  
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?  
IMDG Page Number: SEE 9022  
UN Number: 1950  
UN Hazard Class: 9?  
IMO Packaging Group: -  
Subsidiary Risk Label: -  
EMS Number: 2-13

=

=====

Detail IATA Information

=====

IATA PSN Code: ALS  
IATA UN ID Num: 1950  
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE  
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
IATA UN Class: 2.1  
IATA Label: FLAMMABLE GAS  
Packing Note Passenger: 203  
Max Quant Pass: 75KG  
Max Quant Cargo: 150KG  
Packaging Note Cargo: 203

=====

Detail AFI Information

=

=====  
AFI PSN Code: ALS

AFI Proper Shipping Name: AEROSOLS, NONFLAMMABLE, N.O.S.

AFI PSN Modifier: CONTAINING SUBSTANCES IN CLASS 8, PACKING GROUP I OR II

AFI Hazard Class: FORB

Back Pack Reference: FORBIDDEN  
=====

HAZCOM Label  
=====

Product ID: SO SURE WHITE 37875 54-370

Cage: 0FTT5

Company Name: LHB INDUSTRIES

Street: 8833 FLEISCHER PLACE

City: S

T. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: CONCENTRATING & INHALING MAY BE HARMFUL/FATAL.

REPEATED/PROLONGED OVEREXPOSURE TO SOLVENTS: PERMANENT BRAIN & NERVOUS  
SYSTEM DAMAGE. IN CONFINED AREAS VAPOR IN HIGH CONCENTRATIONS ARE ANESTHETIC.

IRRI T TO SKIN & RESP TRACT. LIGHT HEADEDNESS, STAGGERING, GID

DINESS,

NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRIT TO EYES, THROAT

& RESP TRACT. MAY CAUSE HEADACHES, NAUSEA & VOMITING.  
=====

Disclaimer (provided with this information by the compiling agencies): This  
information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied  
warrants, states, or intends said information to have any appl

ication, use or

viability by or to any person or persons outside the Department of Defense  
nor any person or persons contracting with any instrumentality of the United

States of America and disclaims all liability for such use. Any person  
utilizing this instruction who is not a military or civilian employee of the

United States of America should seek competent professional advice to verify  
and assume responsibility for the suitability of this information to their

particular situati

on regardless of similarity to a corresponding Department of Defense or other government situation.