

AVEX ELECTRONICS CORP -- NICKEL-CADMIUM SEALED CELL BATTERY -- 6140-01-137-6032

===== Product Identification =====

Product ID:NICKEL-CADMIUM SEALED CELL BATTERY

MSDS Date:08/17/1992

FSC:6140

NIIN:01-137-6032

MSDS Number: BPRPF

=== Responsible Party ===

Company Name:AVEX ELECTRONICS CORP

Address:1683 WINCHESTER ROAD

Box:1026

City:BENSALEM

State:PA

ZIP:19020-4510

Country:US

Info Phone Num:215-638-15

15

Emergency Phone Num:215-638-1515

CAGE:58414

=== Contractor Identification ===

Company Name:AVEX ELECTRONICS CORP

Address:1683 WINCHESTER ROAD

Box:1026

City:BENSALEM

State:PA

ZIP:19020-4510

Country:US

Phone:215-638-1515

CAGE:58414

Company Name:HEWLETT-PACKARD CO, CORPORATE HQ

Address:3000 MINUTEMAN RD

Box:City:ANDOVER

State:MA

ZIP:01810-1032

Country:US

Phone:404-648-8754/FAX: 800-947-3299

CAGE:28480

===== Composition/Information on Ingredients =====

Ingred Name:CADMIUM (

SARA III)
CAS:7440-43-9
RTECS #:EU9800000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE 1910.1027
ACGIH TLV:0.01 MG/M3 DUST;9394
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:CADMIUM OXIDE (SARA III)
CAS:1306-19-0
RTECS #:EV1925000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE 1910.1027
ACGIH TLV:0.05 MG(CD)/M3; 9293

Ingred Name:CADMIUM HYDROXIDE
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3 (CD FUME)
ACGIH TLV:0.05 MG/M3 (CD FUME)

Ingred Name:NICKEL HYDROXIDE (SARA III)
CAS:12
054-48-7
RTECS #:QR7040000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG NI/M3
ACGIH TLV:0.1 MG NI/M3; 9293
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:NICKEL (SARA III)
CAS:7440-02-0
RTECS #:QR5950000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9293

Ingred Name:NICKEL OXIDE
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3 (NI DUST)
ACGIH TLV:0.05 MG/M3 (NI DUST)

===== Hazards Identification =====

Routes of Entry: Inhalat

ion:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE: CONTACT WITH CELL CONTENTS MAY CAUSE SKIN AND EYE IRRITATION. INHALING DUST OR MIST FROM CELL CONTENTS MAY CAUSE RESPIRATORY IRRITATION. SWALLOWING CELL CONTENTS MAY CAUSE DIGESTIVE SYSTEM DISTRESS. CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:NICKEL AND CADMIUM AND THEIR COMPOUNDS ARE KNOWN OR SUSPECT CARCINOGENS.

Effects

of Overexposure:INHALED: COUGHING, SHORTNESS OF BREATH, WHEEZING, SNEEZING, SORE THROAT. EYES: BURNING SENSATION, REDNESS, PAIN, TEARING. SKIN: REDNESS, SWELLING, ITCHING. INGESTED: NAUSEA, VOMITING.

Medical Condition Aggravated by Exposure:PERSONS WITH SKIN AND RESPIRATORY DISORDERS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:SKIN: FLUSH WITH WATER. EYE: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES AND CONTACT A PHYSICIAN IMMEDIATELY.

INHALATION: REMOVE TO FRESH AIR AND CONSULT A PHYSICIAN. INGESTED: IF CONSCIOUS, GIVE WATER, THEN INDUCE VOMITING. GET MEDICAL HELP.

===== Fire Fighting Measures =====

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, OR DRY CHEMICAL

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS SUCH AS TOXIC CADMIUM OXIDE FUMES.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL. COLLECT SPILLED MATERIAL AND PLACE IN A CONTAINER FOR LATER DISPOSAL. NEUTRALIZE AND FLUSH SPILL AREA WITH WATER.

Neutralizing Agent:5% ACETIC ACID OR VINEGAR

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE AT ROOM TEMPERATURE IN A DRY PLACE.

Other Precautions:DO NOT INCINERATE BATTERIES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:NONE NORMALLY REQUIRED.

Protective Gloves:NEOPRENE, RUBBER OR LATEX NITRILE

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:RUBBER OR PLASTIC GARMENTS.

Work Hygienic Practices:AVOID EYE/SKIN CONTACT WITH LEAKING BATTERIES.

WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING.

Supplemental Safety and Health

ITEM IS HEWLETT PACKARD PART NUMBER: 1420-0251.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.6

Appearance and Odor:EACH BATTERY CELL IS A SEALED CYLINDRICAL CONTAINER ENCLOSING THE ELECTROLYTES.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ANY SUBSTANCE WHICH WOULD CORRODE THE CASING AND CAUSE LEAKAGE OF THE BATTERY ELECTROLYTE.

Stability Condition to Avoid:HIGH TEMPERATURES AND OPEN FLAMES

Hazardous Decomposition Products:BATTERY MAY EMIT HAZARDOUS VAPORS OF POTASSIUM HYDROXIDE AND CADMIUM AND NICKEL AND THEIR COMPOUNDS WHEN HEATED.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE. BROKEN BATTERIES OR WITH LEAKING ELECTROLYTE CONSTITUTE HAZARDOUS WASTE. CONSULT WASTE DISPOSAL OFFICIALS FOR ADVIC

E. DISPOSE OF IN ACCORDANCE WITH LOCAL,
STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.