View NSN Online: https://aerobasegroup.jp/nsn/8010-01-354-0969

DEFT INC CHEMICAL COATING DIV -- TT-P-2756, 36118, 1-COAT PC03GY381 -- 8010-01-354-0969

Product ID:TT-P-2756, 36118, 1-COAT PC03GY381

MSDS Date:06/07/1991

FSC:8010

NIIN:01-354-0969

Kit Part:Y

MSDS Number: BQDVX === Responsible Party ===

Company Name: DEFT INC CHEMICAL COATING DIV

Address:17451 VON KARMAN AVE

City:IRVINE State:CA

ZIP:92714-6205

Country:US Info Phon

e Num:714-474-0400

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name: NORM GAUL

CAGE:33461

=== Contractor Identification === Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE State:CA ZIP:92614 Country:US

Phone:949-474-0400

CAGE:33461

======= Composition/Information on Ingredients ========

Ingred Name:ALIPHATIC ISOCYANATE, HEXAMETHYLENE DIISOCYANATE (HDI) CAS NO. 822-06-0, FREE MONOMER CONTENT LESS THAN 0.5%.

CAS:28182-81-2

RTECS #:NQ9170000

Fraction by

Wt: 60%

Other REC Limits: MOBAY-0.02 CEILING

ACGIH TLV:0.005 PPM

Ingred Name:ETHYL-3-ETHOXYPROPIONATE (VP: .7 MMGH @ 68F)

CAS:763-69-9

RTECS #:UF3325000 Fraction by Wt: 25%

Other REC Limits:50 PPM-TWA/STEL 100

Ingred Name:N-BUTYL ACETATE (VP: 13 MMGH @ 68F)

CAS:123-86-4

RTECS #:AF7350000 Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED OSHA PEL:150 PPM/STEL 200 ACGIH TLV:150 PPM/STEL 200

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: VAPORS IRRIT TO

EYES-NOSE-THROAT. INHAL MAY CAUSE HEADACHES-DIFFICULT BREATH-LOSS OF CONSCIOUSNESS. CHRONIC: AS A RESULT OF PREVIOUS REPEAT OVEREXPOS/SINGLE LG DOSE, SOME INDIVIDUALS WILL DEVEL OP ISOCYANATE SENSITIZATION CAUSING A REACTION TO LATER EXPOS OF ISOCYANATE LEVELS WELL BELOW TLV VALUE OF ISOCYANATES

Effects of

Overexposure:INHAL: RESP TRACT IRRIT, NERV SYS DEPRESS
W/HEADACHE-DIZZI-STAG GAIT-CONFUSION-UNCONSCIOUS-COMA. EYE: IRRIT,
POSS TEARING-REDNESS-SWELLING W/STING SENSATION. SKIN: IRRIT
W/SWELLING-REDNESS-RASH-DRY-DE FAT. INGEST: IRRIT, POSS CORROSIVE
ACTION IN MOUTH-STOMACH TISSUE-DIGEST TRACT. POSS ASPIR
W/VOMITING-CHEM PNEUMONITIS

Medical Cond Aggravated by Exposure:ASTHMA AND ANY OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMATITIS. ISOCYANATE SENSITI

======================================
First Aid:INHAL: MOVE TO FRESH AIR. RESTORE BREATHING. ASTHMATIC TYPE SYMPTOMS-MAY BE IMMEDIATE OR DELAYED BY SEVERAL HOURS-GET MED AID SKIN: REMOVE CONTAMINATED CLOTHING-WASH BEFORE REUSE. WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER (LOW PRESSURE) 15 MINUTES, LIFTING LIDS-GET MED AID. INGEST: DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON-GET MED AID.
======= Fire Fighting Measures ==============================
Flash Point Method:TCC Flash Point:76.0F,24.4C Lower Limits:1.05% Upper Limits:7.60% Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG Fire Fighting Procedures:FULL FIRE FIGHT EQUIP W/SCBA AND FULL PROTECT CLOTHING. MAY USE WATER TO COOL CLSD CNTNRS-PREVENT PRESSURE BUILD-UP/AUTO IGNIT/EXPLOS. IRRIT VAPORS W/COMBUSTN Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD TIGHT-MAY EXPLODE W/HEAT. ISOLATE FROM HEAT/IGNIT SOURCES. SPECIAL PRECAUTION W/APPLIC TO HOT SURFACES. OVEREXPOSURE-HEALTH HAZ-SYMPTOMS DELAYED
========= Accidental Release Measures ===========
Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.
=========== Handling and Storage ==============
Handling and Storage Precautions:STO RE IN BLDG THAT COMPLY W/OSHA 1910.106. AVOID STOR NEAR HIGH TEMP/FIRE/OPEN FLAMES/SPARK SOURCES. STORE IN TIGHTLY CLSD CNTNRS IN WELL VENT AREAS Other Precautions:KEEP CONTAINERS TIGHT AND UPRIGHT TO PREVENT LEAKAGE. PREVENT BREATHING OF VAPORS/SPRAY MIST. POSSIBLE ALLERGIC REACTION AVOID CONTACT WITH EYES AND SKIN. DO NOT INGEST. DO NOT HANDLE UNTIL MFR SAFET Y PRECAUTIONS ARE READ AND UNDERSTOOD.
====== Exposure Controls/Personal Protection ========
Respir

ZATION.

atory Protection: RESP FOR ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING-FRESH AIR SUPPLIED). OBSERVE OSHA REG. PROVIDE VENT-KEEP EXPOS LEVELS BELOW PEL. VAPOR PARTIC RESP (TC23C NIOSH/MSHA) WHERE DEMONSTRATED THAT VAPOR LE VELS BELOW TEN TIMES APPLIC EXPOS LIMITS Ventilation: UTILIZE EXHST VENT TO KEEP AIRBORNE CONC OF

SOLVENT/HDI/POLYISOCYANATES BELOW RESPECTIVE TLV'S. RMV ALL IGNIT SOURCES

Protective Gloves: COTTON-NEOPRENE-RUBBER POLYETHYLENE

Eve Protection: SPLSH GUARD/SIDE-FACE

SHIELD/CHEM GOGGLE

Other Protective Equipment: THE USE OF LONG SLEEVE AND LONG LEG CLOTHING IS RECOMMENDED. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM. SMOKE IN SMOKING AREAS ONLY.

Supplemental Safety and Health

	Physical/Chemical Properties	=======================================
HCC:F2		
Dailing Dt.D.D. Tayti260	460E	

Boiling Pt:B.P. Text:260-460F Vapor Density:> THAN AIR Spec Gravity:1.02521

Evaporation Rate & Dr. Reference: 0.44 X N-

BUTYL ACETATE

Solubility in Water: INSOLUBLE

Appearance and Odor: AMBER LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:45.0

=======================================	Stability a	nd Reactivity	Data	=======================================
---	-------------	---------------	------	---

Stability Indicator/Materials to Avoid:YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid: CONTACT WITH MOISTURE, MATERIAL WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES.

Hazardous Decomposition Products:BY HIGH HEAT/TEMPERA

TURE: CARBON

MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN, TRACES OF HCN AND HDI

	Disposal Considerations	
--	-------------------------	--

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/FEDERAL-STATE-LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLED W/CARE-DUE TO PRODUCT RESIDUE AND FLAMMABLE VAPOR. DO NOT INCINERATE CLOSED CONTAINER S. EPA HAZARDOUS WASTE NUMBER/CODE: D001-F003-F005

Disclaimer (provided with this information b

y the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.