

FISKE BROTHERS REFINING CO -- LUBRIPLATE 105 -- 9150-00-868-0134

=====
Product Identification
=====

Product ID:LUBRIPLATE 105

MSDS Date:05/01/1987

FSC:9150

NIIN:00-868-0134

MSDS Number: BQGPQ

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150 / FAX 201-589-4432

Emergency Phone Num:201

-589-9150

Preparer's Name:ROBERT J. SIBILIA

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENTS

Other REC Limits:NON

E SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING EYES MAY CAUSE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND F

UMES SHOULD BE

MINIMIZED. THIS PRODUCT HAS A LOW ORDER OR ACUTE ORAL TOXICITY, ASPIRATION HAZARD.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:SKIN IRRITATION, EYE IRRITATION, ASPIRATION HAZARD, MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First

Aid:EYES:FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, CONTACT PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHING. FLUSH WITH WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, CONTACT DOCTOR IMMEDIATE LY. INHALATION: REMOVE TO FRESH AIR. IFSYMPOMS OCCUR, CONTACT PHYSICIAN. INGESTION: DO NOT INDUCE VOMTING. CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>360F,>182C

Lower Limits:0.9%

Upper Limits:

7.0%

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY (FOG).

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . COOL EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE. WASH REMA

INNER WITH SUITABLE

PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWER AND WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS.

Protective Gloves:USE OIL-RESISTANT GLOVES IF NEEDED.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:USE OIL RESISTANT APRON IF NEEDED.

Work Hygienic Practices:REMOVE OIL SOAKED CLOTHING AND LAUNDRER BEFORE

REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.945 - 0.965

Evaporation Rate & Reference: