

NUODEX INC -- ANDEROL 401D SYNTHETIC INSTRUMENT OIL (P/N -- 1650-00-830-2781

=====
Product Identification
=====

Product ID:ANDEROL 401D SYNTHETIC INSTRUMENT OIL (P/N

MSDS Date:05/14/1986

FSC:1650

NIIN:00-830-2781

MSDS Number: BQWLS

=== Responsible Party ===

Company Name:NUODEX INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08854

Country:US

Info Phone Num:201-763-7173

Emergency Phone

Num:201-763-7173

CAGE:GO026

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

Company Name:NUODEX INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08854

Phone:(201) 763-7173

CAGE:GO026

Company Name:STEWART WARNER SOUTH WIND CORP

Box:City:INDIANAPOLIS

State:IN

ZIP:46241-5534

Country:US

Phone:317-243-7367

CAGE:78385

=====
Composition/Information on Ingredie

nts =====

Ingred Name:NON HAZARDOUS INGREDIENTS

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED BY M.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE IRRITATION, NAUSEA AND VOMITING.

Effects of Overexposure:IRRITATION,NAUSEA,VOMITING

Medical Cond Aggravated by Exposure:NONE GIVEN.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED. EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS PERSIS T. INGESTION:DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF WATER. GET MEDICAL HELP IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>450F,>232C

Extinguishing Media:WATER SPRAY,DRY CHEM,FOAM,CARBON DIOXIDE

Fire Fighting Procedures:BURNING WILL PRODUCE TOXIC FUMES. WEAR SLF-CONTND BREATH APPARATUS & FULL TURN-OUT GEAR TO FIGHT FIRE. AVOID SPREADING LIQUID & FIRE BY WATER FLOODING.

Unusual Fire/Explosion Hazard:EXPOS TO HEAT BUILDS UP PRESSURE IN CLOSED CONTNRS. COOL W/WATER SPRAY.

===== Accidental Release Measures =====

Spill Release Pr

cedures:COVER WITH AN INERT ABSORBENT MATERIAL & PLACE
IN DISPOSAL CONTAINER. KEEP FROM CONTAMINATING ANY
LAKES,STREAMS,PONDS OR UNDERGROUND WATER SUPPLY.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE OIL ABOVE MAX RECOMMENDED
OPERATING TEMP OF 450F/232C. MAY SOFTEN SOME PLASTIC & PAINT
SURFACES.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:N

ONE NORMALLY REQUIRED. USE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED OR WHEN
SPRAYING OR USING IN CONFINED SPACES, OR IF OVERHEATED.

Ventilation:LOCAL EXHAUST & GEN MECH RECOMMENDED

Protective Gloves:IMPERVIOUS

Eye Protection:CHEM SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:EYE WASH FOUNTAIN;SAFETY SHOWER

Work Hygienic Practices:DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH
THIS PRODUCT.

Supplemental Safety and Health

===== Physi
cal/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>660F,>349C

Vapor Pres: