

LOCTITE CORP AUTOMOTIVE & CONS -- 44581 FAST CURE EPOXY 45 PART B

=====

MSDS Safety Information

=====

FSC: 8040

NIIN: 01-046-5061

MSDS Date: 03/26/1991

MSDS Num: BRBNN

Product ID: 44581 FAST CURE EPOXY 45 PART B

MFN: 02

Kit Part: Y

Responsible Party

Cage: DO429

Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP

Address:

4450 CRANWOOD CT

City: CLEVELAND OH 44128-4004

Info Phone Number: 216-663-3011

Emergency Phone Number: 800-321-9188

Preparer's Name: KATHRYN A. HOLEN

Review Ind: Y

Published: Y

=====

Preparer Co. when other than Responsible Party Co.

=====

Cage: DO429

Assigned Ind: Y

Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP

Address: 4450 CRANWOOD COURT

City: CLEVELAND OH 44128

=====

=====

Contractor Summary

=====

Cage: DO429

Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP

Address: 4450 CRANWOOD COURT

City: CLEVELAND OH 44128

Phone: (216) 663-3011

Cage: 62377

Name: PERMATEX INDUSTRIAL

Address: HARTFORD SQUARE N 10 COLUMBUS BLVD

City: HARTFORD CT 06106

Phone: 877-376-2839

=====

Item Description Information

=====

=====

Item Manager: GSA
Item Name: ADHESIVE
Unit of Issue: KT
UI Container Qty: 0

=====

Ingredients

=====

Name: POLYMERCAPTAN
% Wt: 30-35

Cas: 1344-28-1
RTECS #: BD1200000
Name: ALUMINUM OXIDE, BAUXITE, ALUMINA, DIALUMINUM TRIOXIDE
% Wt: 45-50
OSHA PEL: 15 MG/M3 TDUST
ACGIH TLV: 10 MG/M3 TDUST; 9293

Name: SUBSTITUTED AMINOPHENOL
% W
t: 5-10

Name: AROMATIC PLASTICIZER
% Wt: 5-10

Cas: 100-42-5
RTECS #: WL3675000
Name: STYRENE, (MONOMER), SUSPECTED ANIMAL CARCINOGEN BY IARC & ACGIH
% Wt: <5
Other REC Limits: 50 PPM
OSHA PEL: 100 PPM
ACGIH TLV: S,50PPM/100STEL;9293
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 7631-86-9
RTECS #: VV3100000
Name: SILICON DIOXIDE, CELITE 322
% Wt: 1-3
OSHA PEL: 80 MG/CUM
ACGIH TLV: 0.2 MG/CUM

Cas: 107-21-1
RTECS #: KW2975000
Name: ETHYLENE GLYCOL, GLYCOL
% Wt: 1-3
Other REC Limits: 10 MG/CUM
ACGIH TLV: C 127 MG/CUM
EPA Rpt Qty: 1 LB
DOT Rpt Qty: 1 LB

=====

Health Hazards Data

=====

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: YES
OSHA: NO
Effects of Exposure: EYES: IRRITATION. SKIN: SENSITIZATION OR DERMA
TITIS.

INHALATION: PULMONARY EFFECTS.
Explanation Of Carcinogenicity: SEE INGREDIENTS
First Aid: INGESTION: DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR.
SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MIN.
OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====

Handling and Disposal

=====

Spill Release Procedures: SOAK UP W/INERT ABSORBENT.
Waste Disposal Methods: LANDFI
LL OR INCINERATE IN ACCORDANCE W/LOCAL, FEDERAL
& STATE REGULATIONS.
Handling And Storage Precautions: STORE <110F TO PRESERVE SHELF LIFE. AVOID
CONTACT W/EYES & SKIN.

=====

Fire and Explosion Hazard Information

=====

Flash Point Method: TCC
Flash Point Text: >200F
Extinguishing Media: CO2, FOAM OR DRY CHEMICAL

=====

Control Meas

ures
=====

Ventilation: SUFFICIENT TO MAINTAIN VAPOR CONCENTRATION BELOW TLV.
Protective Gloves: RUBBER OR PLASTIC
Eye Protection: SAFETY GLASSES
Supplemental Safety and Health: INHALATION OF PURE SILICON DIOXIDE DUST HAS BEEN SHOWN TO CAUSE PULMONARY EFFECTS.

=====

Physical/Chemical Properties
=====

B.P. Text: >300F
Vapor Pres: <5
Solubi
lity in Water: SLIGHT
Appearance and Odor: WHITE & BLACK PASTE; SULFUR ODOR.

=====

Reactivity Data
=====

Stability Indicator: YES
Hazardous Polymerization Indicator: NO

=====

Toxicological Information
=====

=====

Ecological Information
=====

=====

=====

MSDS Transport Information
=====

=====

Regulatory Information
=====

=====

Other Information
=====

=====

=====

HAZCOM Label
=====

Product ID: 44581 FAST CURE EPOXY 45 PART B
Cage: DO429
Assigned IND: Y
Company Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP
Street: 4450 CRANWOOD COURT
City: CLEVELAND OH
Zipcode: 44128
Health Emergency Phone: 800-321-9188
Label Required IND: Y
Date Of Label Review: 07/01/1993
Status Code: C
Label Date: 07/01/1993
Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: CAUTION
Health Ha

zard: Slight
Contact Hazard: Slight
Fire Hazard: Slight
Reactivity Hazard: None
Hazard And Precautions: EYES: IRRITATION. SKIN: SENSITIZATION OR DERMATITIS.
INHALATION: PULMONARY EFFECTS. TARGET ORGANS: SKIN, LUNGS. CARCINOGEN:
STYRENE. TH. TARGET ORGANS: CENTRAL NERVOUS SYSTEM, KIDNE
YS, HEART, BRAIN, BLOOD, SKIN. CARCINOGEN: SILICA DIOXIDE.

=====

Disclaimer (provided with this information by the compiling agencies): This
informat

ion is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a milit

ary or civilian employee of the

United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.