

TEXACO INC. -- 00375 UNLEADED PLUS GASOLINE -- 9130-00-148-7102

===== Product Identification =====

Product ID:00375 UNLEADED PLUS GASOLINE

MSDS Date:10/24/1990

FSC:9130

NIIN:00-148-7102

MSDS Number: BRFLL

==== Responsible Party ====

Company Name:TEXACO INC.

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Info Phone Num:914-831-3400

Emergency Phone Num:914-831-3400

Preparer's Name:M.J. VONALLM

EN

CAGE:38431

==== Contractor Identification ====

Company Name:DIGITAL CONTROL SYSTEMS INC

Address:3160 GRAND MARAIS E

Box:City:WINDSOR, N8W 4W5

State:ON

Country:CN

Phone:NONE

CAGE:38431

Company Name:SCHULTE OIL CO

Address:1516 S ROCK ISLAND

Box:188

City:EL RENO

State:OK

ZIP:73036

Country:US

Phone:405-262-3120

CAGE:4R019

Company Name:TEXACO INC

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Phone:914-831-3400

CAGE:7B131

===== Composition/Information on Ingredients =====

Ingred Name:BENZENE (SARA III)
CAS:71-43-2
RTECS #:CY1400000
Fraction by Wt: 1-3.99%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1PPM/5STEL;1910.1028
ACGIH TLV:10 PPM; A2; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 4-10.99%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fractio
n by Wt: 1-3.99%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 4-10.99%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III)
CAS:95-63-6
RTECS #:DC3325000
Fraction by Wt: 1-3.99%
Other REC Li

mits: NONE SPECIFIED
OSHA PEL: 25 PPM
ACGIH TLV: 25 PPM; 9192

Ingred Name: METHYL TERT-BUTYL ETHER (SARA III)
CAS: 1634-04-4
RTECS #: KN5250000
Fraction by Wt: 0-15%
Other REC Limits: NONE SPECIFIED
EPA Rpt Qty: 1 LB
DOT Rpt Qty: 1 LB

Ingred Name: GASOLINE
CAS: 8006-61-9
RTECS #: LX3300000
Fraction by Wt: 95-99.9%
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 300 PPM/500 STEL
ACGIH TLV: 300 PPM/500 STEL; 9293

Ingred Name: ALIPHATIC PETROLEUM SOLVENT
CAS: 8008-20-6
RTECS #: OA5500000
Fraction by Wt: .01-.09%
Other
REC Limits: NONE RECOMMENDED
OSHA PEL: 400 PPM PETR. DIST.
ACGIH TLV: 400 PPM RUBBER SOLV.

===== Hazards Identification =====

LD50 LC50 Mixture: ORAL LD50 (RAT) = 18.75 ML/KG
Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO
Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: YES
Health Hazards Acute and Chronic: YES: SLIGHT TO MODERATE
IRRITATION. SKIN: MODERATELY IRRITATING. DERMALLY ABSORBED; LD50 DERMAL
RABBIT > 5 MG/KG. INHAL: IRRITATES EYES, NOSE, THROA

T. CAUSES CNS EFFECTS.

INGEST: MAY CAUSE LUNG DAMAGE IF VOMITTED AFTER
SWALLOWING. CHRONIC-GASOLINE VAPORS MAY CAUSE LIVER AND KIDNEY
DAMAGE.

Explanation of Carcinogenicity: CONTAINS B [71-43-2] WHICH IS
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure: SKIN: REDNESS, EDEMA, DRYING. INHAL: CNS
EFFECTS-DIZZINESS, BLUISH SKIN COLOR.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

=====
First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: REMOVE
CONTAMINATED CLOTHING;WASH EXPOSED AREA WITH SOAP AND WATER.
INGESTION: DO NOT INDUCE VOMITING! CALL A PHYSICIAN. INHALATION:
REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION OR OXYGEN
IF NEEDED. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:-40F,-40C
Lower Limits:1.4 %
Upper Limits:7.6 %
Extinguishing Media:DRY CHEMICAL, FOAM
, CARBON DIOXIDE.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE ON FLAMES, BUT SHOULD
BE USED TO COOL FIRE-EXPOSED CONTAINERS. USE A SELF-CONTAINED
BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND TRAVEL
ALONG THE FLOOR;FLOWING GASOLINE GENERATES STATIC ELECTRICITY
...THIS PRESENTS A FLASHBACK HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION
SOURCES. VENTILATE AREA.

AVOID BREATHING VAPORS. USE SCBA FOR LARGE SPILLS OR IN CONFINED
AREAS. CONTAIN SPILL IF POSSIBLE. REMOVE WITH NON-FLAMMABLE
ADSORBANT(EG.DIATOMACEOUS EARTH);PLACE IN APPROPRIATE CONTAINER
FOR DISPOSAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:TRANSPORT, HANDLE AND STORE IN
ACCORDANCE WITH OSHA REGULATION 1910.106 AND APPLICABLE D.O.T.
REGULATIONS.

Other Precaut

ions:DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF
SWALLOWED!

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SCBA OR SUPPLIED AIR RESPIRATORY PROTECTION
REQUIRED FOR ENTRY INTO TANKS, VESSELS, OR OTHER CONFINED SPACES.

Ventilation:ADEQUATE TO MEET PERMISSIBLE CONCENTRATIONS.

Protective Gloves:NITRILE, TEFLON, VITON

Eye Protection:CHEMICAL-TYPE GOGGLES, FACE SHIELD

Other Protective Equipment:PROTECTIVE CLOTHING SUCH AS UNIFORMS,
COVERAL

LS OR LAB COATS SHOULD BE WORN.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:>90F,>32C

Vapor Pres:465-775

Vapor Density:3 - 4.0

Spec Gravity:0.7 - .77

Evaporation Rate & Reference:N.D.

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID;LIGHT STRAW TO L

IGHT RED;GASOLINE ODOR

Percent Volatiles by Volume:100 %

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HEAT, SPARKS, FLAME AND OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:TOXIC LEVELS OF CARBON MONOXIDE, CARBON DIOXIDE, IRRITATING ALDEHYDES AND KETONES.

===== Disposal Considerations =====

Waste Disposal Methods:CONSIDERED RCRA

HAZARDOUS WASTE;IT IS

TOXIC(BENZENE) AND IGNITABLE(FP=-40F).DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek

competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.