Product ID:NON FLAMING ENAMEL, TPD 24607 WHITE 27880 MSDS Date:03/12/1993 FSC:8010 NIIN:01-344-5100 **MSDS Number: BRGPG** === Responsible Party === Company Name: CRAWFORD LABS, INC Address:4165 S EMERALD AVE City:CHICAGO State:IL ZIP:60609 Country:US Info Phone Num:312-376-7132 Emergency Phone Num:312-433-1307 Preparer's Name: DAVID SCHMETTERER CAG E:5V430 === Contractor Identification === Company Name: CRAWFORD LABORATORIES, INC Address:4165 SOUTH EMERALD AVENUE Box:City:CHICAGO State:IL ZIP:60609 Country:US Phone:312-376-7132 CAGE:5V430

Ingred Name:100 SOLVENT (VAPOR PRESSURE 9. MM HG) CAS:64742-95-6 Fraction by Wt: 2.8% Other REC Limits:NONE SPECIFIED OSHA PEL:50 PPM ACGIH TLV:50 PPM

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III) (VAPOR PRESSURE 1.7 MM HG) CAS:95 -63-6 RTECS #:DC3325000 Fraction by Wt: 2.6% Other REC Limits:NONE SPECIFIED ACGIH TLV:25 PPM

Ingred Name:TRIMETHYLBENZENES (VAPOR PRESSURE 1.8 MM HG) CAS:25551-13-7 RTECS #:DC3220000 Fraction by Wt: 2.6% Other REC Limits:NONE SPECIFIED ACGIH TLV:25 PPM

Ingred Name:MINERAL SPIRITS/66 (VAPOR PRESSURE 3.4 MM HG) CAS:8032-32-4 RTECS #:OI6180000 Fraction by Wt: 9.0% Other REC Limits:NONE SPECIFIED OSHA PEL:500 PPM ACGIH TLV:100 PPM

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fra ction by Wt: 1.2% Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ZINC SULFIDE (RELEASED BY SANDING DRIED PAINT FILM) CAS:1314-98-3 Fraction by Wt: 0.45% Other REC Limits:NONE SPECIFIED

Ingred Name:PETROLEUM DISTILLATES Fraction by Wt: 2.2% Other REC Limits:NONE SPECIFIED ACGIH TLV:100 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chr

onic:ACUTE TOXICITY, RESULTING IN HEADACHE, DIZZINESS, NAUSEA, UNCONSCIOUSNESS. SEVERE EYE IRRITATION POSSIBLY RESULTING IN PERMANENT DAMAGE. IRRITATED MUCOUS MEMBRANES. VOMITING DUE TO INGESTON. DEFATTING AND DRYING OF SKIN, MAY RESULT IN DERMATITIS & IRRITATION. SENSITIZATION AFTER REPEATED CONTACT. Explanation of Carcinogenicity:RISK OF CANCER DEPENDS ON DURATION AND LEVEL OF EXPOSURE.

First Aid:EYE:FLU

SH W/WATER 15 MIN,HOLD EYELID OPEN. GET MED AID.INHAL:REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING DIFFICULT,ARTIF RESPIRTN IF NOT BREATHING. GET MED AID.KEEP WARM & COMFORTABLE. NOTHING BY MO UTH TO UNCONSCIOUS. INGEST:CALL DR IMMED.INDUCE VOMIT ONLY ON DR'S INSTRUCTS.KEEP HEAD BELOW HIPS (PREVENT ASPIRATN).SKIN:FLUSH W/WATER REMOVING CONTAM CLOTH.WASH W/SOAP & WATER.IF IRRIT, GET MED AID.

Flash Poin t Method:TCC Flash Point:100F,38C Lower Limits:0.9 Extinguishing Media:FOAM, CO2, DRY CHEMICAL Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS COOL, & TO KEEP FLAMMABLE STRUCTURES WET. DO NOT ENTER FIRE AREA W/O PROPER PROTECTION (HAZARD DECOMP PRESENT). Unusual Fire/Explosion Hazard:WATER PRESSURE MAY SPREAD A COMBUSTIBLE LIQUID FIRE. SEALED CONTAINERS MAY EXPLODE IF OVERHEATED.

Spill Release

Procedures:WARNING - COMBUSTIBLE. ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. WEARING PROTECTIVE CLOTHING. SOAK UP WITH AN ABSORBENT AND PLACE IN NON-LEAKING CONTAINE RS. SEAL TIGHTLY FOR PROPER DISPOSAL. EPA #D001.

Handling and Storage Precautions:HAZARD-COMBUSTBL.STORE IN COOL,DRY PLACE IN BLDGS FOR COMBUST LIQ.EVALUATE USE IN ELEVATED TEMP PROCESSES TO AS SURE SAFETY.HOT ORGANIC CHEM VAPOR APT* Other Precautions:*TO SUDDEN COMBUSTN WHEN MIXED W/AIR.IGNIT TEMPS DECREASE W/INCREASING VAPOR VOLUME & VAPOR/AIR CONTACT TIME & INFLUENCED BY PRESSR CHANGES.IGNIT MAY OCCUR AT ELEVATD TEMPS,ESP WHEN VACUUM IF SUDDEN A IR INGRESS/ESCAPE OF VAPOR TO ATMOSPHERE

Respiratory Protection:USE NIOSH APPROVED ORGANIC VAPOR RESPIRATORS WHERE VENTILATION IS INADEQUATE. Ventilation:M UST PROVIDE ADEQUATE VENTILATION. Protective Gloves:USE RUBBER GLOVES Eye Protection:WEAR APPROVED SAFETY GOGGLES Other Protective Equipment:HAVE EYE BATH AND SAFETY SHOWER AVAILABLE. Work Hygienic Practices:DO NOT REUSE CLOTHING OR SHOES UNTIL CLEANED. Supplemental Safety and Health

HCC:F4 Boiling Pt:B.P. Text:308 TO 396F Vapor Density:> AIR Spec Gravity:1.61 Viscosity:90 KU Evaporation Rate & amp; Reference:0.1 X N-BUTYL ACE TATE Solubility in Water:SLIGHT Appearance and Odor:WHITE LIQUID, SOLVENT ODOR Percent Volatiles by Volume:27.7 Corrosion Rate:NOT CORR

Stability Indicator/Materials to Avoid:YES MAY BE INCOMPATIBLE WITH STRONG OXIDIZING AGENTS AND STRONG ALKALIES. Stability Condition to Avoid:AVOID HEAT, SPARKS, OPEN FLAMES, & INCOMPATIBILITIES. ALSO AIRCRAFT TRANSPORT MUST BE IN ACCORD W/APPLICABLE REGULATIONS Hazardous Decomposition Products:INCOMPLETE COMBUSTION FOR PRODUCTS LIKE THIS MAY FORM HIGHLY POISONOUS CARBON MONOXIDE AND OTHER TOXIC GASES.

Conditions to Avoid Polymerization: AVOID HEAT, SPARKS, OPEN FLAMES, & INCOMPATIBILITIES.

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT LOCAL, STATE AND FEDERAL REGULATION. CONTACT AN APPROVED DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.