

DEVOE COATINGS COMPANY -- P/N 2190910 DEVRAN 219 CLEAR CONVERTER -- 8010-01-326-9704
===== Product Identification =====

Product ID:P/N 2190910 DEVRAN 219 CLEAR CONVERTER

MSDS Date:05/06/1993

FSC:8010

NIIN:01-326-9704

Kit Part:Y

MSDS Number: BSSFB

=== Responsible Party ===

Company Name:DEVOE COATINGS COMPANY

Address:4000 DUPONT CIRCLE

City:LOUISVILLE

State:KY

ZIP:40207

Country:US

Info Phone Num:502

-897-9861

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:1HK86

=== Contractor Identification ===

Company Name:DEVOE COATINGS CO

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:1HK86

===== Composition/Information on Ingredients =====

Ingred Name:METHYL N-AMYL KETONE (VAPOR PRESSURE 2.14 MM HG)

CAS:110-43-0

RTECS #:MJ5075000

Fraction by Wt: 15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM

Ing

red Name:N-BUTYL ALCOHOL (VAPOR PRESSURE 4.2 MM HG) (SARA III)
(CERCLA 103A)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:50 PPM CEILING

ACGIH TLV:50 PPM CEILING

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:POLYAMIDE RESIN (VAPOR PRESSURE 120F/NEAR FIRE/FLAME.STORE LRG QTY IN
BLDG(COMPLY

W/OSHA 1910.106).KEEP CNTNR CLSD.DON'T TRANSFR TO BOTTLE/UNLABELLED
CNTNR.IF P ART OF KIT,OBEY HZD CAUTION OF BOTH PRTS

=====
Exposur
e Controls/Personal Protection =====

Respiratory Protection:DON'T BREATHE VAPOR,SPRAY,SAND DUST.SPRAY IN
OUTDOOR/OPEN AREAS,& DURING/SAND DUST,NIOSH/MSHA MECHAN FILTER(RMV
SOLID PARTICLES).RESTRICTED VENT,NIOSH/MSHA CHEM/MECHANICAL
FILTER(RMV PARTICULATES & VA POR).CONFINED,AIR SUPPLY RSPRTR/HOODS.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST TO KEEP CONTAM
CONCENTRATIONS BELOW TLV/PEL. PREVENT BLDUP IN LOWER LEVELS OF WORK
AREA.

Protective Gloves:SOLVENT IMPERMEABLE
GLOVES

Eye Protection:SOLVENT RESIST SFTY EYEWEAR W/SIDE SHLDS

Other Protective Equipment:DO NOT GET ON SKIN. SOLVENT IMPERMEABLE
CLOTHING & BOOTS TO PREVENT SKIN CONTACT ARE RECOMMENDED.

Work Hygienic Practices:REMOVE AND WASH SOILED CLOTHING BEFORE REUSE.
WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

=====
Physical/Chemical Properties =====

Boiling Pt:B.P. Text:244 TO 340F

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER TH

AN ETHER

Percent Volatiles by Volume:59.03

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:MAY CAUSE TOXIC FUME WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND

FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.