

R M ENGINEERED PRODUCTS INC. -- PK 1006/43050387/MIL-P-24377A -- 5330-00-197-9641

=====
Product Identification
=====

Product ID:PK 1006/43050387/MIL-P-24377A

MSDS Date:07/01/1991

FSC:5330

NIIN:00-197-9641

MSDS Number: BTTFV

=== Responsible Party ===

Company Name:R M ENGINEERED PRODUCTS INC.

Address:4854 O'HEAR AVE

Box:5205

City:NORTH CHARLESTON

State:SC

ZIP:29406

Country:US

Info Phone Num:803-744-

6261

Emergency Phone Num:803-744-6261

Preparer's Name:E. K. HANSON

CAGE:10009

=== Contractor Identification ===

Company Name:R M ENGINEERED PRODUCTS, INC.

Address:4854 O'HEAR AVENUE

Box:City:NORTH CHARLESTON

State:SC

ZIP:29405

Country:US

Phone:843-744-6261

CAGE:10009

=====
Composition/Information on Ingredients
=====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9394

Ingred

Name:AQUEOUS PTFE DISPERSION
CAS:116-14-3
RTECS #:KX4025000
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE: NONE UNDER NORMAL OPERATING
CONDITIONS. HOWEVER, IF DUST IS GENERATED, REPEATED EXPOSURE TO
ASBESTOS FIBERS COULD CAUSE LONG TERM DETRIMENTAL EFFECTS INCULDING
ASBESTOS
IS AND LUNG CANCER. CHRONIC: EFFECTS OF LONG TERM EXPOSURE
TO ASBESTOS FIBERS CAN CAUSE ASBESTOSIS AND LUNG CANCER.
Explanation of Carcinogenicity:CONTAINS A [1332-21-4] WHICH IS
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.
Effects of Overexposure:NONE UNDER NORMAL OPERATING CONDITIONS.
HOWEVER, EXPOSURE TO NUISANCE DUST/FIBERS AND TEFLON FUMES FROM
MACHINING OR HEATING CAN PRODUCE FLU LIKE SYMPTOMS WITH FEVER AND
CHILLS. SYMPTOMS USUALLY DISAPPEAR WITHIN
36 TO 48 HOURS WITH NO
TREATMENT. POSSIBLE IRRITATION TO EYES,NOSE,THROAT,UPPER
RESPIRATORY TRACT AND SKIN.
Medical Cond Aggravated by Exposure:CAN ENHANCE PROBLEMS SUCH AS ASMTA
AND OTHER ALLERGIC REACTIONS, SKIN AND EYE SENSITIVITY AND
PRE-EXISTING LUNG CONDITIONS.

=====
===== First Aid Measures =====

First Aid:AS WITH ANY EMERGENCY, MOVE TO FRESH AIR. GIVE ARTIFICIAL
RESPIRATION IF BREATHING HAS STOPPED. IF BREATHING IS DIFFICULT
GIVE
OXYGEN. SEEK MEDICAL ATTENTION. EYES: FLUSH WITH PLENTY OF
WATER (15 MIN) . IF SYMPTOMS PERSIST SEEK MEDICAL ATTENTION. SKIN:
FLUSH WITH PLENTY OF WATER (15 MIN). REMOVE CONTAMINATED CLOTHING.
IF SYPTOMS PERSISTS SEEK MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Extinguishing Media:WATER SPRAY, FOAM, DRY CHEMICAL, CARBON DIOXIDE.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND
FULL FACE-PIECE SELF-CONTAINED BREATH

ING APPARATUS. COOL FIRE

EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:TOXIC DECOMPOSITION FUMES, INCLUDING FLUORINATED OXIDE FUMES, MAY BE EVOLVED IN A FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:IF DUST OR RESIDUE IS GENERATED, VACUUM OR SWEEP IN SUCH A MANNER AS TO AVOID SPREADING. FOLLOW SAFETY PRECAUTIONS.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:AVOID CREATING EXCESSIVE DUST. FOLLOW GOOD INDUSTRIAL HOUSEKEEPING AND PERSONAL HYGIENE PRACTICES.

Other Precautions:WASH HANDS THOROUGHLY BEFORE EATING OR SMOKING (TO PREVENT CIGARETTE CONTAMINATION WHICH COULD LEAD TO POLYMER FUME FEVER).

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROVED FOR DUST/ FIBERS WHEN NEEDED.

Ventilation:USE LOCAL OR GENERAL EXHAUST TO REMOVE DUST/FIBERS TO STAY BELOW PEL.

Protective Gloves:COTTON, LEATHER, OR RUBBER IF NECESSARY.

Eye Protection:OSHA SAFETY GLASSES WITH SIDE SHIELDS.

Other Protective Equipment:NONE REQUIRED UNDER NORMAL OPERATING CONDITIONS. HOWEVER, IF DUST IS GENERATED, WEAR PROTECTIVE CLOTHING.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

PRODUCT IS CONSIDERED AN ARTICLE AS DEFINED BY OSHA HAZARD

COMMUNICATION STANDARD 29CFR1910.1200. THEREBY DOES NOT REQUIRE MSDS. PRODUCT IS NOT HAZARDOUS IN FORM SHIPPED OR ITS END USE. IF PRODUCT IS FURTHER PROCESSED,INCLUDING CUTTING,GRINDING,MACHINING CREATING DUST,HAZARDOUS LEVELS OF INGREDIENTS COULD BE GENERATED.

===== Physical/Chemical Properties =====

HCC:T6

Decomp Temp:Decomp Text:550F,288C

Appearance and Odor:WHITISH COLORED SOLID. ODORLESS.

===== Stability and Reactiv

ity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS AND OTHER INTERHALOGEN COMPOUNDS.

Stability Condition to Avoid: TEMPERATURES OVER 250C.

Hazardous Decomposition Products: VARIOUS FLUOROCARBON FUMES, CARBON MONOXIDE AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.