View NSN Online: https://aerobasegroup.jp/nsn/8010-00-297-0547

PRATT AND LAMBERT INC -- ENAMEL ALKYD LUST BLACK 37038 -- 8010-00-297-0547

Product ID:ENAMEL ALKYD LUST BLACK 37038

MSDS Date:03/29/1990

FSC:8010

NIIN:00-297-0547

MSDS Number: BTTGR === Responsible Party ===

Company Name: PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153 City:WICHITA State:KS

ZIP:67201 Country:US

Info Phone Num:316-733-1361

Emergency Phone Nu m:316-733-1361

Preparer's Name: W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027 Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: NAPHTHA, MEDIUM ALIPHATIC

CAS:64742-88-7 Fraction by Wt: 35%

Other REC Limits: NONE RECOMMENDED

Ingred Name: SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7 RTECS #:VV7330000 Fraction by Wt: 39C

Extinguishing

- Media:USE NFPA CLASS B FIRE EXTINGUISHERS DESIGNATED TO EXTINGUISH FLAMMABLE LIQUID FIRES. USE POLYMER FOAM FOR LARGE FIRES.
- Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP.
- Unusual Fire/Explosion Hazard:KEEP CONTAINERS CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS & FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

======== Accidental Release Measures ==========

Spill Release Procedures: KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITION SOURCES. DIKE & CONTAIN SPILL WITH INERT MATERIAL. TRANSFER LIQUIDS TO COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL, OR REMOVE WITH INERT ABSORBENT. U SE ONLY NON-SPARKING TOOLS.

========== Handling and Storage ==============

Handling and Storage Precautions:DO NOT STORE ABOVE 95 DEGREES F. STORE LARGE QUANTI

TIES IN COMPLIANCE WITH OSHA 29CFR1910.106.

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. DO NOT BREATHE SANDING DUST. EMPTY CONTAINER MUST NOT BE WASHED & RE-USED FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEI VING CONTAINER.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: PROPER SELECTION OF RESPIRATORY PROTECTION

DEPENDS UPON MANY FACTORS INCLUDING DURATION/LEVEL OF EXPOSURE AND

CONDITIONS OF USE. IN RESTRICTED VENTILATION AREAS A NIOSH CHEMICAL CARTRIDGE RESPIRATOR M AY BE REQUIRED.

Ventilation:PROVIDE GENERAL DILUTION & LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME & PATTERN TO MAINTAIN CONCENTRATIONS BELOW TLV Protective Gloves:SOLVENT IMPERMEABLE GLOVES ARE REQUIRED.

Eve Protection: WEAR SFAETY SPECTACLES.

Other Protective Equipment: NOT LIKELY TO BE NEEDED.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

NOTES TO PHYS

ICIAN: ANY TREATMENT THAT MIGHT BE REQUIRED FOR OVEREXPOSURE SHOULD BE DIRECTED TO THE CONTROL OF SYMPTOMS & THE CLINICAL CONDITIONS. FIRE: IF WATER IS USED, FOG NOZZLES ARE PREFERRED. OT HER PRECAUTIONS: DO NOT WELD/BRAZE/CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL.

======== Physical/Chemical Properties ==========

HCC:F4

Boiling Pt:B.P. Text:295-390F

Vapor Density:>AIR

Evaporation Rate & Deference: SLOWER THAN E

THER

Appearance and Odor:PAINT Percent Volatiles by Volume:82

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT, SPA RKS AND

FLAMES.

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL LAWS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS. RCRA CLASSIFICATION WOULD BE D001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.