View NSN Online: https://aerobasegroup.com/nsn/8030-00-579-8453

COURTAULDS AEROSPACE, INC -- PR-1440 B-2, ACCELERATOR -- 8030-00-579-8453

Product ID:PR-1440 B-2, ACCELERATOR

MSDS Date: 10/21/1993

FSC:8030

NIIN:00-579-8453

Kit Part:Y

MSDS Number: BVNBK === Responsible Party ===

Company Name: COURTAULDS AEROSPACE, INC

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Info Phone Num:818-240-2060

/818-549-7825

Emergency Phone Num:800-228-5635/800-424-9300 CHEMTREC

Preparer's Name: SEROJE HARTOONIANI

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

======= Composition/Information on Ingredients ========

Ingred Name: HYDROGENATED TERPHENYLS (VAPOR PRESSURE 1 MM HG)

CAS:61788-32-7 RTECS #:WZ6535000

Frac

tion by Wt: 31.477%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.5 PPM ACGIH TLV:0.5 PPM

Ingred Name: CARBON BLACK (LISTED AS REQ'D BY 29CFR1910:1200, FULL ENCAPSULATED--NON HAZARDOUS UNDER NORMAL CONDITIONS)

CAS:1333-86-4

RTECS #:FF5800000 Fraction by Wt: 5.673%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3

Ingred Name: MANGANESE DIOXIDE (SARA III)

CAS:1313-13-9

RTECS #:OP0350000 Fraction by Wt: 56.308%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 CEILING

AC

GIH TLV:5 AS MN MG/M3

Ingred Name:DIPHENYL GUANIDINE (GUANIDINE, N, N', DIPHENYL)

CAS:102-06-7

RTECS #:MF0875000 Fraction by Wt: 3.940%

Other REC Limits: NONE RECOMMENDED

Ingred Name: VOC PER EPA METHOD 24: 35 G/L (COMBINED PART A & B)

RTECS #:9999999VO

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification ================


Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:

EYE:SEVERELY IRRITATING.

SKIN:IRRITATION, IRRITATION ON MOIST SKIN. TOXIC BY ABSORPTION. MAY BE SENSITIZER. INHALATION:DIZZINESS, DROWSINESS, FATIGUE. MANGANESE PNEUMONITIS, MANGANESE POISONING. IRRIT ATION, MAY BE ABSORBED THRU LUNGS. INGESTION:APATHY, INSOMNIA, WEAKNESS IN LEGS, MUSCULAR TWITCHING, EMOTIONAL DISTRESS.

First Aid:EYES: FLUSH WITH LUKEWARM WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, CONS



LATL Spec Gravity:1.97

Viscosity:1220P#6@10RPM

Evaporation Rate & Evaporation R

Solubility in Water:SLIGHT

Appearance and Odor:BLACK PASTE

Percent Volatiles by Volume:0.0

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
EASILY OXIDIZABLE MATERIALS
Stability Condition to Avoid:NOT KNOWN
Hazardous Decomposition Products:OXIDES OF CARBON AND NITROGEN,
MANGANESE COMPOUNDS.

====== Disposal Considerations

Waste Disposal Methods:NOT A HAZARDOUS WASTE ACCORDING TO EPA REGULATIONS. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF SPILLAGE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizin g this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.