View NSN Online: https://aerobasegroup.jp/nsn/8030-00-753-5009

Product ID:PR-1440 A-2, BASE

MSDS Date:10/21/1993

FSC:8030

NIIN:00-753-5009

MSDS Number: BVNDL === Responsible Party ===

Company Name: COURTAULDS AEROSPACE INC

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Info Phone Num:818-549-7586 Emergency Phone Num:818-549-

7586

Preparer's Name: SEROJE HARTOONIANI

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

======= Composition/Information on Ingredients ========

Ingred Name:METHYL ETHYL KETONE (SARA III) (VAPOR PRESSURE 70 MM HG)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 8.145%

Other REC Limits: NONE RECOMMENDED

OSHA PE

L:200 PPM;STEL 300 PPM ACGIH TLV:200 PPM;STEL 300 PPM

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: PHENOLIC RESIN

CAS:9039-25-2

Fraction by Wt: 1.010%

Other REC Limits: NONE RECOMMENDED

Ingred Name:TITANIUM DIOXIDE (LISTED AS REQ'D BY 29CFR 1910:1200, FULLY ENCAPSULATED, NOT HAZARDOUS UNDER NORMAL CIRCUMSTANCES)

CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 2.597%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: CALCIUM CARBONATE (LIMESTONE) (LIS

TED AS REQ'D BY

29CFR1910:1200, FULLY ENCAPSULATED, NOT HAZARDOUS UNDER NORMAL

CONDITIONS) CAS:1317-65-3

RTECS #:EV9580000 Fraction by Wt: 27.918%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15.0 MG/M3 ACGIH TLV:10.0 MG/M3

Ingred Name: TOLUENE (SARA III) (VAPOR PRESSURE 23 MM HG)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 4.916%


Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:50 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:SH-TERMINATED POLYSULFI

DE (NON HAZARDOUS INGREDIENT)
CAS:109159-22-0 Other REC Limits:NONE RECOMMENDED
Other NEO Elimio. NOIVE NEOOMINIENDED
Ingred Name:POLYSULFIDE POLYMER (NON HAZARDOUS INGREDIENT)
CAS:68611-50-7 Other REC Limits:NONE RECOMMENDED
Other REC Limits.None Recommended
Ingred Name:VOC PER EPA METHOD 24: 264 G/L (COMBINED PART A & B) RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED
Other REC LITHIS.NONE RECOMMENDED
========= Hazards Identification ===========
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Haza
rds Acute and Chronic:EYE:BURNING, TEARING, REDDENING. TRANSIENT CORNEAL CLOUDING. IRRITATION. SKIN:REDNESS, BURNING,
DRYING & CRACKING SKIN. ALLERGIC RASH IN SENSITIZED. DERMATITIS.
INHALATION:DIZZINESS, DROWSINESS, FATIG UE, LIVER & KIDNEY DAMAGE.
COUGHING, CHEST PAIN, THROAT IRRIT, HEADACHE, ANESTHETIC & OTHER
CENTRL NERV SYSTEM EFFECTS. Effects of Overexposure:INGESTION: DROWSINESS, DIZZINESS, NAUSEA.
GASTROINTESTINAL IRRITATION. EFFECTS OF LONG TERM (CHRONIC) EXP
OSURE MAY CAUSE DISTURBANCE IN MEMORY, THINKING ABILITY, EMOTIONS AND COORDINATION.
======================================
First Aid:EYES: FLUSH WITH LUKEWARM WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, CONSULT PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF SY MPTOMS ARE PRESENT, CONSULT A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN. DO NOT INDUCE VOMITING.
==== Fire Fighting Measures ============
Flash Point Method:PMCC
Flash Point:62.0F,16.7C
Lower Limits:1.3
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEAT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:HIGH TEMPERATURE MAY CAUSE PRESSURE BUILDUP IN CLOSED CONTAINERS.
======== Accidental Release Measures =========
Spill Release Procedures:REMOVE ALL IGNITION



Supplemental Safety and Health

KEY1:F3.

======== Physical/Chemical Properties ===========

HCC:F2

Boiling Pt:B.P. Text:175 TO 230F

Vapor Density:> AIR Spec Gravity:1.412

Viscosity:250P #6@10RPM Solubility in Water:SLIGHT

Appearance and Odor:BEIGE LIQUID

Per

cent volatiles by volume:22.8
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:NOT KNOWN Hazardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE, TRACES OF HYDROGEN SULFIDE
======= Disposal Considerations ==========
Waste Disposal Methods:EPA NO. D001 AND D-035 HAZARDOUS WASTE. DISPOSE OF IN COMPLIANCE WITH FEDERAL AND STATE REGULATION S.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

Disclaimer (provided with this information by the compiling agencies). This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular sit uation.