View NSN Online: https://aerobasegroup.com/nsn/8010-01-309-0329

HENTZEN COATINGS, INC -- MIL-P-53022B TY II CATALYST, 04489CEH, PART B -- 8010-01-309-0329

Product ID:MIL-P-53022B TY II CATALYST, 04489CEH, PART B

MSDS Date:06/16/1994

FSC:8010

NIIN:01-309-0329

Kit Part:Y

MSDS Number: BVNHQ === Responsible Party ===

Company Name: HENTZEN COATINGS, INC

Address:6937 W MILL ROAD

City:MILWAUKEE

State:WI ZIP:53218 Country:US Info Pho

ne Num:414-353-4200

Emergency Phone Num:414-353-4200/800-424-9300 CHEMTREC

Preparer's Name: JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name: HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI ZIP:53218 Country:US

Phone:414-353-4200

CAGE:09225

======= Composition/Information on Ingredients ========

Ingred Name:1-METHOXY-2-PROPANOL (SOLVENT)

CAS:107-98-2

RTECS #:UB7700000 Fraction by Wt: 45.016%

Other REC Limits:STEL: 150 PPM

OSHA

PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name: EPOXY RESIN

Fraction by Wt: 30-40%

Other REC Limits: NONE RECOMMENDED

Ingred Name: METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000 Fraction by Wt: 2.333%

Other REC Limits:STEL: 75 PPM

OSHA PEL:50 PPM ACGIH TLV:50 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SOLVENT) (SARA III)

CAS:95-63-6

RTECS #:DC3325000 Fraction by Wt: 4.468%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:25 PPM ACGIH TLV:25 PPM

ln

gred Name: AROMATIC HYDROCARBON (MIXTURE OF C8'S TO C10'S)

CAS:64742-95-6

Fraction by Wt: 8.797%

Other REC Limits:MFR'S LIMIT: 100 PPM


Ingred Name: VOC: 4.991 LBS/GAL 598.071 GRAMS/LITER

RTECS #:9999999VO

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification ============

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. IRRITANT. RESPIRATORY TRACT/MUCOUS MEMBRANE IRRITATION (HEADACHE,NAUSEA,



EMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES AND ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NONSPARKING TOOLS.

============ Handling and Storage ===========================

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP AWAY FROM SPARKS AND OPEN FLAME.

Other Precautions: DON'T INGEST. GROUN

D CONTAINERS WHEN POURING. AVOID
FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. USE WITH ADEQUATE
VENTILATION & RESPIRATORY EQUIP. AVOID PROLONGED BREATHING OF VAPOR
OR SPRAY MIST. AVOID PROLONGED/REPEATED SKIN CONTACT. *

===== Exposure Controls/Personal Protection ========

Respiratory Protection:OPEN AREA DURING SAND/GRINDING,USE NIOSH MECHAN FILTER RESPRTR.RESTRICTED VENT,WEAR NIOSH CHEM/MECHAN FILTER RESPRTR.CONFINED AREA,WEAR NIOSH AIR SUPPLIED RESPRTR/H OOD. USE

NIOSH RESPRTR WHEN FLAME CU TTING, WELDING, HAZING MAT'L COATED W/PROD

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENT TO KEEP AIR CONTAMINANT CONCENTRATION BELOW PEL & REMOVE DECOMP PRODUCTS Protective Gloves:REQUIRED FOR PROLONGED/REPEATED CONTACT.

Eye Protection:SAFETY EYEWEAR W/SPLASH GUARD/SIDESHIELD

Other Protective Equipment: USE PROTECTIVE SKIN CREAM WHERE CONTACT IS LIKELY. PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Work Hygienic Practice

s:WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH
HANDS BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED AREAS ONLY.
Supplemental Safety and Health

* OTHER PRECAUTIONS CONT'D: EMPTIED CONTAINERS MAY RETAIN HAZARDOUS RESIDUE OR EXPLOSIVE VAPORS. FOLLOW ALL HAZARDS PRECAUTIONS IN THIS DATA SHEET UNTIL CONTAINER IS THOROUGHLY CLEANED OR DESTROYED.

======== Physical/Chemical Properties ==========

Boiling Pt:B.P. Text:232 TO 418F

Decomp Temp:Decomp Text:400F,204C

Vapor P

res:15.00 @68F Vapor Density:> AIR Spec Gravity:0.97

Viscosity:20-40"#3 ZAHN

Evaporation Rate & Dryl Reference: FASTER THAN BUTYL ACETATE

Solubility in Water: NEGLIGIBLE

Appearance and Odor: OPAQUE LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:66.41

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION AS IN WELDING. FUMES MAY CO

NTAIN CARBON MONOXIDE AND DIOXIDE.

particular situation.

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE IN AN APPROVED FACILITY. EPA HAZARDOUS WASTE CODE: D001, IGNITABLE.

Disclaimer (provided with this information by the compiling agencies): This information is formu lated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their