

AMERICAN GAS AND CHEMICAL COMPANY,LTD -- LEAK-TEC 16-OX -- 6830-00-621-1820

=====  
Product Identification  
=====

Product ID:LEAK-TEC 16-OX

MSDS Date:03/22/1994

FSC:6830

NIIN:00-621-1820

MSDS Number: BVPZD

=== Responsible Party ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Info Phone Num:201-767-7300

Emergency Phon

e Num:201-767-7300

Preparer's Name:ELENA FROST

CAGE:03530

=== Contractor Identification ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Phone:201-767-7300

CAGE:03530

=====  
Composition/Information on Ingredients  
=====

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE  
PRESENT IN THIS PRODUCT.

RTECS #:9999999ZZ

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: INHALATION IS NOT CONSIDERED A  
LIKELY ROUTE OF EXPOSURE. SKIN AND EYE CONTACT MAY CAUSE MILD  
IRRITATION. INGESTION MAY CAUSE GI TRACT IRRITATION. CHRONIC: NONE  
SPECIFIED BY MANUFACTURER.  
Explanation of Carcinogenicity:NOT CONSIDERED TO BE A CARCINOGEN BY  
NTP, IARC, OR OSHA.  
Effects of Overexposure:INGESTED-NAUSEA, VOMITING, DIARRHEA.  
SKIN-REDNESS, ITCHING, DISCOMFORT. EYES: REDNESS, TEARING,  
DISCOMFORT.  
Medical Cond Aggravated by Exposure:NONE.

=====  
First Aid Measures  
=====

First Aid:EYES-FLUSH WITH WATER. SEEK MEDICAL ATTENTION IF IRRITATION  
PERSISTS. SKIN-WASH WITH SOAP AND WATER. INHALATION-REMOVE TO FRESH  
AIR. INGESTION-INDUCE VOMITING. CALL A PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Lower Limits:NONE  
Upper Limits:NONE  
Extinguishing Media:MEDIA APPROPRIATE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER  
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:FLUSH WITH WATER  
TO SANITARY SEWER SYSTEM.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. KEEP  
CONTAINERS CLOSED AND PLAINLY LABELED.  
Other Precautions:AVOID REPEATED OR PROLONGED CONTACT WITH SKIN. DO NOT  
GET IN EYES. SHELF LIFE IS 2 YEARS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NONE NORMALLY REQUIRED.IF ENGINEERING

**CONTROLS**

FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:NON-ABSORBENT GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AFTER CONTACT WITH THIS MATERIAL. DO NOT EAT, DRINK, OR SMOKE NEAR THIS MATERIAL.

Supplemental Safety and Health

MSDS REPRESENTS FORMULA CHANGE FROM PREVIOUS HMIS RECORD (PNI A). CURRENT MSDS MAKES NO REFERENCE TO WATER AS A COMPONENT. MSDS PRESENTED BY CAGE 03530 FOR CONTRACT NUMBER SP0450-95-C0093.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:17.5MMHG

Vapor Density:>1

Spec Gravity:1.01

pH:6-7.5

Evaporation Rate & Reference: