

DIVERSIFIED INDUSTRIAL CONCEPTS -- PHENOLIC VARNISH SPAR -- 8010-00-597-7856

===== Product Identification =====

Product ID:PHENOLIC VARNISH SPAR  
MSDS Date:01/11/1994  
FSC:8010  
NIIN:00-597-7856  
MSDS Number: BVTYC  
=== Responsible Party ===  
Company Name:DIVERSIFIED INDUSTRIAL CONCEPTS  
Address:228-A PATTERSON AVENUE  
City:HAMPTON  
State:VA  
ZIP:23669  
Country:US  
Info Phone Num:804-722-5691  
Emergency Phone Num:800-424-9300 (CHEMTREC)  
Preparer's Name:B GARDIER  
CAGE:0SN93

=== Contractor Identification ===  
Company Name:DIVERSIFIED INDUSTRIAL CONCEPTS  
Address:228-A PATTERSON AVENUE  
Box:City:HAMPTON  
State:VA  
ZIP:23669  
Country:US  
Phone:804-722-5691  
CAGE:0SN93

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS (SARA III) (VAPOR PRESSURE 2 MM HG @ 68F)  
CAS:64475-85-0  
RTECS #:PY8240000  
Fraction by Wt: 40-60%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM

===== Hazards Identification

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHAL: NASAL & RESP IRRITATION,  
DIZZINESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS,  
ASPHYXIATION. SKIN: IRRITATION. EYES: SEVERE IRRITATION, REDNESS,  
TEARING, BLURRED VISION. ABSORPTION: MAY CONTRI BUTE TO OVERALL  
EXPOSURE. INGEST: GASTROINTESTINAL IRRIT, NAUSEA, VOMITING,  
DIARRHEA. ASPIRATION INTO LUNGS MAY  
BE FATAL  
Effects of Overexposure:ACUTE: IRRITATION OF SKIN, EYES, MUCOUS  
MEMBRANES, DRYING, DEFATTING OF SKIN. AVOID INGESTION AND BREATHING  
OF VAPORS. CHRONIC: EYE, LIVER, KIDNEY, AND CENTRAL NERVOUS SYSTEM  
DAMAGE MAY OCCUR.  
Medical Cond Aggravated by Exposure:MAY PROVOKE ASTHMATIC RESPONSE IN  
PERSONS WITH ASTHMA WHO ARE SENSITIVE TO AIRWAY IRRITANT.

===== First Aid Measures =====

First Aid:IF SPILLED ON THE SKIN OR IN THE EYE, WASH WITH  
COPIOUS  
QUANTITIES OF WATER, CONTACT PHYSICIAN IF SPILLED IN THE EYE. IF  
INGESTED, DO NOT INDUCE VOMITING, KEEP PERSON WARM, QUIET AND  
CONTACT PHYSICIAN . BREATHING: REMOVE PERSON TO FRESH AIR. GIVE  
OXYGEN IF BREATHING DIFFICULT; GIVE ARTIFICIAL RESPIRATION IF  
BREATHING STOPS. KEEP PERSON WARM AND GET MEDICAL HELP.

===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:>104F,>40C  
Lower Limits:1.0  
Upper Limits:7.6  
Extinguishi  
ng Media:FOAM, CO2, DRY CHEMICAL  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH A  
FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE  
PRESSURE MODE WHEN FIGHTING FIRES.  
Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR MAY TRAVEL ALONG  
GROUND/BE MOVED BY VENT & IGNITED BY HEAT, PILOT LIGHTS, OTHER  
FLAMES & IGNITION SOURCES DISTANT FROM HANDLING POINT.

===== Accidental Release Measures =====

Spill Release Procedure

s:DIKE UP & CONTAIN SPILL WITH INERT MATERIAL,  
MOP UP AND PLACE MATERIAL INTO CONTAINERS. PREVENT RUN-OFF TO  
SEWER, STREAMS. NOTIFY AUTHORITIES.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE OR USE IN HIGH  
TEMPERATURE AREAS OR NEAR HEAT, SPARKS, OR FLAME. KEEP CLOSURE  
TIGHT AND CONTAINER UPRIGHT TO PREVENT LEAKAGE.

Other Precautions:STORE ONLY IN VENTILATED AREA. AVOID CONTACT WITH OR  
BREATHING OF VAPORS RELEASED DURING CURING PROCESS. DO NOT INGEST.  
AVOID CONTACT WITH SKIN & EYES. AVOID BREATHING OF VAPORS OR SPRAY  
MIST. OBSERVE ALL HAZARD PRECAUTIONS GIVEN IN MSDS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV OF PRODUCT/COMPONENT EXCEEDED, NIOSH/MSHA  
APPROVED AIR SUPPLIED RESPIRATOR ADVISED IN ABSENCE OF  
ENVIRONMENTAL CONTROL. OSHA REGS ALSO PERMIT OTHER RESPIRATORS  
UNDER SPECIFIC CONDITION. IMPLEMENT ENGINEERING/ADMINISTRATIVE  
CONTROLS.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL &/OR LOCAL EXHAUST)  
VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:WEAR RESISTANT GLOVES (NITRILE RUBBER).

Eye Protection:CHEMICAL SPLASH GOGGLES.SEE IF OTHERS OK

Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN  
CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING  
WASHROOM.

Supplemental Safety and Health

=====  
=== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:281 TO 388F

Vapor Density:> AIR

Spec Gravity:0.92 (WATER=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NOT SOLUBLE IN WATER

Appearance and Odor:CLEAR LIQUID WITH MINERAL SPIRITS SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NEVER USE WELDING O

R CUTTING TORCH ON OR  
NEAR DRUMS (EVEN EMPTY) BECAUSE PRODUCT (EVEN RESIDUE) CAN IGNITE  
EXPLOSIVELY.

===== Disposal Considerations =====

Waste Disposal Methods:SMALL:ALLOW VOLATILE PART TO EVAPORATE IN HOOD  
(ALLOW TIME FOR VAPOR TO CLEAR HOOD DUCT WORK).DISPOSE OF REMAINING  
MAT'L IN ACCORD W/REGS. LARGE:DESTROY BY LIQ  
INCINERATION.CONTAMINATED ABSORBNT MAY B E PUT IN LANDFILL IN  
ACCORD W/FED,STATE,LOCAL REGS

Disclaimer (provided with th  
is information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.