View NSN Online: https://aerobasegroup.jp/nsn/6850-01-353-4460

CANON USA INC -- CANON TONER BLACK FOR CLC 200/300 -- 6850-01-353-4460

Product ID:CANON TONER BLACK FOR CLC 200/300 MSDS Date:12/01/1991 FSC:6850 NIIN:01-353-4460 MSDS Number: BVZQB === Responsible Party === Company Name: CANON USA INC Address: ONE CANON PLAZA City:LAKE SUCCESS State:NY ZIP:11042 Country:US Info Phone Num:516-488-6700 Emergency Phone Num:800-424-93 00 (CHEMTREC) CAGE:1BA63 === Contractor Identification === **Company Name: CANON USA INC** Address:ONE CANON PLAZA Box:City:LAKE SUCCESS State:NY ZIP:11042 Country:US Phone:516-328-5600 CAGE:1BA63

Ingred Name:BISPHENOL A PROPYLENE OXIDE FUMARATE CAS:39382-25-7 Fraction by Wt: 85-95% Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSH A PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9394

Ingred Name:SALICYLIC ACID CHELATE CAS:72869-85-3 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture: PEL: 0.5 MG/M3 CHROMIUM Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION: TONER IS FINELY DIVIDED SOLID. DO NOT BREATHE DUST. EYES: NO SPECIFIC HAZARD IS K NOWN TO CANON, HOWEVER, ANY MATERIAL CONTACTING THE EYE MAY BE IRRITATING. SKIN: LOW HAZARD FOR INDUSTRIAL HANDLING. Explanation of Carcinogenicity:NOT CARCINOGENIC. Effects of Overexposure:NO DATA AVAILABLE FOR CHRONIC EFFECTS OF OVEREXPOSURE. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid:INHALATION: REMOVE FROM EXPOSURE TO FRESH AIR. EYE: OPEN EYE AND FLUSH WITH PLENTY OF WAT ER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER, INGE ST: DRINK SEVERAL GLASSES OF WATER, CALL A PHYSICIAN. Extinguishing Media: CARBON DIOXIDE, WATER, DRY CHEMICAL. Fire Fighting Procedures:NONE.

Unusual Fire/Explosion Hazard: THIS MATERIAL, LIKE MOST ORGANIC MATERIALS IN POWDER FORM, IS CAPABLE OF CREATING A DUST EXPLOSION.

====== Accident

Spill Release Procedures: SWEEP MATERIAL ONTO PAPER AND PLACE IN FIBER CARTON. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM CONTACT WITH OXIDIZING MATERIALS. STORE IN THE ROOM BELOW 40C. Other Precautions:NONE Respiratory P rotection:NONE REQUIRED. Ventilation: GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT. Protective Gloves:NONE REQUIRED. Eye Protection:NONE REQUIRED. Other Protective Equipment:NONE REQUIRED. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health NONE. HCC:N1 Melt/Freeze Pt:M.P/F.P Text:100-150C Spec Gravity:1.0-1.2(H20=1) Evaporation Rate & amp; Reference: NEGLIGIBLE (BUAC=1) Solubility in Water:NO **T SOLUBLE** Appearance and Odor: TONER IS FINE POWDER, SLIGHT PLASTIC ODOR. Percent Volatiles by Volume:NEG Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products: COMBUSTION WILL PRODUCE CARBON DIOXIDE AND, POSSIBLY TOXIC CHEMICALS SUCH AS CARBON MONOXIDE.

Wa

ste Disposal Methods:THE WASTE TONER COULD BE CONSIDERED AS PLASTIC WASTE. FOR INCINERATION, PACKAGE TONER ADEQUATELY. DO NOT DISPERSE TONER INTO FIRE. DISPOSE IN ACCORDANCE WITH FEDERAL, STATE &/LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurat e and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.