View NSN Online: https://aerobasegroup.jp/nsn/8010-01-374-4331

## DEL PAINT CORPORATION -- TT-E-2784 -- 8010-01-374-4331

Product ID:TT-E-2784 MSDS Date:10/01/1994

FSC:8010

NIIN:01-374-4331

MSDS Number: BVZRH === Responsible Party ===

Company Name: DEL PAINT CORPORATION

Address:3105 EAST RENO City:OKLAHOMA CITY

State:OK ZIP:73117 Country:US

Info Phone Num:405-672-1431

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name: ONEY

FLEMING CAGE:EO326

=== Contractor Identification ===

Company Name: DEL PAINT CORPORATION \*

Address:3105 EAST RENO City:OKLAHOMA CITY

State:OK ZIP:73117 Country:US

Phone: 405-672-1431

CAGE:EO326

Company Name: DEL PAINT MFG

Address:3105 EAST RENO Box:City:OKLAHOMA CITY

State:OK ZIP:73117 Country:US

Phone: 405-672-1431

CAGE:39934

======= Composition/Information on Ingredients ========

Ingred Name: EKTASOLVE EEH SOLVENT

CAS:1559-35-9

RTECS #:KK9625000 Fraction by Wt: 3.32% Other REC Limit s:NONE RECOMMENDED Ingred Name:BENZYL ALCOHOL CAS:100-51-6 RTECS #:DN3150000 Fraction by Wt: 3.32% Other REC Limits: NONE RECOMMENDED Ingred Name: DIMETHYLAMINOETHANOL LOW VOE CAS:108-01-0 RTECS #:KK6125000 Fraction by Wt: 0.38% Other REC Limits: NONE RECOMMENDED Ingred Name: NON-HAZARDOUS INGREDIENTS Fraction by Wt: 92.98% Other REC Limits: NONE RECOMMENDED Ingred Name: VOC: 1.8 LB/GL; 211 G/LTR RTECS #:9999999VO Other REC Limits: NONE RECOMMENDED ========= Hazards Identification == \_\_\_\_\_ Routes of Entry: Inhalation: NO Skin: YES Ingestion: YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: CAN CAUSE IRRITATION OF RESPIRATORY PASSAGES. Effects of Overexposure: INHALATION OF VAPOR OR MIST CAN CAUSE HEADACHES, NAUSEA, IRRITATION OF NOSE, THROAT, AND LUNGS. EYE CONTACT CAN CAUSE SLIGHT IRRITATION. PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE SLIGHT IRRITATION. Medical Cond Aggravated by Exposure: PRE-EXISTING LU NG DISEASE MAY BE AGGRAVATED BY EXPOSURE. First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES, CONSULT PHYSICIAN IF IRRITATION PERSISTS. SKIN CONTACT: SWALLOWED, GIVE 2 GLASSES OF WATER TO DRINK, CONSULT PHYSICIAN.

WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER. INGESTION: IF

Flash Point Method:SCC Flash Point:>212F,

>100C Autoignition Temp: Autoignition Temp Text: 216 F Lower Limits: NONE Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS (PRESSURE DEMAND MSHA/NIOSH APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard: MATERIAL CAN SPLATTER ABOVE 100C. POLYMER FILM CAN BURN. ======== Accidental Release Measures ============= Spill Release Procedures: KEEP SPECTATORS AWAY. F LOOR MAY BE SLIPPERY, USE CARE TO AVOID FALLING. CONTAIN SPILLS WITH INERT MATERIALS (SAND, EARTH). TRANSFER LIQUIDS AND SOLID DIKING MATERIAL TO SEPARATE SUITABLE CONTAINERS FO R RECOVERY/DISPOSAL. Neutralizing Agent:NONE ============ Handling and Storage =========================== Handling and Storage Precautions: KEEP FROM FREEZING. Other Precautions: DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN. ====== Exposure Controls/Personal Protection ======== Respi ratory Protection: APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATION. Ventilation: NORMAL, SUCH AS A FAN Protective Gloves: RUBBER Eve Protection: SAFETY GLASSES OR GOGGLES Other Protective Equipment: EYE WASH STATION. Supplemental Safety and Health ========= Physical/Chemical Properties =========== Boiling Pt:B.P. Text:212 TO 644F

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C Decomp Temp:Decomp Text:350F,177C

Vapor Pres:N

ONE

Vapor Density:> AIR

Spec Gravity: 1.01 (WATER=1)

pH:9 MAX

Viscosity:77-95 KU

Evaporation Rate & Evaporation R

Solubility in Water:SLIGHT

Appearance and Odor: GREEN LIQUID WITH SLIGHT ODOR

Percent Volatiles by Volume:60.6

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
THERE ARE NO KNOWN MATERIALS WHICH ARE INCOMPATIBLE WITH THIS PRODUCT.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:THERMAL
DECOMPOSITION MAY YIELD
ACRYLIC MONOMERS.

======= Disposal Considerations ===========

Waste Disposal Methods:KEEP SPILLS AND CLEANING RUN-OFF OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER. CONSULT FEDERAL, STATE, OR LOCAL AUTHORITIES FOR PROPER DISPOSAL PROCEDURES CONCERNING HEALTH AND ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.