View NSN Online: https://aerobasegroup.com/nsn/3439-01-008-7577

Product ID:SOLDER ALLOYS OF PB, SN, AG, BI, SB, AND IN MSDS Date:10/24/1990 FSC:3439 NIIN:01-008-7577 **MSDS Number: BWPZS** === Responsible Party === **Company Name: ALPHA METALS** Address:600 ROUTE 440 City: JERSEY CITY State:NJ ZIP:07304 Country:US Info Phone Num:201-434-6778 **Emergency Phon** e Num:201-434-6778/800-424-9300(CHEMTREC) CAGE:96613 === Contractor Identification === Company Name: FRYS METALS INC (FORMER ALPHA METALS) Address:600 ROUTE 440 Box:City:JERSEY CITY State:NJ ZIP:07304 Country:US Phone:201-434-6778 CAGE:96613

Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 Other REC Limits:NONE SPECIFIED OSHA PEL:SEE 1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9394 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred

Name:TIN CAS:7440-31-5 RTECS #:XP7320000 Other REC Limits:NONE SPECIFIED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9394

Ingred Name:SILVER (SARA III) CAS:7440-22-4 RTECS #:VW3500000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9394 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:BISMUTH CAS:7440-69-9 RTECS #:EB2600000 Other REC Limits:NONE SPECIFIED

Ingred Name:ANTIMONY (SARA III) CAS:7440-36-0 RTECS #:CC4025000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.5 MG/M3 ACGIH T LV:0.5 MG (SB)/M3; 9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:INDIUM CAS:7440-74-6 RTECS #:NL1050000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.1 MG/M3; 9394

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chronic:CHRONIC TOXICITY: WOMEN OF CHILD BEARING AGE SHOULD AVOID EXPOSURE TO LEAD AND ITS IN ORGANIC

COMPOUNDS DUE TO POST-NATAL EFFECTS. LEAD CAN CAUSE POTENTIAL INJURY TO A DEVELOPING FETUS AND POSSIBLE EFF ECTS ON REPRODUCTION. LEAD AND ITS INORGANIC COMPOUNDS ARE NEUROTOXINS. SEE SUPPLIMENTAL DATA.

Explanation of Carcinogenicity:IARC CLASSIFIES LEAD AND SOME LEAD COMPOUNDS AS POSSIBLY CARCINOGENIC TO HUMANS. NOT LISTED BY NTP OR OSHA.

Effects of Overexposure:LEAD: EXPOSURE TO HIGH LEVELS OF AIRBORNE OF INGESTED LEAD MAY PRODUCE SYMPTOMS OF ANEMIA, INSOMNI A, WEAKNESS,

CONSTIPATION, NAUSEA AND ABDOMINAL PAIN. OVEREXPOSURE MAY CAUSE DAMAGE TO BLOOD-FORMING, NERVOUS, REPRODUCTIVE, INTESTINAL AND URINARY SYSTEMS.

Medical Cond Aggravated by Exposure:DISEASES OF THE BLOOD AND BLOOD-FORMING ORGANS, KIDNEY, NERVOUS AND POSSIBLY REPRODUCTIVE SYSTEMS.

First Aid:INHALATION:LEAD-EXCESSIVE OVEREXPOSURE MAY RESULT IN AN ACUTE OR CHRONIC ILLNESS. IF SYMPTOMS ARE PRES

ENT, THE INDIVIDUAL SHOULD

BE REMOVED FROM EXPOSURE AND A PHYSICIAN CONSULTED. INGESTION:CALL A PH YSICIAN OR POISON CONTROL CENTER AT ONCE. SKIN:FOR HOT METAL BURNS, EXPOSED AREA SHOULD BE COOLED WITH WATER AND MEDICAL ATTENTION SOUGHT. EYES:FLUSH WITH WATER, CONTACT A PHYSICIAN.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING IF INVOLVED IN

Α.

FIRE.

Unusual Fire/Explosion Hazard:MODERATE IN THE FORM OF DUST WHEN EXPOSED TO HEAT OR FLAME. WHEN HEATED TO HIGH TEMPERATURES, LEAD EMITS HIGHLY TOXIC FUMES.

Spill Release Procedures: AVOID INHALATION OF SOLDER FUME OR DUST. VACUUMING OR WASHING IS RECOMMENDED. DO NOT USE DRY SWEEPING OR COMPRESSED AIR CLEANING SYSTEMS. Neutralizing Agent: MFR GAVE NO INFORMATION ON MSDS.

====== Handlin

Handling and Storage Precautions: FOOD AND DRINK SHOULD NOT BE CONSUMED OF TOBACCO PRODUCTS USED, NOR COSMETICS APPLIED IN AREAS WHERE SOLDER MAY BE USED. ALWAYS WASH HANDS AFTER USE.

Other Precautions:SINCE EMPTY CONTAINERS MAY RETAIN PREDUCT RESIDUES, ALL LABELED HAZARD PRECAUTIONS MUST BE OBSERVED. FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

====== Exposure Controls/Personal Protection =======

=====

Respiratory Protection: A NIOSH/MSHA APPROVED DUST/FUME RESPIRATOR SHOULD BE WORN SHERE AIRBORNE EXPOSURES MAY EXCEED OSHA/ACGIH PERMISSABLE AIR CONCENTRATIONS.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW PERMISSABLE LEVELS.
Protective Gloves:PROTECTIVE GLOVES SHOULD BE WORN.
Eye Protection:SAFETY GLASSES AND/OR FACE PROTECTION.
Other Protective Equipment:MFR GAVE NO INFORMATION ON MSDS.
Work Hygienic Practices
:MFR: ? HMIS:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID UNNECESSARY EXPOSURE. WASH THOROUGHLY BEFORE EATING OR DRINKING
Supplemental Safety and Health

SN:DUST OR FUME MAY CAUSE IRRTATION OF THE SKIN, MUCOUS MEMBRANES, AND MAY RESULT IN BENIGN PNEUMOCONIOSIS. AG:MAY CAUSE DISCOLORATION OF EYES AND SKIN. BI:MAY CAUSE FOUL BREATH, A BLUE-BLACK LINE ON THE GUMS AND STOMATITIS. SB:MAY CAUSE GASTROINTESTINAL UPSET, SLEEPLESSNESS, IRRITABILITY AND MUSCULAR PAIN.

HCC:N1 NRC/State Lic Num:NONE Solubility in Water:INSOLUBLE Appearance and Odor:SILVER-GRAY METAL, ODORLESS, VARIOUS SHAPES AND SIZES.

Stability Indicator/Materials to Avoid:YES OXIDING MATERIALS, ACIDS, HYDROGEN PEROXIDE > 52% Hazardous Decomposition Products:LEAD OXIDE AND ANTIMONY OXIDE FUME MAY BE EVOLVED AT TEMPERATURES GREATER THAN 1000 F (538 C). Condition s to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:SCRAP OR WASTE SOLDER SHOULD BE RECYCLED OF STORED IN SEALED CONTAINERS FOR LATER DISPOSAL. MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, exp

ressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.