

DEXTER CORP; AUTOMOTIVE MATERIALS DIVISION -- EPK 1C HARDENER AB0001 --
8040-00-777-0631

===== Product Identification =====

Product ID:EPK 1C HARDENER AB0001

MSDS Date:11/10/1993

FSC:8040

NIIN:00-777-0631

Kit Part:Y

MSDS Number: BWRWY

=== Responsible Party ===

Company Name:DEXTER CORP; AUTOMOTIVE MATERIALS DIVISION

Address:ONE DEXTER DRIVE

City:SEABROOK

State:NH

ZIP:03874

Country:US

Info Phone Num

:603-474-5541

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:KEN DECOSTA

CAGE:1JB33

=== Contractor Identification ===

Company Name:DEXTER CORP THE HYSOL DIV

Address:1 DEXTER DR

Box:City:SEABROOK

State:NH

ZIP:03874

Country:US

Phone:603-474-5541/FAX: 603-474-5545

CAGE:1JB33

Company Name:RESIN FORMULATORS CO

Address:8500 STELLER DR

Box:City:CALVER CITY

State:CA

ZIP:90232

Country:US

Phone:213-870-9561

CAGE:03355

===== Composition/Information on Ingredients =====

Ingr

ed Name:QUARTZ (CRYSTALLINE SILICA)
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 15.602%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:0.3 MG/M3

Ingred Name:DIETHYLENETRIAMINE
CAS:111-40-0
RTECS #:IE1225000
Fraction by Wt: 10-30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 PPM
ACGIH TLV:1 PPM

Ingred Name:EPOXY RESIN
CAS:25068-38-6
RTECS #:KC2100000
Fraction by Wt: 10-30%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry:

Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES

Health Hazards Acute and Chronic:INHAL: LUNG SCARRING (COUGH,SHORT OF BREATH). SILICOSIS (FORM OF PULMONARY FIBROSIS). EYE:SEVERE IRRITATION W/CORNEAL INJURY, MAY BE PERMANENT VISION IMPAIRMENT, BLINDNESS. VAPORS MAY IRRITATE. SKIN: ALLERGIC SKIN REACTIONS IN HUMANS. ABSORPTION: MAY BE ABSORBED IN HARMFUL AMTS. INGEST:GI IRRITATION/ULCERATION. BURNS *

Explanation of Carcinogenicity:CRYSTA

LLINE SILICA: NTP: (RESPIRABLE)

MAY REASONABLY ANTICIPATED TO BE CARCINOGEN. IARC: LIMITED EVIDENCE IN HUMANS.

Effects of Overexposure:IRRITATIONS AS NOTED. SKIN SENSITIZATION (ALLERGY) MAY BE EVIDENCED BY RASHES, ESPECIALLY HIVES.

* OF MOUTH & THR OAT. INHALATION: RESPIRATORY SENSITIZATION OR ASTHMA IN SUSCEPTIBLE INDIVIDUALS. UPPER RESPIRATORY TRACT IRRITATION.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN & EYE DISORDERS. PRE-EXISTIN

G SKIN OR LUNG ALLERGIES MAY INCREASE CHANCE OF DEVELOPING INCREASED ALLERGY SYMPTOMS.

=====
First Aid Measures
=====

First Aid:EYES: IMMEDIATE & CONTINUOUS IRRIGATION WITH FLOWING WATER AT LEAST 30 MINUTES. PROMPT MEDICAL AID ESSENTIAL. SKIN: IMMEDIATELY FLUSH SKIN WITH WATER AT LEAST 15 MINUTES, WHILE REMOVING CONTAMINATED CLOTHING, PREFERABLY UNDER SAFETY SHOWER. GET MEDICAL AID IMMEDIATELY. AVOID PROLONGED/REPEATED CONTACT WITH SKIN. WASH THOROUGHLY AFTER HANDLING. INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE AMOUNT OF WATER/MILK IF AVAILABLE & TRANSPORT TO **

=====
Fire Fighting Measures
=====

Flash Point Method:OC
Flash Point:215F,102C
Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, "ALCOHOL" FOAM, OR CARBON DIOXIDE
Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE & TO DILUTE SPILLS TO NONFLAMMABLE MIXTURES.
Unusual Fire/Explosion Hazard:CARE MUST BE TAKEN TO PREVENT IGNITION WHEN PROCESSING OR HANDLING AT TEMPERATURES ABOVE THE FLASH POINT.

=====
Accidental Release Measures
=====

Spill Release Procedures:CLEANUP AND DISPOSAL SHOULD BE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

=====
Handling and Storage
=====

Handling and Storage Precautions:PROTECT FROM PHYSICAL DAMAGE. STORE IN A COOL, DRY AREA, WELL VENTILATED AWAY FROM ANY AREA WHERE FIRE HAZARD MAY BE ACUTE.
Other Precautions:STRONG SKIN SENSITIZER. AVOID SKIN CONTACT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:WHERE COMPARATIVELY SMALL AMOUNTS ARE BEING USED, VENTILATION SHOULD MOVE AIR OVER THE WORK AND AWAY FROM THE WORKER. DO NOT RECIRCULATE UNLESS SCRUBBED WITH ACID.
Ventilation:VENTILATION SHOULD MOVE AIR OVER THE WORK AND AWAY FROM THE WORKER.
Protective Gloves:RUBBER

ER OR PLASTIC

Eye Protection:GOGGLES WHERE THERE IS DANGER OF SPLASH

Other Protective Equipment:USE OF PROTECTIVE SKIN CREAM IS RECOMMENDED.

Supplemental Safety and Health

** MED FACILITY. INHAL: REMOVE TO FRESH AIR IF EFFECTS OCCUR. CONSULT DR. NOTE TO PHYSICIAN: CORROSIVE. MAY CAUSE STRICTURE. IF LAVAGE PERFORMED, SUGGEST ENDOTRACHEAL &/OR ESOPHAGOSCOPIC CONTROL. IF BURN PRESENT, TREAT AS ANY THERMAL BURN,AFTER DECONTAMINATION. NO SPECIFIC IN RESPONSE TO REACTIONS OF PATIENT.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:404F,207C

Vapor Pres: