

DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV. -- HYSOL PC16M,PART A --  
5970-01-099-8525

===== Product Identification =====

Product ID:HYSOL PC16M,PART A

MSDS Date:08/14/1991

FSC:5970

NIIN:01-099-8525

Kit Part:Y

MSDS Number: BWSVN

=== Responsible Party ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV.

Address:211 FRANKLIN ST.

City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Info Phone

Num:716-372-6300

Emergency Phone Num:716-372-6309

Preparer's Name:JAMES P. HORNBURG

CAGE:04347

=== Contractor Identification ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

Company Name:MCKEOWN ROBERT CO. INC.

Address:111 CHAMBERS BROOK RD.

Box:City:SOMERVILLE

State:NJ

ZIP:08876

Country:US

Phone:908-218-9000

CAGE:7B953

===== Composition/Information on Ingredien

ts =====

Ingred Name:BISPHENOL A-EPICHLOROHYDRIN COPOLYMER  
CAS:25068-38-6  
RTECS #:SL6475000  
Fraction by Wt: 60-100%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:N-BUTYL GLYCIDYL ETHER (BGE)  
CAS:2426-08-6  
RTECS #:TX4200000  
Fraction by Wt: 6.612%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:50 PPM  
ACGIH TLV:25 PPM; 9394

===== Hazards Identification =====

LD50 LC50 Mixture:PEL FOR THIS PRODUCT IS 50PPM  
Routes of Entry: Inhalation:NO Skin:YES Ingestion:  
YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES:MAY CAUSE MODERATE  
IRRITATION.MATERIAL AT HIGH TEMPERATURES MAY CAUSE THERMAL  
BURNS.SKIN:MAY CAUSE MODERATE IRRITATION OR SENSITIZATION.MATERIAL  
AT HIGH TEMPERATURE MAY CAUSE THERMAL BURNS.INGEST :MAY CAUSE GI  
TRACT IRRITATION.INHAL:UNLIKELY ROUTE OF EXPOSURE.  
Explanation of Carcinogenicity:INGRED #2 IS LISTED ON CALIFORNIA  
PROPOSITION 65 AS A POSSIBLE CARCINOGEN.  
Effects of Overexp  
osure:SKIN:RASHES(EG.HIVES).  
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING EYE  
DISORDERS OR SKIN AND RESPIRATORY ALLERGIES MAY BE AT INCREASED  
RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WIPE OFF EXCESS;FLUSH WITH  
WATER;WASH WITH SOAP AND WATER.BURNS SHOULD BE TREATED AS A MEDICAL  
EMERGENCY.EYES:FLUSH WITH COOL WATER FOR 15 MINUTES.INHAL:REMOVE TO  
FRE SH AIR.GIVE OXYGEN

OR ARTIFICIAL RESPIRATION IF  
NEEDED.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL  
ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:155F,68C  
Extinguishing Media:SMALLER FIRES-DRY CHEMICAL,CARBON DIOXIDE;LARGER  
FIRES- ALCOHOL OR POLYMER FOAM.  
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND  
FULL PROTECTIVE EQUIPMENT.  
Unusual Fire/Explosion Hazard:FIRE CONDITIONS MAY EVOLVE TOXIC FU  
MES.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT  
ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE  
CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.  
Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED  
PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY  
FROM HEAT AND  
INCOMPATIBLE MATERIALS.  
Other Precautions:AVOID SKIN AND EYE CONTACT.DO NOT INHALE  
VAPORS/MISTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN  
ENCLOSED SPACES USE A SELF-CONTAINED BREATHING APPARATUS.  
Ventilation:USE GENERAL DILUTION VENTILATION.  
Protective Gloves:RUBBER OR PLASTIC  
Eye Protection:SAFETY GLASSES OR GOGGLES.  
Other Protective Equipment:PROTECTIVE CLOTHING,AS NEED  
ED.PROVIDE A  
LOCAL EYE WASH STATION AND SAFETY SHOWER.  
Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS  
PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.  
Supplemental Safety and Health  
KEY1;F8.INGRED #2 IS LISTED IN SECTION 313 AND EMISSIONS MUST BE  
INCLUDED IN EPCRA TRI REPORTING.NOTE OT PHYSICIAN:NO TREATMENT IS  
NEEDED EXCEPT FOR INGESTION OF LARGE QUANTITIES OF THIS PRODUCT;IN  
GE NERAL,EMESIS IS NOT NEEDED.

===== Physical/Chemical Properties =====

=====

HCC:F6

Spec Gravity:1.08

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:LIQUID,MEDIUM VISCOCITY;AMBER;VERY SLIGHT  
CHARACTERISTIC ODOR.

Percent Volatiles by Volume:8

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALIES,AMINES,ACIDS,WATER.

Stability Condition to Avoid:HIGH HEAT.

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON  
MONOXIDE,ALDEHYD

ES,ACIDS AND UNIDENTIFIED ORGANIC COMPOUNDS.

Conditions to Avoid Polymerization:EXOTHERMIC REACTION OCCURS (HEAT MAY  
BE GIVEN OFF) WHEN LARGE QUANTITIES ARE MIXED WITH THE CURING  
AGENT.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND  
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.