View NSN Online: https://aerobasegroup.jp/nsn/9525-00-409-1866

BROOKFIELD WIRE CO INC -- STAINLESS NICKEL, NICKEL-COPPER, NICKEL-CHROMIUM-IRON ALLOYS -- 9525-00-409-1866

============= Product Identification ========================

Product ID:STAINLESS NICKEL, NICKEL-COPPER, NICKEL-CHROMIUM-IRON ALLOYS

MSDS Date:11/21/1985

FSC:9525

NIIN:00-409-1866

MSDS Number: BWZLK === Responsible Party ===

Company Name: BROOKFIELD WIRE CO INC

Box:248

City:BROOKFIELD

State:MA

ZIP:01506-0248

Country:US

Inf

o Phone Num:617-867-6474

Emergency Phone Num:617-867-6474

CAGE:94129

=== Contractor Identification ===

Company Name: BROOKFIELD WIRE CO INC

Box:City:BROOKFIELD

State:MA

ZIP:01506-0248

Country:US

Phone:617-867-6474

CAGE:94129

======= Composition/Information on Ingredients ========

Ingred Name: CHROMIUM (SARA 313) (CERCLA)

CAS:7440-47-3

RTECS #:GB4200000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9495

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: COBALT (

SARA 313) CAS:7440-48-4

RTECS #:GF8750000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.1 MG/M3

ACGIH TLV:0.02 MG/M3; A3; 9495

Ingred Name: COPPER (SARA 313) (CERCLA)

CAS:7440-50-8

RTECS #:GL5325000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2 MG/M3 FUME; 9495

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 MG/M3 (TDUST)

ACGIH TLV:5 MG/M3 (OXIDE FUME)

Ingred Name: MANGANESE (

SARA 313)

CAS:7439-96-5

RTECS #:OO9275000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:C 5 MG/M3 DUST ACGIH TLV:5 MG/M3 DUST 9495

Ingred Name: MOLYBDENUM

CAS:7439-98-7

RTECS #:QA4680000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:10 PPM. ACGIH TLV:10 PPM.

Ingred Name: NICKEL (SARA 313) (CERCLA)

CAS:7440-02-0

RTECS #:QR5950000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9495

Ingred Name: SILICON

CAS:7440-21-3

RTECS #: VW0400000

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15 M

G/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9495
=========== Hazards Identification ============
LD50 LC50 Mixture:ORAL LD50 (RAT) IS NOT RELEVANT. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:LUNGS. ACUTE- NOT HAZARDOUS IN SOLID FORM. METAL FUMES, OXIDES/DUST MAY CAUSE DRYNESS OF THROAT, HEADACHE, DIZZINESS, FEVER, WATERY EYES, CHEST PAIN, BREATHING DIFFI CULTY, COUGHING. SOME TOXIC GASES MAY CAUSE PULMONARY EDEMA & EXCESSIVE EXPOSURE CAN BE FATAL. CHRONIC- MAY CAUSE NEUROLOGICAL & LUNG DAMAGE. Explanation of Carcinogenicity:CONTAINS CHROMIUM AND NICKEL. Effects of Overexposure:NAUSEA, WATERY EYES, DRY THROAT, SHORTNESS OF
BREATH, FEVER, HEADACHE, BREATHING DIFFICULTY, CHEST PAIN, DIZZINESS Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THE WELD ING FUMES.
======================================
First Aid:EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS. INHALATION:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. CALL PHYSICIAN. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS O PEN. SKIN:WASH WITH SOAP & WATER. FOR HOT METAL BURNS, EXPOSED AREA SHOULD BE COOLED WITH WATER. ORAL:INGESTION OF SOLID WIRE IS UNLIKELY TO OCCUR.
======================================
Flash Point:NONE

Extinguishing Media: THIS ALLOY IS NONCOMBUSTIBLE. TO EXTINGUISH A METAL POWDER FIRE, USE DRY SAND, DRY GRAPHITE OR OTHER CLASS "D" POWDER. Fire Fighting Procedures: WEAR PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. NEVER USE WATER AS AN EXTINGUISHING MEDIA IN AREAS NEAR MOLTEN METAL.

======== Accidental Release Measures ============

Spill Release Procedures: CAREFULLY VACUUM ANY GRINDING

DUST OR WASTE RESIDUES AND PLACE IN PROPER CONTAINER FOR LATER DISPOSAL. AVOID RAISING DUST. WEAR PROTECTIVE EQUIPMENT IF NECESSAY. Neutralizing Agent:NOT RELEVANT ========== Handling and Storage ================ Handling and Storage Precautions: KEEP AWAY FROM INCOMPATIBLE MATERIALS. FOOD AND DRINK SHOULD NOT BE CONSUMED IN AREAS WHERE SOLDER MAY BE USED. Other Precautions: WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING AND DRINKING. AVOID BREATHING FUM ES, VAPORS AND DUSTS, KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY. AVOID EYE AND SKIN CONTACT. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: USE NIOSH APPROVED SUPPLIED AIR RESPIRATORY PROTECTION WHEN GRINDING, WELDING, BRAZING OR SOLDERING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV. Ventilation: LOCAL EXHAUST AT THE ARC (OR FLAME), OR BOTH, TO KEEP THE **FUMES AND GASES B** ELOW PEL'S, TLV'S OR STEL'S IN BREATHING ZONE Protective Gloves: WELDER'S GLOVE Eye Protection: PROTECTIVE FACE SHIELD Other Protective Equipment: EYE WASH STATION, APRONS, HATS, ARM & SHOULDER PROTECTION, AS WELL AS DARK SUBSTANTIAL CLOTHING. Work Hygienic Practices: WEAR HEAD AND BODY PROTECTION WHICH HELP TO PREVENT INJURY FROM RADIATION, SPARKS AND ELECTRICAL SHOCK. Supplemental Safety and Health ========= Physical/Chemical Properties =========== HCC:N1 NRC/State Lic Num:NOT RELEVANT Viscosity:NOT RELEVANT Evaporation Rate & Evaporation Relevant Solubility in Water: INSOLUBLE Appearance and Odor: ROUND AND FLATTENED WIRE ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES

STRONG ACIDS

Stability Condition to Avoid: MOISTURE

Hazardous Decomposition Products: CARBON MONOXIDE, NITROGEN DIOXIDE, CHROMIUM, MOLYBDENUM, NICKEL, OZONE, PHOSGENE AND FUMES OF COPPER, COBALT, IRON, MN

==== Disposal Considerations =========

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. SCRAP OR WASTE SOLDER SHOULD BE RECYCLED OR STORED IN SEALED, DRY CONTAINERS FOR LATER DISPOSAL. DISPOSAL MUST BE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Amer ica in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.