

JOHNSON & JOHNSON MEDICAL INC -- 2920 CIDEX SOLUTION TEST STRIPS -- 6840-01-364-9421
===== Product Identification =====

Product ID:2920 CIDEX SOLUTION TEST STRIPS

MSDS Date:09/09/1994

FSC:6840

NIIN:01-364-9421

MSDS Number: BXPDL

=== Responsible Party ===

Company Name:JOHNSON & JOHNSON MEDICAL INC

Address:2500 ARBROOK BLVD

Box:90130

City:ARLINGTON

State:TX

ZIP:76004-3130

Country:US

Info Phone Num:8

00-423-5850

Emergency Phone Num:800-423-5850

CAGE:DO392

=== Contractor Identification ===

Company Name:JOHNSON & JOHNSON MEDICAL INC. (SUB OF JOHNSON & JOHNSON)

Address:2500 ARBROOK BOULEVARD

Box:City:ARLINGTON

State:TX

ZIP:76014

Country:US

Phone:800-433-5170

CAGE:52780

Company Name:JOHNSON & JOHNSON ORTHOPAEDICS, INC

Address:501 GEORGE STREET

City:NEW BRUNSWICK

State:NJ

ZIP:08903

Phone:800-526-2459

CAGE:DO392

===== Composition/Information on Ingredients =====

Ingred Name:GLY

CINE; AMINOACETIC ACID; GLYCOLIXIR; HAMPSHIRE GLYCINE

CAS:56-40-6

RTECS #:MB7600000

Ingred Name:SODIUM SULFITE

CAS:7757-83-7

RTECS #:WE2150000

Other REC Limits:5 MG/CUM (DUST)

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT): 7930 MG/KG

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of Carcinogenicity:NONE

===== First Aid Measures =====

=====

First Aid:OBTAIN MEDICAL ATTENTIONN IN ALL CASES.

===== Fire Fighting Measures =====

Extinguishing Media:SMALL: CO2, DRY CHEMICAL. LARGE: WATER FOG,
ALCOHOL/POLYMER/REGULAR FOAM.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T REMOVE DESSICANT. KEEP CAP
TIGHTLY CLOSED. STORE AT CONTROLLED ROOM TEM 59-86F & IN A DRY
PLACE.

Other Precautions:KEEP OUT OF REACH OF CHILDREN.

=====

=== Exposure Controls/Personal Protection =====

Ventilation:STANDARD ROOM VENTILATION, AIR CONDITIONING, 1 NATURAL
DRAFT.

Protective Gloves:LATEX RUBBER

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:AVOID CONTAMINATION OF FOOD.

Supplemental Safety and Health

TEST STRIP CONSISTS OF 3-7/8" X 5/8" WHITE POLYESTER SHEET HANDLE
W/5/8" X 5/8" WHITE REAGENT PAD W/A 1/8" BLUE BORDER AFFIXED TO ONE
END OF HANDLE W/ADHESIVE. REAGENT PAD COSISTS OF GLYCINE & SODIUM
SULFI

TE IMPREGNATED & DRIED ON FILTER PAPER. TEST STRIPS ARE
PACKAGED 60/15 IN WHIE HIGH DENSITY POLUETHYLENE BOTTLE.

===== Physical/Chemical Properties =====

Appearance and Odor:(SEE SUPP)

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:MOISTURE.

Hazardous Decomposition Products:CO & NITROGEN/SULFUR OXIDES.

===== Disposal Considerations =====

=====

Waste Disposal Methods:DISPOSE OF USED/EXPIRED TEST STRIPS, PLASTIC
BOTTLES & SILICA GEL DESSICANT IN TRASH RECEPTACLE IAW/FEDERAL,
STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any per

son utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.