

FUJI ELECTROCHEMICAL CO, LTD -- DL2032 LITHIUM MNO2 BATTERY -- 6135-01-210-8715

===== Product Identification =====

Product ID:DL2032 LITHIUM MNO2 BATTERY

MSDS Date:10/19/1988

FSC:6135

NIIN:01-210-8715

MSDS Number: BXYFR

=== Responsible Party ===

Company Name:FUJI ELECTROCHEMICAL CO, LTD

Address:5-36-11 SHIMBASHI

City:MINATO-KU TOKYO 105 JAPAN

Emergency Phone Num:203-796-4000/617-449-7600

Preparer'

s Name:T. MIZUNO

CAGE:S7173

=== Contractor Identification ===

Company Name:DURACELL INC TECHNICAL SALES AND MARKETING GROUP

Address:BERKSHIRE CORPORATE PARK

Box:City:BETHEL

State:CT

ZIP:06801

Country:US

Phone:203-796-4000

CAGE:90303

Company Name:FUJI ELECTROCHEMICAL CO LTD

Address:HAMAGOMU BLDG 5-36-11 SHIMBASH MINATO-KU

Box:City:TOKYO 105

Country:JA

Phone:203-796-4000 (IMPORTER)

CAGE:S7173

===== Composition/Information on Ingredients =====

Ingred Name:LITHIUM METAL

CAS:7439

-93-2

RTECS #:OJ5540000

Fraction by Wt: 2.5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MANGANESE DIOXIDE

CAS:1313-13-9

RTECS #:OP0350000

Fraction by Wt: 30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG MN/M3 CEILING

ACGIH TLV:5 MG MN/M3

Ingred Name:GRAPHITE, SYNTHETIC

CAS:7440-44-0

RTECS #:FF5250100

Fraction by Wt: 3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:2 MG/M3 TDUST; 9495

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHOXYETHANE

CAS:110-71-4

RTECS #:KI1451000

Fraction by Wt: 2.5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:LITHIUM PERCHLORATE

CAS:7791-03-9

Fraction by Wt: 0.5%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: RISK OF EXPOSURE ONLY IF

BATTERY RUPTURES OR VENTS. EXPOSURE TO DME MAY BE HARMFUL; MAY CAUSE REPRODUCTIVE HARM. LITHIUM MAY CAUSE THERMAL & CHEMICAL BURNS ON CONTACT. CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:SKIN-BURNS. EYES-BURNS. INHALED-UNKNOWN. INGESTED-UNKNOWN.

Medical Cond Aggravated by Exposure:AN ACUTE EXPOSURE GENERALLY WILL NOT AGGR

AVATE ANY MEDICAL CONDITION.

===== First Aid Measures =====

First Aid:EYES-IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. SEEK MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED CLOTHES. FLUSH WITH WATER. INHALED-REMOVE TO FRESH AIR. INGESTED-CONTACT NATIONAL BATTERY INGESTION HOTLINE 202-625-3333. OBTAIN IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Extinguishing Media:WATER.

Fire Fighting Proc

cedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER.
Unusual Fire/Explosion Hazard:FIRE & EXPLOSION MAY OCCUR AS A RESULT OF
STACKING OR JUMBLING A LOTS OF BATTERIES.

===== Accidental Release Measures =====

Spill Release Procedures:LEAVE AREA TO ALLOW BATTERIES TO COOL AND
VAPRS TO DISSAPATE. AVOID SKIN AND EYE CONTACT OR INHALATION OF
VAPORS. REMOVE SPILLED LIQUID WITH ABSORBENT AND INCINE
RATE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID MECHANICAL OR ELECTRICAL ABUSE.
Other Precautions:BATTERIES MAY EXPLODE, PYROLIZE OR VENT IF SHORTED,
DISASSEMBLED, CRUSHED, RECHARGED OR EXPOSED TO FIRE OR HIGH
TEMPERATURES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE
OR AN
EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR OR
AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IN ACCORDANCE
WITH 29 CFR 1910.13 4 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:IF VENTING; USE ADEQUATE MECHANICAL VENTILATION OR LOCAL
EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:RUBBER.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING,
DRINKING, OR SMOKING. LAUND
ER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

BATTERY SHOULD BE IN ACCORDANCE WITH ANSI STANDARD C18.3M-1991 USING
SPECIFICATION SHEET 10-0787-0126 FOR ANSI/NEDA NUMBER 5004LC.

===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:BATTERY. CYLINDRICAL. 0.787 X 0.106 INCHES. 3.0
VOLTS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACT

URER.

Stability Condition to Avoid:DO NOT HEAT, DISASSEMBLE, RECHARGE OR
JUMBLE UP.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL ENVIRONMENTAL REGULATIONS. OPEN BATTERIES SHOULD BE TREATED
AS HAZARDOUS WASTE.

Disclaimer (provided with this information by the compilin
g agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.