View NSN Online: https://aerobasegroup.jp/nsn/7930-01-381-3396

Product ID: PROFECTION ADVANCED FLOOR COATING #0512 MSDS Date:02/21/1995 FSC:7930 NIIN:01-381-3396 **MSDS Number: BYCTT** === Responsible Party === Company Name: NATIONAL CHEMICAL LABORATORIES OF PENNSYLVANIA INC Address:401 N 10TH ST City:PHILADELPHIA Stat e:PA ZIP:19123-3803 Country:US Info Phone Num:215-922-1200 Emergency Phone Num:215-922-1200 Preparer's Name:F.C. CAGE:93607 === Contractor Identification === Company Name: NATIONAL CHEMICAL LABORATORIES OF PENNSYLVANIA INC Address:401 N 10TH ST Box:City:PHILADELPHIA State:PA ZIP:19123-3803 Country:US Phone:215-922-1200 CAGE:93607

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: PROP. Other REC Limits:NONE RECO MMENDED

Ingred Name:ACRYLIC ACID POLYMER CAS:25987-66-0 Fraction by Wt: PROP. Other REC Limits:NONE RECOMMENDED

Ingred Name:DIETHYLENE GLYCOL MONOMETHYL ETHER CAS:111-77-3 RTECS #:KL6125000 Fraction by Wt: PROP. Other REC Limits:NONE RECOMMENDED

Ingred Name:TRIBUTOXYETHYLPHOSPHATE (LD50 ORAL=9.5 G/KG) CAS:78-51-3 RTECS #:KJ9800000 Fraction by Wt: PROP. Other REC Limits:NONE RECOMMENDED

Ingred Name:PHTHALIC ACID, DIBUTYL ESTER CAS:84-74-2 RTECS #:TI0875000 Fraction by Wt: PROP. Other REC Limi ts:NONE RECOMMENDED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Ingred Name:POLYETHYLENE EMULSION CAS:67892-91-5 Fraction by Wt: PROP. Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN/EYES: MAY IRRITATE. INGESTION: MAY CAUSE SEVERE GASTRIC DISTRESS & BLOCKAGE. Med ical Cond Aggravated by Exposure:NONE

First Aid:EYES: FLUSH W/WATER AT LEAST 15 MINUTES. GET MEDICAL AID. SKIN: FLUSH THOROUGHLY W/WATER. IF IRRITATION PERSISTS, GET MEDICAL AID. INGESTION: INDUCE VOMITING. GET MEDICAL AID.

Flash Point Method:TOC Flash Point:NONE TO BOILING Lower Limits:NA Upper Limits:NA Unusual Fire/Explosion Hazard:HEATED MATERI AL MAY LIBERATE TOXIC FUMES; WEAR SCBA.

Spill Release Procedures:RECONTAINERIZE BY MOPPING, WET VACUUM OR SUITABLE ABSORBENT. RINSE REMAINING MATERIAL TO DRAINS. BE CAUTIOUS OF SLIPPERY FLOORS.

Handling and Storage Precautions:STORE BETWEEN 40-140F. Other Precautions:KEEP OUT OF REACH OF CHILDREN. FOR SALE TO, USE & STORAGE BY SERVICE PERSONN EL ONLY.

Respiratory Protection:NOT REQUIRED Ventilation:LOCAL Protective Gloves:NOT REQUIRED Eye Protection:SAFETY GLASSES Other Protective Equipment:NONE Supplemental Safety and Health NK

Boiling Pt:B.P. Text:212F,100C Vapor Pres:=WATER Vapor Density:=WATER Spec Gravity:1.051 pH:8.2 Evaporation Rate & Reference:=WATER Solubility in Water:DISPERSES App

## earance and Odor:OPAQUE, WHITE LIQUID W/ACRYLIC ODOR

Stability Indicator/Materials to Avoid:YES STRONG ACIDS & OXIDIZERS Stability Condition to Avoid:NONE Hazardous Decomposition Products:CARBON OXIDES & ACRYLATES

Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agenci es):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.