

CINCINNATI MILACRON MARKETING CO -- CIMTECH 400 UNDYED 291 -- 9150-00-051-4626
===== Product Identification =====

Product ID:CIMTECH 400 UNDYED 291

MSDS Date:01/01/1994

FSC:9150

NIIN:00-051-4626

MSDS Number: BYXJP

=== Responsible Party ===

Company Name:CINCINNATI MILACRON MARKETING CO

Address:4701 MARBURG AVE

City:CINCINNATI

State:OH

ZIP:45209

Country:US

Info Phone Num:513-841-8964

Emergency Phone

Num:513-841-8181

CAGE:86167

=== Contractor Identification ===

Company Name:CINCINNATI MILACRON

Address:4701 MARBURG AVE

Box:City:CINCINNATI

State:OH

ZIP:45209

Country:US

Phone:513-841-8133;800-862-8463

CAGE:86167

===== Composition/Information on Ingredients =====

Ingred Name:ETHANOL, 2-AMINO-; (ETHANOLAMINE)

CAS:141-43-5

RTECS #:KJ5775000

Fraction by Wt: 10%

OSHA PEL:3 PPM

ACGIH TLV:3 PPM; 6 STEL

Ingred Name:NEODECANOIC ACID

Fraction by Wt: 10%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:1-PROPANOL, 2-AMINO-2-METHYL-; (AMINOMETHYLPROPANOL)
CAS:124-68-5
RTECS #:UA5950000
Fraction by Wt: 10%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:HEPTANOIC ACID
CAS:111-14-8
RTECS #:MJ1575000
Fraction by Wt: 10%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:NONANOIC ACID; (PELARGONIC ACID)
CAS:112-05-0
RTECS #:RA6650000
Fraction by Wt: 10%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:ETHANOL, 2,2',2"-NITRILOTRI-; (TRIETHANOLAMINE)
CAS:102-71-6
RTECS #:KL9275000
Fraction by Wt: 10%
OSHA PEL
:N/K
ACGIH TLV:N/K

Ingred Name:SUPP DATA: SOON AS POSS. DILUTED PROD IS NOT IRRIT TO SKIN
WHEN USED AS RECOM & GOOD PERS HYGIENE IS PRACTICED.(ING 8)
RTECS #:9999999ZZ

Ingred Name:ING 7: REMOVE SEVERLY CONTAMD CLOTHING, INCLG SHOES.
LAUNDER BEFORE REUSE. IF IRRIT PERSISTS, GET MED ATTN.
RTECS #:9999999ZZ

Ingred Name:WASTE DISP METH: AS DEFINED UNDER 40CFR 261. CIMCOOL
TECHNICAL SERVICES CAN PROVIDE A LIST OF WASTE HAULERS FOR(ING 10)
RTECS #:9999999ZZ

Ingred Name:ING 9:YOUR ARE

A. "EMPTY" CNTNRS: WILL CONTAIN A RESIDUE WHICH IS NOT CONSIDERED HAZARDOUS WASTE UNDER RCRA REGS.(ING 11)
RTECS #:9999999ZZ

Ingred Name:ING 10: DRUMS CAN BE DRAINED TO A "DRIP DRY" CNDTN BY INVERSION & CAN BE OFFERED FOR RECYCLING OR SCRAP.
RTECS #:9999999ZZ

Ingred Name:VENT: TOGETHER OR VENT IS INADEQ, OEPRATORS MAY EXPER RESP IRRIT. FOR SUCH APPLICS, USE OF SPLASH GUARDS/MIST (ING 13)
RTECS #:9999999ZZ

Ingred Name:ING 12: COLLECTORS IS RECOMMENDED. WHEN USED IN APPLIC GENER ATING HIGH LEVELS OF MIST, OP EXPOSURE CAN BE MIN BY(ING 14)
RTECS #:9999999ZZ

Ingred Name:ING 13: PROPER VENT. IF THERE IS DOUBT ABOUT ACTUAL MIST LEVELS PRESENT, MONITORING SHOULD BE CONDUCTED.
RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL: EXTENDED EXPOS TO MISTS MAY

CAUSE UPPER RESP IRRIT. EYE: WILL CAUSE STINGING SENSATION IN EYE. INGEST: SWALLOWING SMALL QTYS MAY CAUSE NAUSEA/DIARRHEA. MILD SKIN IRRIT(REDNESS & DRYNESS OF HANDS) MAY BE EXPERIENCED WHEN DILUTED PROD HAS BEEN CONTAMD BY CERTAIN OILS, BY DISSOLVED METALS/WHEN MIX(EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ: RATIO IS TOO STRONG. SYMPS OF OVEREXP: EYE INJURY MAY RESULT FROM CONTACT W/CONCENTRATED PRODUCT.

SKIN IRRITATION CAN RESULT FROM IMPROPER USE & HANDLING OF CONCENTRATE OR MIX.

Medical Cond Aggravated by Exposure:MAY AGGRAVATE EXISTING SKIN IRRITATION WHERE FURTHER DEFATTING OR SKIN PENETRATION COULD OCCUR.

===== First Aid Measures =====

First Aid:EYES: FLUSH IMMED W/RUNNING WATER FOR AT LEAST 15 MINS, THEN PROMPTLY GET MED ATTN TO CHECK FOR POSS IRRIT. INGEST: DO NOT INDUCE VOMIT. DILUTE BY DRINKING WATER/MILK. IMMED CONT MD & OBT

AIN

TREATMENT . INGEST OF SMALL QTYS OF DILUTED PROD IS NOT EXPECTED TO CAUSE INJURY/ILLNESS; BUT AS SHOULD BE EXPECTED WHEN DRINKING OILY, SOAPY, WATER, NAUSEA, DIARRHEA/ABDOM DISTRESS MAY BE EXPERIENCED. (SUPDAT)

=====
Fire Fighting Measures
=====

Flash Point Method:COC

Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Haz

ard:HAZARDOUS COMBUSTION PRODUCTS: SMOKE, FUMES & OXIDES OF CARBON.

=====
Accidental Release Measures
=====

Spill Release Procedures:CONTN SPILL, COLLECT ON ABSORB MATL & DISCARD AS DICTATED BY FEDERAL, STATE & LOCAL REGULATIONS THAT MAY APPLY. FLUSH AREA THOROUGHLY W/WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:USE ONLY AS RECOM BY MFR. AVOID ALL

CONT OF CONC W/EYES/SKIN. DO NOT SWALLOW. IF FROZEN, PROD SEPARATES. THAW COMPLETEY AT ROOM TEMP & STIR THORO.

Other Precautions:CONTNS AMINES. DO NOT ADD SODIUM NITRITES/OTHER NITROSATING AGENTS TO THIS PRODUCT. SUSPECTED CANCER CAUSING NITROSAMINES COULD BE FORMED.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:PRODUCT IS NOT VOLATILE. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation:FOR

MOST APPLICS, NORM SHOP VENT IS ADEQ. HOWEVER, WHEN HIGH MIST LEVELS ARE GENERATED/WHERE MACHINES ARE CLOSE(ING 12)

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGS.

Other Protective Equipment:EMER EYEWASH & DELUGE SHOWER MEETING ANSI DESIGN CRITERIA. EFTIVE METALWORKING PLANT PROT CLTHG AS APPROPRIATE.

Work Hygienic Practices:GOOD PERSONAL HYGIENE SHOULD ALWAYS BE PRACTICED.

Supplemental Safety and Health

PH(CONC): 9.5-9.8. (5% MIX): 8.8-9.2. FI

RST AID PROC: INHAL: INHAL OF

DILUTED MIX CAN OCCUR IN APPLIC WHERE HIGH MIST LEVELS ARE GENERATED. OSHA HAS SET PEL OF 15 MG/M3 FOR ANY AIRBORNE PARTICULATE AS NUISANCE LEVEL OF EXPOS. REMOVE TO FRESH AIR. SUPPORT BRTHG(GIVE O*2/ARTF RESP). SKIN: WASH W/WATER AS(ING 7)

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C
Vapor Pres:LIKE WATER
Spec Gravity:1.0582
pH:SUPDAT
Evaporation Rate & Reference:LIKE WATER
Solubility in
Water:100% MISCIBLE
Appearance and Odor:CLEAR W/CHEMICAL ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID ADDITION OF STRONG ACIDS TO PRODUCT CONCENTRATE.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:SMOKE, FUMES & OXIDES OF CARBON.

===== Disposal Considerations =====

Waste Disposal Methods:USED MIX: DISP PROCS MUST COMPLY W/LOC, COUNTY, STATE & FED REGS. IF PRE-TREATMENT IS NEEDED, CHEM EMULSION BREAKING/ULTRAFILTRATION MAY BE USED. CONT CIMCOOL TECHNICAL SERVICES(513-841-8133) FOR ASSI ST. UNUSED CONC: CONC IS NOT HAZ WASTE,(ING 9)

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.