

DEXTER AEROSPACE MATERIAL DIVI -- EA 960 PART A, (AA9042)
=====

MSDS Safety Information
=====

FSC: 8040
NIIN: 01-208-6003
MSDS Date: 03/01/1992
MSDS Num: BYXXY
Product ID: EA 960 PART A, (AA9042)
MFN: 05
Kit Part: Y
Responsible Party
Cage: 33564
Name: DEXTER AEROSPACE MATERIAL DIVISION
Address: 2850 WILLOW PASS
ROAD
Box: 312
City: PITTSBURG CA 94565-0031
Info Phone Number: 510-458-8000
Emergency Phone Number: 800-424-9300(CHEMTREC)
Preparer's Name: MSDS DEPT
Proprietary Ind: Y
Review Ind: Y
Published: Y
=====

Preparer Co. when other than Responsible Party Co.
=====

Cage: 33564
Name: DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address: 2850 WILLOW PASS ROAD
Box: 312
City: BAY POINT CA 94565-3299
=====

=====

Contractor Summary
=====

Cage: 33564
Name: DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address: 2850 WILLOW PASS ROAD
Box: 312
City: BAY POINT CA 94565-3299
Phone: 202-483-7616
Cage: 03355
Name: RESIN FORMULATORS CO
Address: 8500 STELLER DR
City: CALVER CITY CA 90232
Phone: 213-870-9561
=====

Item Description Information
=====

=====

Item Manager: GSA
Item Name: ADHESIVE
Unit of Issue: KT
UI Container Qty: 0

=====

Ingredients

=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data

=====

LD50 LC50 Mixture: MIXTURE HAS NOT BEEN TESTED AS A WHOLE.

Route Of Entr

y Inds - Inhalation: YES

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: BRIEF CONTACT MAY IRRIT SKIN OR CAUSE A RASH. REPEATED OR PROLONGED SKIN CONTACT MAY RESULT IN ALLERGIC SENSITIZATION. CARCINOGENICITY NOTE: BISPHENOL A/EPICHLOROHYDRIN EPOXY RESIN HAS EXHIBITED MUTAG ENICITY IN BACTERIA.

Explanation Of Carcinogenicity: TALC IS AN IARC GRP 3 MAT'L (NOT A HUMAN CARCINOGEN).

Signs And Symptions Of Overexposure: SKIN RASH, IRRITATION.

Medic

al Cond Aggravated By Exposure: SKIN SENSITIZATION.

First Aid: EYE:FLUSH W/WATER FOR 15MINS. IF IRRIT PERSISTS GET MED ATTN.

SKIN:WASH THOROUGHLY W/SOAP & WATER. IF IRRIT PERSISTS GET MED ATTN.

INHAL:REMOVE VICTIM TO FRESH AIR. IF SYMPTOMS PERSIST GET MED ATTN. I

NGEST:DRINK PLENTY OF WATER. GET MED ATTN IMMED.

=====

Handling and Disposal

=====

Spill Release Procedures: WEAR PROTECTIVE C

LOTHING, GLOVES & SAFETY

GLASSES. SCRAPE UP OR SHOVEL INTO DOT APPROVED WASTE CONTAINERS.

Waste Disposal Methods: NOT RCRA HAZ WASTE.HOWEVER, INCINERATION IN EPA

APPROVED WASTE INCINERATOR IS PREFERRED.CHEM ADDITIONS/ PROCESSING/OTHERWISE

ALTERING MATL MAY MAKE WASTE MANAGEMENT INFOR HEREIN INCOMPLETE/INACCURATE/

INAPPROPRIATE.CONSULT STATE/LOC REGULATIONS.

Handling And Storage Precautions: REFRIGERATED STORAGE IS RECOMMENDED TO

MAINTAIN PRODUCT QUALITY. THIS PRODUCT MAY BE STORED

@ ROOM TEMP (77F) FOR UP
TO 12 MONTHS.
Other Precautions: FOLLOW CURING SCHEDULE AS RECOMMENDED IN PRODUCT
LITERATURE.DON'T CUT/GRIND/WELD/DRILL ON/NEAR CONTAINER.AVOID MIXING PARTS
A&B IN BATCHES >1LB UNLESS PLAN TO USE IMMED.DON'T HEAT MIXED ADHESIVE
>75F UNLESS CURING SURFACES TO BE BONDED.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: NOT TESTED
Lower
Limits: NOT TESTED
Upper Limits: NOT TESTED
Extinguishing Media: DRY CHEMICAL, OR HALON FIRE EXTINGUISHER, OR WATER SPRAY,
FOAM OR FOG.
Fire Fighting Procedures: WEAR SCBA & FULL PROTECTIVE CLOTHING, SUCH AS
TURN-OUT GEAR. CARTRIDGE RESP DO NOT PROVIDE ADEQUATE PROTECTION FOR
FIREFIGHTERS OR EXOTHERM MITIGATION.
Unusual Fire/Explosion Hazard: MAY LIBERATE LARGE QUANTITIES OF DENSE
FOUL-SMELLING SMOKE WHICH MAY CONTAIN UNIDENTIFIED TOXIC GASES.

=====
=====

Control Measures
=====

Respiratory Protection: UNNECESSARY WITH ADEQUATE EXHAUST VENTILATION.
Ventilation: LOCAL EXHAUST VENTILATION AT THE POINT OF USE.
Protective Gloves: BUTYL RUBBER, PVC, NITRILE RUBBER GLOVES
Eye Protection: SAFETY GLASSES W/SIDE SHIELD;CHEM GOGGLE
Other Protective Equipment: AN EYEWASH AND SAFETY SHOWER SHOULD BE NEARBY AND
READY FOR USE.
Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER HANDLING MATER
IALS.
Supplemental Safety and Health: VISCOSITY:BROOKFIELD, SPDKL 5. FAILURE TO
OBSERVE PRECAUTIONS IN MIXING/HEATING MAY RESULT IN EXCESSIVE HEAT BUILD-UP
CAUSING AN EXOTHERM. THE EXOTHERM HAS POTENTIAL FOR RELEASE OF TOXIC GASES.
SEE SA ME NSN/CAGE PN/IND: F FOR PART B OF 2-PART KIT.

=====
Physical/Chemical Properties
=====

B.P. Text: UNDEFINED
Decomp Text: UNTESTED
Vapor Pres: NIL
Vapor

Density: >1
Spec Gravity: >1
Viscosity: 400-10000 BRK
Solubility in Water: NEGLIGIBLE.
Appearance and Odor: PASTE, DARK ORANGE PASTE WITH EPOXY ODOR.
Corrosion Rate: NA

=====

Reactivity Data

=====

Stability Indicator: YES
Stability Condition To Avoid: AVOID MIXING PARTS A&B IN BATCHES >1LB & HEATING MIXTURE >75F.
Materials To Avoid: STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.
Hazardous Decomposition Products: CO, NOX, ALDEHYDES, ACIDS & UNDETERMINED ORGANICS.
Hazardous Polymerization Indicator: YES
Conditions To Avoid Polymerization: NO INFORMATION PROVIDED BY MFG.

=====

Toxicological Information

=====

=====

Ecological Information

=====

=====

=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

Transportation Information

=====

=====

Responsible Party Cage: 33564
Trans ID NO: 115316
Product ID: EA 960 PART A, (AA9042)
MSDS Prepared Date: 03/01/1992
Review Date: 02/20/1996
MFN: 5
Multiple KIT Number: 0
Kit Part IND: Y
Review IND: Y
Unit Of Issue: KT
Container QTY: 0

=====

Detail DOT Information

=====

DOT PSN Code: AJJ
Symbols: G
DOT Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. OR POLYAMINES, LIQUI

D, CORROSIVE, N.O.S.
Hazard Class: 8
UN ID Num: UN2735
DOT Packaging Group: III
Label: CORROSIVE
Special Provision: T8
Non Bulk Pack: 203
Bulk Pack: 241
Max Qty Pass: 5 L
Max Qty Cargo: 60 L
Vessel Stow Req: A

=====

Detail IMO Information

=====

IMO PSN Code: AQA
IMO Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. o
IMDG Page Number: 8109-2
UN Number: 2735
UN Hazard Class: 8
IMO Packaging
Group: I/II/III
Subsidiary Risk Label: -
EMS Number: 8-05
MED First Aid Guide NUM: 320

=====

Detail IATA Information

=====

IATA PSN Code: AWR
IATA UN ID Num: 2735
IATA Proper Shipping Name: ALKYLAMINES, N.O.S. (POLYALKYLAMINES, N.O.S.)
IATA PSN Modifier: * CORROSIVE
IATA UN Class: 8
Subsidiary Risk Class: -
IATA Label: CORROSIVE
UN Packing Group: II
Packing Note Passenger: 808
Max Quant Pass: 1L
Max Quant Cargo: 30L
Packaging Note Cargo: 812

=====

Detail AFI Information

=====

AFI PSN Code: AWR
AFI Proper Shipping Name: ALKYLAMINES, N.O.S., OR POLYALKYLAMINES, N.O.S.
AFI PSN Modifier: ,CORROSIVE
AFI Hazard Class: 8
AFI UN ID NUM: UN2735
AFI Packing Group: II
AFI Label: CORROSIVE
Special Provisions: N34
Back Pack Reference: A12.3

=====

HAZC

OM Label

=====

Product ID: EA 960 PART A, (AA9042)

Cage: 33564

Company Name: DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Street: 2850 WILLOW PASS ROAD

PO Box: 312

City: BAY POINT CA

Zipcode: 94565-3299

Health Emergency Phone: 800-424-9300(CHEMTREC)

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: BRIEF CONTACT MAY IRRIT SKIN OR CAUSE A RASH. REPEATED

OR PROLONGED SKIN CONTACT MAY RESULT IN ALLERGIC SENSITIZATION.

CARCINOGENICITY NOTE: BISPHENOL A/EPICHLOROHYDRIN EPOXY RESIN HAS EXHIBITED
MUTAGENICITY IN BACTERIA.

SKIN RASH, IRRITATION.

=====

Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for
the suitability of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.