View NSN Online: https://aerobasegroup.jp/nsn/6525-01-168-0528

EASTMAN KODAK COMPANY -- 102 8869;KODAK READYMATIC DENTAL DEL AND REPL;KAN471440

-- 6725-01-168-0528

Product ID:102 8869;KODAK READYMATIC DENTAL DEL AND REPL;KAN471440

MSDS Date: 10/25/1995

FSC:6725

NIIN:01-168-0528

MSDS Number: BZPKR === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-477-3194 MSDS:800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 85-90%

Other REC Limits: NONE RECOMMENDED

Ingred Name:SODIUM

SULFITE CAS:7757-83-7

RTECS #:WE2150000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: POTASSIUM SULFITE

CAS:10117-38-1 RTECS #:WT3530000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: DIETHYLENE GLYCOL

CAS:111-46-6

RTECS #:ID5950000 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: HYDROQUINONE (SARA 302/313) (CERCLA)

CAS:123-31-9

RTECS #:MX3500000 Fraction by Wt: 2%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3

; 9596

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

========== Hazards Identification ================

LD50 LC50 Mixture:TLV FOR HYDROQUINONE IS 2MG/M3 TWA

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHAL: LOW HAZARD FOR EXPECTED


HANDLING, HOWEVER CONTACT WITH STRONG ACIDS OR IF HEATED MAY RELEASE SULFUR DIOXIDE WHICH MAY CAUSE RESPIRATORY SENSITIZATION. EYES: MAY CAUSE TRANSCIENT I

RRITATION.SKIN:MAY CAUSE ALLERGIC SKIN REACTION.INGEST:LOW INGESTION HAZARD.

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:EYES:IRRITATION.INHAL:WHEEZING,CHEST TIGHTNESS.SKIN:RASH.

Medical Cond Aggravated by Exposure: PERSONS WITH SENSITIVITY TO SULFITES OR WITH ASTHMA MAY BE AT INCREASED RISK FROM EXPOSURE.



======= Physical/Chem

ical Properties ==========
HCC:B3 Boiling Pt:B.P. Text:>212F,>100C Vapor Pres:24 Vapor Density:0.6 Spec Gravity:1.09 pH:10.1 Solubility in Water:COMPLETE Appearance and Odor:LIQUID;ODORLESS;COLORLESS Percent Volatiles by Volume:90
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG ACIDS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:SULFUR DIOXIDE.
Disposal Considerations ====================================
Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document shou ld seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.