View NSN Online: https://aerobasegroup.jp/nsn/8010-00-290-4054

Product ID:OIL EXTERIOR GLOSS, 13613 IVORY CREAM MSDS Date:11/01/1991 FSC:8010 NIIN:00-290-4054 MSDS Number: BZQWJ === Responsible Party === Company Name: FARWEST PAINT MFG CO Address:4522 SOUTH 133RD ST City:TUKWILA State:WA ZIP:98168 Country:US Info Phone Num:206-244-8844 Emergency Phone Num:206-941-1619 CAGE:6F266 === Contractor Identification === Company Name: FARWEST PAINT MANUFACTURING CO Address:4522 SOUTH 133RD ST Box:City:TUKWILA State:WA ZIP:98168 Country:US Phone:206-244-8844 CAGE:6F266 Ingred Name:LIGROINE; (MINERAL SPIRITS)

CAS:8032-32-4 RTECS #:OI6180000 Fraction by Wt: 9.48% OSHA PEL:300 PPM ACGIH TLV:300 PPM

Ingred Name:STODDARD SOLVENT; (MINERAL SPIRITS (STODDARD)) CAS:8052-41-3 RTECS #: WJ8925000 Fraction by Wt: 15.80% **OSHA PEL:500 PPM** ACGIH TLV:100 PPM Ingred Name:XYLENE (SARA 313) (CERCLA) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 0.83% OSHA PEL:100 PPM ACGIH TLV:100 PPM/150STEL EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: VOLATILE ORGANIC CONTENT: 250 G/L RTECS #:9999999VO **OSHA PEL:N/K** ACGIH TLV:N/K LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin: YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: SKIN: MAY CAUSE IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN UPON PROLONGED OR REPEATED CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS CAN RESULT IN HEADACHE, DIZZINESS, NA USEA AND LOSS OF CONSCIOUSNESS. EYES: MAY CAUSE IRRITATION. CHRONIC: SOME REPORTS HAVE ASSOCIATED (EFTS OF OVEREXPOSURE) Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure: HLTH HAZ: REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS.

First Aid:SKIN: PROMPTLY WASH W/SOAP & WATER. REMOVE & WASH ANY CONTAM CLTHG BEFORE REUSE. EYES: FLUSH W/LGE QTYS OF WATER FOR AT LEAST 15 MIN & SEEK MED ATTN. INGEST: DO NOT INDUCE VOMIT. KEEP PERS WARM, QUIET , & GET MED ATTN. ASPIR OF MATL INTO LUNGS CAN CAUSE CHEM PNEUMIT WHICH CAN BE FATAL. INHAL: REMOVE TO FRESH AIR IMMED. IF RESP SYMP DEVELOP, SEEK MED ATTN AT ONCE.

Flash Point Method:TCC Flash Point:100F,38C Lower Limits:1.0% Upper Limits:7.0% Extinguishing Media:USE FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER FOG, OR ANY CLASS B EXTINGUISHING AGENT. Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . WATER MAY BE UNSUITABLE AS EXTINGUISHING MEDIUM, BUT HELPFUL IN KEEPING ADJACENT CONTRS COOL. Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

Spill Release Procedures: REMOVE ALL SOURCES OF IGNIT. VENT AREA. ABSORB

PILL W/ABSORB MATL SUCH AS SAWDUST, VERMICULITE/SAND & PLACE INTO CLSD CONTR. IF LGE SPILL, DIKE AREA TO PVNT THIS MATL FROM ENTERING WATER SYS/SEWERS. WEAR PROT EQUIP DURING CLEANUP. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: AVOID PROLONGED OR REPEATED INHALATION OF HEATED VAPORS OR SPRAY MISTS. KEEP AWAY FROM HEAT OR OPEN FLAME. THIS MATERIAL MAY CAUSE SENSITIZATION.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR CLOTHING. DO NOT ALLOW CONTAMINATED CLOTHING TO CONTACT SKIN. DO NOT WELD ON FULL OR EMPTY CONTAINERS. KEEP CONTAINERS CLOSED WHEN NOT IN USE, AND PROPERLY LABELED.

Respiratory Protection: A NIOSH/MSHA APPROVED CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV OR PEL IS EXCEEDED. Ventilation: GEN VENT IS REQU IRED DURING NORM USE. LOC VENT MAY BE

REQUIRED DURING CERTAIN OPERATIONS TO KEEP EXPOS LEVEL < LIMITS. Protective Gloves:NITRILE, NEOPRENE OR RUBBER.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGS .

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EMERGENCY EYEWASH & DELUGE SHOWER MEETING ANSI DESIGN CRITERIA.

Work Hygienic Practices: WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

WASTE DISP METH: STDS. DISP I/A/W LOC, STATE & FED AGENC IES. GROUND

HNDLG EQUIP TO PVNT SPARKS. FOR FURTHER INFO CONT YOUR STATE/LOC WASTE AGENCY/UNITED STATES ENVIRON PROTECTION AGENCY'S RCRA HOTLINE (1-800-424-9346/1-202-382-3000).

Boiling Pt:B.P. Text:>281F,>138C Vapor Pres:9.5 Vapor Density:HVR/AIR Evaporation Rate & amp; Reference:FASTER THAN ETHER Solubility in Water:NIL Appearance and Odor:WHITE LIQUID, WITH MILD ODOR, OR COLOR OF TINT Percent Volatiles by Volum e:43.89

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES AND EPOXY HARDENERS UNDER UNCONTROLLED CONDITIONS.

Stability Condition to Avoid:HEAT, SPARKS AND OPEN FLAMES. IF PRODUCT CONTAINS ALUMINUM, MOISTURE IN CLOSED CONTAINERS WILL GENERATE HYDROGEN GAS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CABON MONOXIDE AND TOXIC VAPORS.

Waste Disposal Methods: IF DISCARDED, THIS MATL & CONTRS SHOULD BE TREATED AS HAZ WASTE BASED ON CHARACT OF IGNITABILITY AS DEFINED UNDER FED RCRA REGS (40 CFR 261). DISP OF THIS MATL/ITS CONTR REQUIRES COMPLIANCE W/APPLIC L ABELING, PACKAGING, & RECORDKEEPING (SUP DAT)

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The U nited States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.