

View NSN Online: <https://aerobasegroup.jp/nsn/6750-01-165-5425>

EASTMAN KODAK COMPANY -- 199 7915 VERSAMAT 885 DEVELOPER STARTER (WORKING SOLUTION) -- 6750-01-165-5425

===== Product Identification =====

Product ID:199 7915 VERSAMAT 885 DEVELOPER STARTER (WORKING SOLUTION)

MSDS Date:06/24/1992

FSC:6750

NIIN:01-165-5425

MSDS Number: BZQYD

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Count

ry:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

Company Name:FULLER

AND D ALBERT INC
Address:3170 CAMBELL
Box:2706
City:FAIRFAX
State:VA
ZIP:22031-2302
Country:US
Phone:703-591-8000
CAGE:82960

===== Composition/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 90-95%
Other REC Limits:NONE RECOMMENDED

Ingred Name:TRIETHYLENE GLYCOL
CAS:112-27-6
RTECS #:YE4550000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SULFITE
CAS:7757-83-7
RTECS #:WE2150000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA)
CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9596
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:POTASSIUM SULFITE
CAS:10117-38-1
RTECS #:WT3530000
Fraction by Wt: 100C
Vapor Pres:18MM @ 20C
Vapor Density:0.6
Spec Gravity:1.025
pH:10
Evaporation Rate & Reference:N/P (N-BUTYL ACETATE=1)
Solubility in Water:COMPLETE
Appearance and Odo

r: CLEAR, LIGHT YELLOW SOLUTION; ODORLESS.

Percent Volatiles by Volume: 90 %

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE WITH COMMON MATERIALS AND CONTAMINANTS WITH WHICH MATERIAL MAY REASONABLY COME INTO CONTACT.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: NONE.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

=====

Waste Disposal Methods: DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO LOCAL, STATE AND FEDERAL REGULATIONS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.