

NILES CHEMICAL PAINT CO -- N5223 YELLOW A/D ENAMEL, 13538 -- 8010-00-527-2045

=====
Product Identification
=====

Product ID:N5223 YELLOW A/D ENAMEL, 13538

MSDS Date:12/20/1995

FSC:8010

NIIN:00-527-2045

MSDS Number: BZSVN

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:3RD AND FORT ST

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3370 OR 219-236-585

6

Emergency Phone Num:616-683-3370 OR 219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:ALKYD RESIN SOLUTION

CAS:68459-31-4

Fraction by Wt: 46%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM/STEL 200 PPM

ingred Name: BUTYL ACETATE (VAPOR PRESSURE 10 MM HG @ 20C)
CAS: 123-86-4
RTECS #: AF7350000
Fraction by Wt: 29%
Other REC Limits: NONE SPECIFIED
OSHA PEL: 100 PPM
ACGIH TLV: 150 PPM/STEL 200 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

ingred Name: BARIUM SULFATE (SARA 313)
CAS: 7727-43-7
RTECS #: CR0600000
Fraction by Wt: 8%
Other REC Limits: NONE SPECIFIED
OSHA PEL: 5 MG/M3
ACGIH TLV: 10 MG/M3

ingred Name: ORGANOPHYLIC CLAY
CAS: 71011-25-1
Fraction by Wt: < 1%
Other REC Limits: NONE SPECIFIED

ingred Name:
COBALT COMPOUNDS (AS CO)
CAS: 7440-48-4
RTECS #: GF8750000
Fraction by Wt: < 1%
Other REC Limits: NONE SPECIFIED
OSHA PEL: 0.1 MG/M3; AS CO
ACGIH TLV: 2.0 MG/M3; DUST 9293

ingred Name: PROPRIETARY INGREDIENTS
Fraction by Wt: BALANCE
Other REC Limits: NONE SPECIFIED

ingred Name: VOC: 3.09 LB/GAL
RTECS #: 9999999VO
Other REC Limits: NONE SPECIFIED

ingred Name: XYLENES (O-,M-,P- ISOMERS)(SARA 313)(CERCLA)(VAPOR PRESSURE = 7.0)
CAS: 1330-20-7
RTECS #: ZE2100000
Fraction by Wt: 2.0%
Other REC Limits: NONE RECO

MMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACRYLIC RESIN
Fraction by Wt: 1.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:NOT EST.

Ingred Name:YELLOW PIGMENT
Fraction by Wt: 8.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:NOT EST.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO
IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYES: SEVERE IRRITATION,
LACRIMATION, REDNESS, BLURRED VISION. SKIN: REDNESS, IRRITATION.
DEFATTING OF SKIN LEADING TO DERMATITIS. INHALE: NASAL & RESP
IRRITATION, CNS DEPRESSION. DIZZINESS, DR OWSINESS, WEAKNESS,
FATIGUE, CONFUSION.NAUSEA, HEADACHE, VERTIGO, UNCONSCIOUSNESS,
ASPHYXIATION. CHRONIC DERMATITIS.*
Explanation of Carcinogenicity:NA
Effects of Overexposure:*INGESTION: GASTROINTESTINAL IRRITATION,
ABDOMINA
L PAIN, NAUSEA, VOMITING, DIARRHEA. TARGET ORGANS: LIVER,
KIDNEYS, EYES, SKIN, RESPIRATORY SYSTEM, NUISANCE DUST, CNS, GI
TRACT. CHRONIC EFFECTS OVEREX POSURE: DERMATITIS, INCOHERENCE,
CORNEAL VACUOLIZATION, ANOREXIA.
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:INHAL: GET FRESH AIR. RESTORE BREATHING. GET MED AID IMMED.
SKIN: IMMED FLUSH SKIN W/WATER. IF MATERIAL PENETRATES CLOTHING
REMOVE & W

ASH BEFORE REUSE. GET MEDICAL ATTENTION. EYES:

IMMEDIATELY FLUSH EYES WITH LOTS WATER > 15 MINS, LIFTING EYELIDS OCCASIONALLY. GET MED AID IMMED. INGEST: DRINK 1-2 GLASSES WATER. DON'T INDUCE VOMITING. SEE DR/POINSON CONTROL CTR IMMEDIATELY. TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:72.0F,22.2C

Lower Limits:0.8

Upper Limits:7.6

Extinguishing Media:DRY CHEMICAL, FOAM, CO2.

Fire Fighting Procedure:

WEAR SCBA W/FULL FACEPIECE OPERATED IN

POSITIVE PRESSURE MODE. WATER USED TO COOL CLSD CNTNRS TO PREVENT BUILDUP & POSSIBLE AUTO IGNITION OR EXPLO EXPOS TO HEAT

Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLSD. VAPORS > AIR

TRAVEL ALONG GRND TO AN IGNITION SOURCE. ISOLATE FM ALL HEAT TYPES. CLSD CNTNRS MAY EXPLODE EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. DON'T BREATHE

VAPORS. AVOID SKIN CONTACT. ABSORB WITH INERT MATERIAL. SHOVEL RECLAIMED INTO DRUMS FOR DISPOSAL. DIKE TO PREVENT FURTHER MOVEMENT & RECLAIM INTO RECOVERY OR SALVAGE DRUMS OR TANK TRUCK FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMPERATURE AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR AN APPROPRIATE (TYPE TC-23C-75) PROPERLY FITTED HALF-MASK OR FULL FACEPIECE RESPIRATOR (NIOSH/MSHA) DURING & AFTER APPLICATION UNLESS AIR MONITORING KEEPS VAPOR/MIST BELOW APPLICABLE LEVELS. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS.

Ventilation:SUFFICIENT VENT IN VOLUME/PATTERN TO KEEP AIR CONCENTRA

TION

BELOW ACGIH'S TLV LIMIT.

Protective Gloves:CHEMICAL RESISTANT, NITRILE, VITON

Eye Protection:CHEMICAL/SAFETY GLASSES, FACE SHIELD

Other Protective Equipment:CLOTHING AS NEEDED TO PREVENT SKIN CONTACT

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, USING

RESTROOMS. REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

DON'T WEAR CONTACT LENSES WHEN WORKING WITH THIS MATERIAL.

===== Physical/Chemical Properties =====

Bo

iling Pt:B.P. Text:212 TO 398F

Decomp Temp:Decomp Text:NE

Vapor Density:> AIR

Spec Gravity:1.061

pH:NA

Viscosity:70-75 KU

Evaporation Rate & Reference:< ETHER

Solubility in Water:YES

Appearance and Odor:LIQUID, ODOR OF SOLVENTS

Percent Volatiles by Volume:42.19

Corrosion Rate:MINIMAL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS.

Stability Condition to Avoid:HIGH TEMPERATURES, SHOCK

FROM DROPPING.

Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND/OR
CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL,
STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly

or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.