

ELSCO INTERNATIONAL -- BLAST OFF RUST

=====

MSDS Safety Information

=====

FSC: 7930

NIIN: 01-381-3442

MSDS Date: 01/31/1994

MSDS Num: CBTZF

Product ID: BLAST OFF RUST

MFN: 01

Responsible Party

Cage: 52790

Name: ELSCO INTERNATIONAL

Address: 3407 E STREET

City: SAN DIEGO CA 92102

Info Phone Num

ber: 619-696-6609

Emergency Phone Number: 619-696-6609

Preparer's Name: W R MENYHERT

Proprietary Ind: Y

Review Ind: Y

Published: Y

=====

Preparer Co. when other than Responsible Party Co.

=====

Cage: 52790

Name: ELSCO INTERNATIONAL

Address: 3407 E ST

City: SAN DIEGO CA 92102

=====

Contractor Summary

=====

=====

Cage: 52790

Name: ELSCO INTERNATIONAL

Address: 3407 E ST

City: SAN DIEGO CA 92102

Phone: 619-696-6609; -8609 (FAX)

=====

Item Description Information

=====

Item Manager: GSA

Item Name: DETERGENT,GENERAL PURPOSE

Unit of Issue: BX

Quantitative Expression: 00000000012EA

UI Container Qty: 1

=====

Ingredients

=====

=====

Name: *** PROPRIETARY ***

=====

Health Hazards Data

=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: NO

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: NAUSEA MAY OCCUR WHEN TAKEN INTERNALLY-NOT TOXIC. NAUSEA OR DIZZINESS MAY OCCUR BUT WOULD BE EXTREMELY RARE. COULD IRRITATE MUC MEMBS.

WEAR OSHA/NIOSH/MSHA APPROVED FACE MASK IF EXPOSED TO MATL FOR LO NG PERIODS OF TIME. ALTHOUGH PROD IS INHIBITED & CORROSION CONTROL, PROLONGED EXPUSURE CAUSES SKIN DRYING/IRRITATION.

Explanation Of Carcinogenicity: NOT RELEVANT

Signs And Symptions Of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated By Exposure: COULD CAUSE SLIGHT SKIN RASH IF OVEREXPOSURE OCCURS. COULD CAUSE EYE DAMAGE BY EXTENDED CONTACT.

First Aid: INHAL:REMOVE TO FRESH AI

R. SUPPORT BREATHING (GIVE O2/ARTF RESP) (FP

N). EYES:IMMEDIATELY FLUSH W/POTABLE WATER FOR A MINIMUM OF 15 MINUTES, SEEK ASSISTANCE FROM MD (FP N). INGEST:DRINK COPIOUS AMOUNT S OF WATER. SKIN:USE REGULAR SOAP OR PLAIN WATER TO WASH MAT'L OFF SKIN/CLOTHES. GET MEDICAL AID IF IRRITATION OR SYMPTOMS SEEM AGGRAVATED.

=====

Handling and Disposal

=====

Spill Release Procedures: ABSORB SPILLS W

ITH DRY SAND OR EARTH, THEN PLACE IN

CHEMICAL WASTE CONTAINER FOR DISPOSAL. FLUSH RESIDUAL AREA WITH WATER.

Neutralizing Agent: WATER, SODA ASH OR OTHER ALKALINE PRODUCTS.

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL, STATE OR FEDERAL LAWS.

REMEMBER SOME STATES ABSOLUTELY FORBID ANYTHING EXCEPT RAINWATER TO GO INTO DRAINAGE SYSTEMS.

Handling And Storage Precautions: STORE IN PLASTIC, RUBBER LINED, OR 316

STAINLESS STEEL CONTAINERS. STORE AWAY FROM EXTREME HEAT. DO NOT GET IN EYE

S,
ON SKIN OR CLOTHING.
Other Precautions: AVOID BREATHING MIST. KEEP CONTAINER CLOSED. KEEP OUT OF
REACH OF CHILDREN. USE WITH ADEQUATE VENTILATION.

=====

Fire and Explosion Hazard Information

=====

Flash Point Method: OC
Flash Point Text: NONE
Extinguishing Media: MEDIA SUITABLE FOR SURROUNDING FIRE (FP N).
Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT (FP N).

=====

Control Measures

=====

Respiratory Protection: AVOID BREATHING MIST. IF PRODUCT IS BEING SPRAYED WEAR
NIOSH/MSHA APPROVED MASK.
Ventilation: USE WITH ADEQUATE VENTILATION.
Protective Gloves: NIOSH/MSHA OR RECOMMENDED.
Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).
Other Protective Equipment: IF SPRAYING IN WINDY SITUATION WEAR CHEMICAL
RESISTANT CLOTHING.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health: SPEC GRAV:1.11/12.05 BE' (H*2O=1).

=====

Physical/Chemical Properties

=====

B.P. Text: 270F,132C
M.P/F.P Text: 25.0F,-3.9C
Vapor Pres: 850 MM/HG
Spec Gravity: 1.11/12.05
PH: 1.8
Evaporation Rate & Reference: 1.42 (H*2O=1)
Solubility in Water: 98.0
Appearance and Odor: PURPLE & VISCOUS, LILAC ODOR.

=====

Reactivity Data

=====

Stability Indicator: YES
Materials To Avoid: ALKALINE, SULFIDES AND SULFIDE PRODUCTS.
Hazardous Decomposition Products: NONE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT

=====

Toxicological Information

=====

=====

=====

Ecological Information

=====

=====

MSDS Transport Information

=====

=====

Regulatory Information

=====

=====

Other Information

=====

=====

=====

Transportation Information

=====

Responsible Party Cage: 52790

Trans ID NO: 131843

Product ID: BLAST OFF RUST

MSDS Prepared Date: 01/31/1994

Review Date: 07/22/1996

MFN: 1

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: BX

Container QTY: 1

=====

Detail DOT Information

=====

DO

T PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

=====

Detail IMO Information

=====

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

=====

Detail IATA Information

=====

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT

REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: BLAST OFF RUST

Cage: 52790

Company Name: ELSCO INTERNATIONAL

Street: 3407 E ST

City: SAN DIEGO C

A

Zipcode: 92102

Health Emergency Phone: 619-696-6609

Label Required IND: Y

Date Of Label Review: 10/12/1999

Status Code: A

Origination Code: G

Hazard And Precautions: NAUSEA MAY OCCUR WHEN TAKEN INTERNALLY-NOT TOXIC.

NAUSEA OR DIZZINESS MAY OCCUR BUT WOULD BE EXTREMELY RARE. COULD IRRITATE MUC
MEMBS. WEAR OSHA/NIOSH/MSHA APPROVED FACE MASK IF EXPOSED TO MATL FOR LO NG
PERIODS OF TIME. ALTHOUGH PROD IS INHIBITED & CORROSION CONTROL,
PROLONGED EXPUSURE CAUSES SKIN DRYING/IRRITATION.

=

Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumen

tality of the United

States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.