

PYRAMID PLASTICS INC, TOLBER D -- MICROPATCH - BLACK

=====
MSDS Safety Information
=====

FSC: 8040
NIIN: 01-089-5730
MSDS Date: 10/15/1993
MSDS Num: CCBGD
Product ID: MICROPATCH - BLACK
MFN: 01
Responsible Party
Cage: 59460
Name: PYRAMID PLASTICS INC, TOLBER DIVISION
Address: 220 W 5TH ST
City: HOPE AR 7180
1-5212
Info Phone Number: 501-777-5750
Emergency Phone Number: 800-264-2535
Proprietary Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 59460
Name: PYRAMID PLASTICS INC, TOLBER DIVISION
Address: 220 W 5TH ST
City: HOPE AR 71801-5212
Phone: 501-777-5759

=====
Item Description Information
=====

=====
Item Manager: N35
Item Name: MICRO-PATCH LIQUID
Unit of Issue: GL
UI Container Qty: 1

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====
Health Hazards Data
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry Inds - Inhalation: YES
Skin:

YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: SKIN: PROLONGED SKIN CONTACT MAY CAUSE IRRITATION IN SOME INDIVIDUALS. EYES: DIRECT CONTACT MAY CAUSE PAINFUL STINGING OR BURNING OF EYES AND LIDS, WATERING EYES. INHALATION: PROLONGED BREATHING OF VA PORS FROM FUSING OPERATION MAY CAUSE LUNG IRRITATION, DIZZINESS, HEADACHES, NAUSEA. INGESTION: (EFTS OF OVEREP)

Explanation Of Carcinogenicity: NOT RELEVANT

Signs And Symptions Of Overexposure: HLTH HA

Z: DEPENDING ON DEGREE OF EXPOSURE

AND INDIVIDUAL SUSCEPTIBILITY SYMPTOMS MAY INCLUDE METALLIC TASTE, FATIGUE, HEADACHES, INTERMITTENT STOMACH CRAMPS, MUSCLE ACHES AND WEAKNESS. CHRONIC: HEADAC HE, DIZZINESS, NAUSEA, SHORTNESS OF BREATH AND BLURRED VISION POSSIBLE UPON PROLONGED EXPOSURE.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: SKIN: WASH WITH SOAP AND WATER FOR 15 MINUTES. CONSULT MD IF IRRITATION PERSISTS. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. CONSULT

MD IF IRRITATION PERSISTS. INGESTION: DRINK WATER. DO NOT INDU CE VOMITING. CONSULT MD IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR.

=====
Handling and Disposal

=====
Spill Release Procedures: SCOOP INTO DRUMS, ABSORB REMAINDER ON INERT FILLER. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Dispo

sal Methods: DISPOSE OF WASTE AND CONTAINER IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: AVOID BREATHING FUMES EMITTED DURING DRYING.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

=====
Fire and Explosion Hazard Information

=====
Flash Point Method: TCC

Flash Point Text: 36.0F,2.2C

Lower Limits: 2%

Upper Limits: 12%

Extinguishing Media: CARBON

DIOXIDE, DRY CHEMICAL, FOAM OR WATER SPRAY.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT (FP N).

Unusual Fire/Explosion Hazard: VOLATILE MATERIAL. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL TO IGNITION SOURCE AND FLASH BACK.

=====
Control Measures
=====

Respiratory Protection: NOT REQUIRED WITH ADEQUATE VENTILATION. IN RESTRICTED VENTILATION AREAS, WE AR NIOSH/MSHA APPROVED CHEMICAL/MECHANICAL FILTERS TO REMOVE FUMES OR MIST.

Ventilation: EXHAUST SYSTEM SHOULD BE SUFFICIENT TO REMOVE VAPORS EMITTED DURING DRYING.

Protective Gloves: USE NEOPRENE OR VINYL GLOVES.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N).

Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER (FP N). PROTECTIVE CLOTHING IF SKIN CONTACT IS LIKELY.

Work Hygienic Practices: WASH HANDS BEFORE EATING, USING BATHROOM, SMOKING, ETC. WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health: NONE SPECIFIED BY MANUFACTURER.

=====
Physical/Chemical Properties
=====

HCC: F2

B.P. Text: 122F,50C

M.P/F.P Text: 122F,50C

Vapor Density: 1

Spec Gravity: 1.2

Evaporation Rate & Reference: 1.4 (BUAC=1)

Solubility in Water: NIL

Appearance and Odor: BLACK LIQUID; KETONE ODOR.

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: HEAT, SPARK AND FLAMES.

Materials To Avoid: OXIDIZING MATERIALS CAN CAUSE A REACTION.

Hazardous Decomposition Products: HYDROGEN CHLORIDE, CARBON MONOXIDE AND CARBON DIOXIDE AT ELEVATED TEMPERATURES.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT

=====
Toxicological Information
=====

=====
=====
Ecological Information
=====
=====

=====
=====
MSDS Transport Information
=====
=====

=====
=====
Regulatory Information
=====
=====

=====
=====
Other Information
=====
=====

=====
=====
Transportation Information
=====
=====

Responsible Party Cage: 59460
Trans ID NO: 106570
Product ID: MICROPATCH - BLACK
MSDS Prepared Date: 10/15/1993
Review Date: 01/07/1997
MFN: 1
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: GL
Container QTY: 1
=====
==

=====
=====
Detail DOT Information
=====
=====

DOT PSN Code: GJJ
Symbols: G
DOT Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.
Hazard Class: 3
UN ID Num: UN1993
DOT Packaging Group: II
Label: FLAMMABLE LIQUID
Special Provision: T8,T31
Non Bulk Pack: 202
Bulk Pack: 242
Max Qty Pass: 5L
Max Qty Cargo: 60 L
Vessel Stow Req: B
=====
=====

=====
=====
Detail IMO Information
=====
=====

IM

O PSN Code: HIN
IMO Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. o
IMDG Page Number: 3230
UN Number: 1993
UN Hazard Class: 3.2
IMO Packaging Group: I/II
Subsidiary Risk Label: -
EMS Number: 3-07
MED First Aid Guide NUM: T

=====
Detail IATA Information
=====

IATA PSN CA
IATA UN ID Num: 1993
IATA Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. *
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
UN Pac
king Group: III
Packing Note Passenger: 309
Max Quant Pass: 60L
Max Quant Cargo: 220L
Packaging Note Cargo: 310

=====
Detail AFI Information
=====

AFI PSN CA
AFI Symbols: *
AFI Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.
AFI Hazard Class: 3
AFI UN ID NUM: UN1993
AFI Packing Group: III
Special Provisions: P5
Back Pack Reference: A7.3

=====
HAZC
OM Label
=====

Product ID: MICROPATCH - BLACK
Cage: 59460
Company Name: PYRAMID PLASTICS INC, TOLBER DIVISION
Street: 220 W 5TH ST
City: HOPE AR
Zipcode: 71801-5212
Health Emergency Phone: 800-264-2535
Label Required IND: Y
Date Of Label Review: 07/24/1997
Status Code: C
Label Date: 07/24/1997
Origination Code: G
Chronic Hazard IND: Y
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER
Respiratory Protection IND: YES
Health Haza

rd: Moderate

Contact Hazard: Moderate

Fire Hazard: Severe

Reactivity Hazard: None

Hazard And Precautions: EXTREMELY FLAMMABLE. ACUTE: SKIN: PROLONGED CONTACT MAY CAUSE IRRITATION IN SOME INDIVIDUALS. EYES: DIRECT CONTACT MAY CAUSE PAINFUL STINGING OR BURNING OF EYES AND LIDS, WATERING EYES. INHALATION: PROLONGED BREATHING OF VAPORS FROM FUSING OPERATION MAY CAUSE LUNG IRRITATION, DIZZINESS, HEADACHES, NAUSEA. INGESTION: METALLIC TASTE, FATIGUE, HEADACHES, INTERMITTENT STOMACH CRAMPS, M

MUSCLE ACHES AND WEAKNESS. CHRONIC: HEADACHES, DIZZINESS, NAUSEA, SHORTNESS OF BREATH AND BLURRED VISION.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.