View NSN Online: https://aerobasegroup.jp/nsn/1377-01-271-9072

Product ID:51483-1 EXPLOSIVE ONE WAY TRANSFER ASSEMBLY MSDS Date:01/11/1996 FSC:1377 NIIN:01-271-9072 MSDS Number: CCGMS === Responsible Party === Company Name: OEA AEROSPACE INC. Address: HWY 12 AND ET RD Box:KK City:FAIRFIELD State:CA ZIP:94533-0659 Country:US Info Phone Num:707 -422-1880 Emergency Phone Num:707-422-1880 Preparer's Name:S SCHOOLFIELD/J KOHRING CAGE:17610 === Contractor Identification === Company Name: OEA AEROSPACE INC Address:3530 BRANSCOMBE RD Box:KK City:FAIRFIELD State:CA ZIP:94533-0659 Country:US Phone:707-422-1880 CAGE:17610

Ingred Name:HEXANITROSTILBENE I ACGIH TLV:10 MG/CUM

Ingred Name: HEXANITROSTILBENE II

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: IRRITATION TO THE NOSE, THROAT, MUCOUS MEMBRANE & ALLERGIC REACTIONS. SKIN: IRRITATION & POSSIBLE ALLERGIC REACTIONS. EYES: IRRITATION. INGESTION: TOXIC. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION, NAUSEA, REDNESS.
======================================
First Aid:EYES: FLUSH W /WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Extinguishing Media:DON'T ATTEMPT TO EXTINGUISH. Fire Fighting Procedures:EVACUATE AREA. USE SCBA TO CONTAIN RESULTING FIRE. Unusual Fire/Explosion Hazard:IF EXPOSED TO FIRE, THE UNIT MAY ACTUATE/EXPLODE.
======================================
Spill Release Proce dures:CALL LOCAL HAZARDOUS MATERIALS TEAM. REMOVE IGNITION SOURCES. COVER/EXPOSED MATERIAL W/VEGETABLE OIL & REMOVE FOR APPROVED DISPOSAL. USE FLAME RETARDANT CLOTHING, SAFETY GLASSES & NON-SPARKING TOOLS.
======================================
Handling and Storage Precautions:DON'T STORE AT TEMPS >200F. Other Precautions:ANTI-STATIC BAGS SHALL BE USED FOR STORAGE & SHIPPING.

Resp

iratory Protection:USE NIOSH APPROVED HEPA RESPIRATOR IF PEL/TLV IS EXCEEDED.
Ventilation:LOCAL EXHAUST: REQUIRED FOR TEST FIRING.
Protective Gloves:POLY-BENZ-IMIDAZOLE/LEATHER
Eye Protection:SAFETY GLASSES AS A MINIMUM.
Other Protective Equipment:FLAME RETARDANT COAT & GROUNDING STRAPS TO PREVENT ELECTROSTATIC DISCHARGE.
Supplemental Safety and Health

Solubility in Water:LOW Appearance and Odor:HNS: YELLOW POWDER; OD ORLESS

Stability Indicator/Materials to Avoid:YES AKALIS, ACIDS, COPPER, BRONZE, CORROSIVES, OXIDIZERS, WATER. Stability Condition to Avoid:MECHANICAL SHOCK, STATIC ELECTRICITY, HEAT, FLAME/SPARKS.

Hazardous Decomposition Products:CO, NITROGEN, NITROUS OXIDES, HYDROGEN, CARBON, CO2.

Waste Disposal Methods:UNFIRED UNITS/WASTE SHOULD BE DISPOSED AS

REACTIVE HAZARDOUS WASTE, D003, IAW/FEDERAL, STATE & LOCAL REGULATIONS. UN 0367.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and ass

ume responsibility for the suitability of this information to their particular situation.