

MPD INC.(FORMERLY GENERAL ELECTRIC CO) -- ELECTRON VACUUM TUBES -- 5960-00-062-4894

===== Product Identification =====

Product ID:ELECTRON VACUUM TUBES

MSDS Date:03/15/1994

FSC:5960

NIIN:00-062-4894

MSDS Number: CCLMS

=== Responsible Party ===

Company Name:MPD INC.(FORMERLY GENERAL ELECTRIC CO)

Address:316 E 9TH STREET

City:OWENSBORO

State:KY

ZIP:42301-2312

Country:US

Info Phone Num:502-685-6200

Emergency Phone Num:502-685-6200

CAGE:33173

=== Contractor Identi

fication ===

Company Name:MPD INC.(FORMERLY GENERAL ELECTRIC CO)

Address:316 E 9TH STREET

City:OWENSBORO

State:KY

ZIP:42303-2312

Country:US

Phone:502-685-6200

CAGE:33173

===== Composition/Information on Ingredients =====

Ingred Name:RHENIUM 187 (COMPOSITION OF INTERNAL HEATER WIRE FILAMENTS)
(SPEC ACTIVITY 0.00445MICROCURIE/GRAM).

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

Ingred Name:TUNGSTEN INCLUDING INGRED #3. (NOT RADIOACTIVE)

CAS:7440-33-7

RTECS #:YO71750

00

Fraction by Wt: BALANCE

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

Ingred Name:RHENIUM 185 INCLUDING INGREDIENTS #2 (NOT RADIOACTIVE).

Fraction by Wt: SEE #2%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE MINOR SKIN

BURNS. ELECTRON
TUBES OPERATE @TEMP THAT CAN PRODUCE BURNS TO SKIN IF CONTACT IS
MADE.
Effects of Overexposure:ELECTRONG TUBES OPERATE @TEMPS THAT CAN PRODUCE
BURNS TO SKIN IF CONTACT IS MADE.
Medical Cond Aggravated by Exposure:NONE KNOWN.

===== First Aid Measures =====

First Aid:NO EMERGENCY CAR ANTICIPATED.

===== Fire Fighting Measures =====

Flash Point:NA
Autoignition Temp:Autoignition Temp Text:NA
Lower
Limits:NA
Upper Limits:NA
Extinguishing Media:MATERIAL IS NON-FLAMMABLE.
Fire Fighting Procedures:NONE.
Unusual Fire/Explosion Hazard:ELECTRON TUBES OPERATE UNDER HIGH VACUUM
& IMPLOSION COULD OCCUR @HIGH TEMP DURING FIRES OR DURING DISPOSAL
PROCEDURES.

===== Accidental Release Measures =====

Spill Release Procedures:NONE.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and St
orage Precautions:NONE
Other Precautions:CALCULATED SPECIFIC ACTIVITY OF FILAMENT IS
0.000089MICROCURIE/GRAM.IF VIEWED FROM TOTAL MASS THE TUBE ITSELF
WOULD HAVE EVEN LOWER SPECIFIC ACTIVITY.MILHBDK 600 SPECIFIES MATL
CONSIDERED RADIOACTIVE, IONIZING RADIATION MUST EXCEED (SUPPLEM)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:NONE
Protective Gloves:COTTON.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:NONE
W

ork Hygienic Practices:NONE
Supplemental Safety and Health
OTHER PRECAUT:0.002MICROCURIE/GRAM;THEREFORE PRODUCT NOT RADIOACTIVE &
THEREFORE NOT HAZARDOUS.

===== Physical/Chemical Properties =====

HCC:A2
Boiling Pt:B.P. Text:NA
Melt/Freeze Pt:M.P/F.P Text:NA
Decomp Temp:Decomp Text:NP
Vapor Pres:NA
Vapor Density:NA
Spec Gravity:NA
pH:NP
Viscosity:NP
Evaporation Rate & Reference:NA
Solubility in Water:NONE.
Appearance and Odor:GLASS ENVELOPE, NO ODOR.
Percent
Volatiles by Volume:NP
Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE.
Stability Condition to Avoid:NONE.
Hazardous Decomposition Products:NONE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE
FED/STATE/LOC REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is for
mulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.