View NSN Online: https://aerobasegroup.jp/nsn/5960-00-062-4894

Product ID:ELECTRON VACUUM TUBES

MSDS Date:03/15/1994

FSC:5960

NIIN:00-062-4894

MSDS Number: CCLMS === Responsible Party ===

Company Name: MPD INC. (FORMERLY GENERAL ELECTRIC CO)

Address:316 E 9TH STREET

City:OWENSBORO

State:KY

ZIP:42301-2312 Country:US

Info Phone Num:502-685-6200

F

mergency Phone Num:502-685-6200

CAGE:33173

=== Contractor Identification ===

Company Name: MPD INC. (FORMERLY GENERAL ELECTRIC CO)

Address:316 E 9TH STREET

City:OWENSBORO

State:KY

ZIP:42303-2312

Country:US

Phone:502-685-6200

CAGE:33173

====== Composition/Information on Ingredients ========

Ingred Name:RHENIUM 187 (COMPOSITION OF INTERNAL HEATER WIRE FILAMENTS)

(SPEC ACTIVITY 0.00445MICROCURIE/GRAM).

Fraction by Wt: 2%

Other REC Limits: NONE RECOMMENDED

Ingred Name: TUNGSTEN INCL

UDING INGRED #3. (NOT RADIOACTIVE)

CAS:7440-33-7

RTECS #:YO7175000 Fraction by Wt: BALANCE

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3

Ingred Name:RHENIUM 185 INCLUDING INGREDS #2 (NOT RADIOACTIVE).

Fraction by Wt: SEE #2%

Other REC Limits: NONE RECOMMENDED

========== Hazards Identification ============

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:

NO OSHA:NO Health Hazards Acute and Chronic: MAY CAUSE MINOR SKIN BURNS. ELECTRON TUBES OPERATE @TEMP THAT CAN PRODUCE BURNS TO SKIN IF CONTACT IS MADE. Effects of Overexposure: ELECTRONG TUBES OPERATE @TEMPS THAT CAN PRODUCE BURNS TO SKIN IF CONTACT IS MADE. Medical Cond Aggravated by Exposure: NONE KNOWN. First Aid:NO EMERGENCY CAR ANTICIPATED. Flash Point:NA Autoignition Temp: Autoignition Temp Text: NA Lower Limits:NA **Upper Limits:NA** Extinguishing Media: MATERIAL IS NON-FLAMMABLE. Fire Fighting Procedures: NONE. Unusual Fire/Explosion Hazard: ELECTRON TUBES OPERATE UNDER HIGH VACUUM & IMPLOSION COULD OCCUR @HIGH TEMP DURING FIRES OR DURING DISPOSAL PROCEDURES. ======== Accidental Release Measures ============ Spill Release Procedures: NONE. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

== Handling and Storage ===========

Handling and Storage Precautions: NONE

Other Precautions:CALCULATED SPECIFIC ACTIVITY OF FILAMENT IS 0.000089MICROCURIE/GRAM.IF VIEWED FROM TOTAL MASS THE TUBE ITSELF WOULD HAVE EVEN LOWER SPECIFIC ACTIVITY.MILHBDK 600 SPECIFIES MATL CONSIDERED RADIOACTIVE, IONIZING RADIATION MUST EXCEED (SUPPLEM)

====== Exposure Controls/Personal Protection ========

Respiratory Protection: NONE

Ventilation:NONE

Protective Gloves: COTTON.

Supplemental Safety and Health OTHER PRECAUT:0.002MICROCURIE/GRAM;THEREFORE PRODUCT NOT RADIOACTIVE & THEREFORE NOT HAZARDOUS.
========= Physical/Chemical Properties =========
HCC:A2 Boiling Pt:B.P. Text:NA Melt/Freeze Pt:M.P/F.P Text:NA Decomp Temp:Decomp Text:NP Vapor Pres:NA Vapor Density:NA Spec Gravity:NA PH:NP Viscosity:NP Evaporation Rate & amp; Reference:NA Solubility in W ater:NONE. Appearance and Odor:GLASS ENVELOPE, NO ODOR. Percent Volatiles by Volume:NP
Corrosion Rate:NP ====================================
Stability Indicator/Materials to Avoid:YES NONE. Stability Condition to Avoid:NONE. Hazardous Decomposition Products:NONE.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FED/STATE/LOC REGULATIONS.

======= Disposal Considerations ============

Disclaimer (provided with this

information by the compiling agencies):

Eye Protection:SAFETY GLASSES. Other Protective Equipment:NONE Work Hygienic Practices:NONE

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.