

RADIATOR SPECIALTY COMPANY -- SOLDER SEAL LIQUID WRENCH NO1 (AEROSOL), PN L1-06;-12
-- 9150-00-973-9504

===== Product Identification =====

Product ID:SOLDER SEAL LIQUID WRENCH NO1 (AEROSOL), PN L1-06;-12

MSDS Date:04/01/1997

FSC:9150

NIIN:00-973-9504

MSDS Number: CCLTZ

=== Responsible Party ===

Company Name:RADIATOR SPECIALTY COMPANY

Address:1400 W. INDEPENDENCE BLVD.

City:CHARLOTTE

State:NC

ZIP:2

8208

Country:US

Info Phone Num:704-377-6555

Emergency Phone Num:704-377-6555

Preparer's Name:T.LIEBMAN,TECH DIR

CAGE:77628

=== Contractor Identification ===

Company Name:BALKAMP INC

Address:2601 S HOLT ROAD

Box:City:INDIANAPOLIS

State:IN

ZIP:46241

Country:US

Phone:317-244-7241

CAGE:70842

Company Name:NAPA, A DIVISION OF LINCOLN AUTOMOTIVE

Address:ONE LINCOLN WAY

Box:City:ST. LOUIS

State:MO

ZIP:63120-1578

Country:US

Phone:414-255-5520

CAGE:050Q3

Company Name:RADIATOR SPECIALTY COMPANY

Address:190

0 WILKINSON BLVD.
Box:34689
City:CHARLOTTE
State:NC
ZIP:28208
Country:US
Phone:704-377-6555/303-623-5716
CAGE:77628

===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETROLEUM SOLVENT
CAS:8008-20-6
RTECS #:OA5500000
Fraction by Wt: 89-90%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PETROLEUM MINERAL OIL
CAS:64742-06-9
Fraction by Wt: 8-9%
Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON DIOXIDE (PROPELLANT)
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 2-3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;96

===== Hazards Identification =====

LD50 LC50 Mixture:TLV:5MG/M3 (MIST) PETROLEUM MINERAL OIL
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE:IRRIT. SKIN:IRRIT,PROLONG EXPO CAN
CAUSE DERMATITIS. INHAL:EXCESSIVE INHAL CAN CAUSE
DIZZ,RESPIRATORYMLUNG IRRIT. ING
EST:HARMFUL OR FATAL IF
SWALLOWED!!CAN CAUSE GASTRIC DISTURBANCE,NAUSEA.ASPIRATION CAN
LEAD TO LUNG IRRIT.
Explanation of Carcinogenicity:PER MSDS:PETROLEUM MINERAL OIL POSSIBLE
CARCINOGEN BY NTP.
Effects of Overexposure:EYE/SKIN IRRIT. DERMATITIS. DIZZINESS,
RESP/LUNG IRRIT. HARMFUL OR FATAL IF INGEST. GASTRIC DISTURBANCES,
NAUSEA, ASPIRATION LUNG IRRIT.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

=====

First Aid:EYE:FLUSH W/WATER FOR 15MINS THOROUGHLY WHILE LIFTING EYELIDS.IF ADVERSE EFFECTS PERSIST GET MED ATTN IMMED. SKIN:WASH W/SOAP/WATER THOROUGHLY.REMOVE CONTAMIN CLOTH. INHAL:REMOVE TO FRESH AIR.BREATHIN G DIFFICULT ADMIN OXYGEN.BREATH STOPPEDAPPLY ARTIFICIAL RESP.GET MED ATTN. INGEST:DO NTO INDUC VOMIT.GET MED ATTN IMMED.DO NOT ADMIN EPINEPHRINE OR ADRENALIN!!

===== Fire Fighting Measures =====

Flash Point Method:T
CC
Flash Point:>120F,>49C
Lower Limits:NP
Upper Limits:NP
Extinguishing Media:FOAM,CO2,DRY CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED POSITIVE PRESSURE BREATHING APPARATUS & PROTECTIVE CLOTHES.WATERSPRAY TO COOL CNTNR.SHIELD TO PROTECT FROM VENTING/RUPTURING/BURSTING CANS.
Unusual Fire/Explosion Hazard:AT ELEVATED TEMPERATURES CONTAINERS MAY VENT,RUPTURE OR BURST EVEN VIOLENTLY.

===== Accidental Release Measures =====

Spill Release Procedures
:OBSERVING HEALTH HAZDARDS DESCRIBED IN MSDS
REMOVE IGN SOURCE, VENTILATE AREA. CONFINE SPILL, WIPE-UP W/RAGS & TRANSFER TO WASTE DRUM.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM IGN SOURCES AND OXIDIZERS!STORE IN COOL PLACE.
Other Precautions:WEARING CONTACT LENSES IS INADVISABLE.DO NOT PUNCTURE OR INCINERATE CONTAINERS.KEEP AWAY FROM CHILDREN AND ANIMALS

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CONSUMER:NA. BULK HNDLG:USE NIOSH APPROVED SELF-CONTAINED RESPIRATOR.
Ventilation:CONSUMER:USE W/ADEQUATE VENTILATION. BULK HNDLG:GENERAL.
Protective Gloves:CONSUMER:NA.BULK:SOLVENT RESIST GLOVES.
Eye Protection:CONSUMER:NA.BULK:FULLY PROT GOGG/FCSHIEL
Other Protective Equipment:CONSUMER:NA. BULK HNDLG:SOLVENT RESIST APRON.
Work Hygienic Practices:LAUNDER CONTAMIN CLOTHING BEFORE REUSE.
Supplem

ental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>300F,>149C

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NP

Vapor Pres:NA

Vapor Density:NA

Spec Gravity:0.82

pH:NA

Evaporation Rate & Reference:NA

Solubility in Water:INSOLUBLE.

Appearance and Odor:DARK LIQUID WITH PETROLEUM ODOR.

Percent Volatiles by Volume:90

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Ind

icator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. HMIS:ALL

IGNITION SOURCES.

Hazardous Decomposition Products:FIRE:NORMAL PRODUCTS OF

COMBUSTION,SMOKE,CARBON DIOXIDE,CARBON MONOXIDE,SUFLUR TRIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE IWTH ALL APPLICABLE
GOVERNMENT LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compili
ng agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.