

DREW CHEMICAL CORP,DIV OF ASHLAND CHEMICAL CO -- 4641 PERFORMAX 401 CORROSION INHIBITOR -- 6810-01-313-9541

===== Product Identification =====

Product ID:4641 PERFORMAX 401 CORROSION INHIBITOR

MSDS Date:02/10/1995

FSC:6810

NIIN:01-313-9541

MSDS Number: CCVTW

=== Responsible Party ===

Company Name:DREW CHEMICAL CORP,DIV OF ASHLAND CHEMICAL CO

Address:ONE DREW CHEMICAL PLAZA

City:BOONTON

State:NJ

ZI

P:07005

Country:US

Info Phone Num:201-263-7600

Emergency Phone Num:606-324-1133

CAGE:52454

=== Contractor Identification ===

Company Name:DREW CHEMICAL CORP,DIV OF ASHLAND CHEMICAL CO

Address:ONE DREW CHEMICAL PLAZA

Box:City:BOONTON

State:NJ

ZIP:07005

Country:US

Phone:606-324-1133

CAGE:52454

===== Composition/Information on Ingredients =====

Ingred Name:SODIUM MOLYBDATE

CAS:7631-95-0

RTECS #:QA5075000

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG MO/M3

ACGIH TLV:5 MG MO/M3

Ingred Name:ORGANIC SALT, SPECIFIC CHEMICAL NAME IS BEING WITHHELD AS
TRADE SECRET

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM TOLYLTRIAZOLE

CAS:64665-57-2

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ORGANIC SALT, SPECIFIC CHEMICAL NAME IS BEING WITHHELD AS
TRADE SECRET

Fraction by Wt: 1-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM HYDROXIDE (CERCLA)

CAS:1310-73-2

RTECS #:WB4900000

Fraction by Wt

: 1-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:2 MG/M3

ACGIH TLV:C 2 MG/M3; 9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:EXPO CAUSES IRREVERSIBLE EYE

DMG.SKIN:EXPO CAUSES IRREVERSIBLE SKIN DMG.EXPOSURE MAY BE HARMFUL
OR FATAL.SWALLOWING-MAY BE HARMFUL OR FATAL.

Explana

tion of Carcinogenicity:PER MSDS:NO NTP/IARC/OSHA CARCINOGENS.

Effects of Overexposure:EYE:STINGING,TEARING,REDNESS,SWELLING,CORNEAL

DMG,BLINDNESS.SKIH:REDNESS,SWELLING,BURNS,SEVERE SKIN DMG.IRRIT &
BURNS TO NOSE/THROAT/RESPIRATORY TRACT.SEVERE IRRITATION AND BURNS
OF MOUTH/THROAT/DIGES TIVE TRACT.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE

AGGRAVATED BY EXPOSURE TO THIS MATL.PRE-EXISTING LUNG

DISORDERS(E.G. ASTHMA-LIKE CONDITIONS)MAY BE AGGRAVATED

BY EXPO TO
THIS MATL.

===== First Aid Measures =====

First Aid:SKIN:IMMED FLUSH W/WATER FOR @LEAST 15MINS WHILE REMOVEING
CONTAM CLOTH/SHOES.SEEK IMMED MED ATTN.EYE:IMMED FLUSH GENTLY
W/WATER FOR @LEAST 15MINS WHILE HOLDING EYELIDS APART.SYMPT DVLP AS
RESULT OF V AP EXPO IMMED MOVE INDIVIDUAL AWAY FRM EXPO & INTO
FRESH AIR BEF FLUSING RECOMMENDED AS ABOVE.SEEK IMMED MED
ATTN.INGEST:SEEK IMMED MED ATTN.DONT INDUCE VOMIT-IT WILL CAUS
E
FURTHER DMG TO MOUTH/(SUPP)

===== Fire Fighting Measures =====

Flash Point:NA
Autoignition Temp:Autoignition Temp Text:NP
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:REGULAR FOAM OR WATER FOG OR CARBON DIOXIDE OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS W/FULL
FACEPIECE OPERATED IN POSITIVE PRESSURE DEMAND MODE W/APPROP
TURNOUT GEAR & CHEM RESIST PPE.REFER PPE SEC OF MSDS
Unusual Fire/Explosion Ha
zard:NO SPECIAL FIRE HAZARDS ARE KNOWN TO BE
ASSOCIATED W/THIS PRODUCT.

===== Accidental Release Measures =====

Spill Release Procedures:SM:ABSORB LIQ ON ERMI,FLOOR ABSORBENT,OTHER
ABSORBENT MATL.LG:PERSONS NOT WEAR PPE SHOULD BE EXCLUDED FRM AREA
TIL CLEANUP COMPLETED.STOP SPILL @SOURCE.DIKE TO PREVENT
SPREADING.PUMP LIQ TO SALVAGE TN K,REMAIN LIQ TAKEUP ON
SAND,CLAY,FLOOR (SUPPLEMEN)
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:CNTNR OF MATL MAY BE HAZ WHEN EMPTIED
SINCE EMPTIED CNTNR RETAIN PROD RESIDUES(VAP,LIQ,&/OR SOLID)ALL HAZ
PRECAUT GIVEN IN DATA SHEET MUST BE OBSERVED
Other Precautions:KEEP FROM FREEZING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WORKPLACE EXPO LIMIT OR PROD/COMPO
EXCEEDED,NIOSH/MSHA APPROV AIR SUPP RESP ADVISED IN ABSENCE OF
PROPER ENVI

ROCNTRL.OSHA REG ALSO PERMIT OTHER NIOSH/MSHA RESP(NEG PRESS TYP)UNDER SPEC CONDITIONS.ENGI NEER/ADMIN CNTRL SHOULD BE INMPLEMENTED.

Ventilation:PROVIDE SUFFICIENT MECH(GENERAL &/OR LOCAL EXHAUST)VENTIALTION TO MAINTAIN EXPO BELOW TLV(S).

Protective Gloves:RESISTANT GLOVES SUCH AS NEOPRENE

Eye Protection:CHEM SPLASH GOGG,FCSHIELD(8")IAW OSHA RG

Other Protective Equipment:EYE PROT REGS ALSO PERMITS OTHER TYP OF SAF GLASS(CONSULT YOUR INDUST HYG).CLOTHING,BOOTS.

Work Hygienic Pract

ices:WASH CONTAM CLOTH BEF REUSE & DECONTAM/DISCARD CONTAM SHOES.

Supplemental Safety and Health

1ST AID:THROAT.PERSON CONSC/ALERT IMMED RINSE MOUTH W/H2O.GIVE MILK/H2O TO DRINK.IF POSSIBLE DONT LEAVE UNATTN.INHAL:SYMPT DVLP MOVE AWAY FRM EXPO INTO FRESH AIR.SYMPT PERSIST GET MED ATTN.BREATH DIFFI ADMIN OXY.KEEP WARM/QUIET.GET IMMED MEDATTN. SPILL:ABSORBENT.SHOVEL INTO CNTNR.PREVENT RUNOFF TO SEWER/STREAM/H2O BODY

=====
===== Physical/Chemical Properties =====
=====

HCC:B2

Boiling Pt:=100.C, 212.F

Vapor Pres:17.5

Vapor Density:>AIR

Spec Gravity:1.195

pH:13.0

Viscosity:NP

Evaporation Rate & Reference:UNAVAILABLE

Solubility in Water:NP

Appearance and Odor:CLEAR YELLOW LIQUID

Percent Volatiles by Volume:70-85

Corrosion Rate:NP

=====
===== Stability and Reactivity Data =====
=====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH:STRONG MINERAL ACIDS, STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED B

Y MANUFACTURER.

Hazardous Decomposition Products:MAY FORM:NITROGEN

COMPOUNDS,PHOSPHOROUS COMPOUNDS,CARBON DIOXIDE AND CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:SM:DISPO OF IAW ALL LOCAL, STATE AND FEDERAL REGULATIONS. LG:DISPO OF IAW ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the D

epartment

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.