Product ID: EPOXY CLEAR PRIMER PART A MSDS Date:08/17/1994 FSC:8010 NIIN:01-396-6848 Kit Part:Y MSDS Number: CDHKN === Responsible Party === Company Name: CRAWFORD LABORATORIES, INC. Address:4165 SOUTH EMERALD AVENUE City:CHICAGO State:IL ZIP:60609 Country:US Info Phone Num:312-376-7132 Е mergency Phone Num:312-433-1307 CAGE:DO165 === Contractor Identification === Company Name: CRAWFORD LABORATIES, INC Address:4165 SOUTH EMERALD AVENUE City:CHICAGO State:IL ZIP:60609 Phone:800-424-9300 CHEMTREC CAGE:DO165 Company Name: CRAWFORD LABORATORIES, INC Address:4165 SOUTH EMERALD AVENUE Box:City:CHICAGO State:IL ZIP:60609 Country:US Phone:312-376-7132 CAGE:5V430

Ingred Name:EPOXY RESIN CAS:25085-99-8 Fraction by Wt: >75 .0% Other REC Limits:NONE RECOMMENDED

Ingred Name:DIACETONE ALCOHOL (SARA 313)(VP = 1.1) CAS:123-42-2 RTECS #:SA9100000 Fraction by Wt: 5-20% Other REC Limits:NONE RECOMMENDED OSHA PEL:50 PPM ACGIH TLV:50 PPM

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Medical Cond Aggravated by Exposure:\*IF IRRITATION PERSISTS GET MED AID.

======= First

First Aid:EYE: FLUSH W/LOTS WATER 15 MIN HOLDING LIDS OPEN. GET MED AID. INHAL: GET FRESH AIR. GIVE OXYGEN IF TROUBLE BREATHING. IF NOT BREATHING GET MED AID. KEEP WARM. NEVER GIVE UNCONSCIOUS PERSON LIQUIDS. I NGEST: CALL DR IMMED. ONLY INDUCE VOMITING IF DR REC. IF VOMITING SPONTANEOUSLY KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION. SKIN: FLUSH W/WATER. REMOVE CONTAM CLOTHES/WASH BEFORE REUSE.\*

======================= Fire Fighting Measu

Flash Point Method:SCC
Flash Point:195F,91C
Lower Limits:1.8
Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL.
Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS COOL AND TO KEEP FLAMMABLE STRUCTURES WET. DO NOT ENTER FIRE AREA W/O PROPER PROTECTION (HAZARDOUS DECOMP PRODUCTS)
Unusual Fire/Explosion Hazard:SEALED CONTAINES MAY EXPLODE IF OVERHEATED. WATER PRESSURE MAY SPREAD A FLAMMABLE LIQUID FIRE.

======== Accidental Release

Measures ===============

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. SOAK UP WITH AN ABSORBENT AND PLACE IN NON-LEAKING CONTAINERS. SEAL TIGHTLY FOR PROPER DISPOSAL.

Handling and Storage Precautions:TREAT AS A HAZARDOUS-FLAMMABLE MATERIAL. STORE IN COOL DRY PLACE IN BUILDING DESIGNED FOR COMBUSTIBLE LIQUIDS.
Other Precautions:ANY PRO
POSED USE AT ELEVATED TEMPERATURE PROCESSES SHOULD BE THOROUGHLY EVALUATED TO ASSURE THAT SAFE OPERATING CONDITIONS ARE ESTABLISHED/MAINTAINED.

Respiratory Protection:USE NIOSH APPROVED ORGANIC VAPOR RESPIRATORS WHERE VENTILATION IS INADEQUATE. Ventilation:MUST PROVIDE ADEQUATE VENTILATION. Protective Gloves:RUBBER GLOVES. Eye Protection:APPROVED SAFETY GOGGLES AND FACE SHIELD. Other Protective Equipment:HAVE EYE B ATH & SAFETY SHOWER AVAILABLE. Supplemental Safety and Health NK

Boiling Pt:B.P. Text:337F,169C Vapor Density:>AIR Evaporation Rate & amp; Reference:0.13 X N-BUTYL ACETATE Appearance and Odor:CLEAR THIN LIQUID. Percent Volatiles by Volume:10.0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS AND STRONG ALKALIES. Stability Condition to Avoid :HEAT, SPARKS, OPEN FLAME Hazardous Decomposition Products:IMCOMPLETE COMBUSTION FOR PRODUCTS LIKE THIS MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND OTHER TOXIC GASES.

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH CURRENT LOCAL, STATE AND FEDERAL REGULATION. CONTACT AN APPROVED DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use

by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.