

INTERNATIOAL LUBRICANTS CO INC -- VV-C-844C WATER SOLUBLE CUTTING OIL --
9150-00-912-8784

===== Product Identification =====

Product ID:VV-C-844C WATER SOLUBLE CUTTING OIL

MSDS Date:10/01/1996

FSC:9150

NIIN:00-912-8784

MSDS Number: CDJQY

=== Responsible Party ===

Company Name:INTERNATIOAL LUBRICANTS CO INC

Address:10363 AIRLINE HIGHWAY

City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Info Phone Num:

504-469-0940

Emergency Phone Num:504-469-0940

CAGE:JO811

=== Contractor Identification ===

Company Name:INTERNATIONAL LUBRICANTS INC

Address:10363 W AIRLINE HWY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940(504-471-0104FAX)

CAGE:0W1H4

Company Name:INTERNATIONAL LUBRICATES INC

Address:10363 AIRLINE HIGHWAY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940

CAGE:JO811

Company Name:SDB CONSULTANTS LTD

Address:401 WHITNEY AVE SUITE 120

Box:City:GRETNA

State:L

A
ZIP:70056
Country:US
Phone:504-366-9105
CAGE:0PGK2

=====
Composition/Information on Ingredients
=====

Ingred Name:CUTTING FLUID (OIL), VV-C-846C (CAS#:64142-52-5)
CAS:64142-52-5
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:ACGIH TLV(OIL MIST)=5MG/M3.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL OF VAP/MIST MAY BE IRRIT TO RESP
PASSAGES.PROL EXPO MAY CAUSE DIZZ/NAU.SKIN PROL/REP CONTACT DEFAT
SKIN WHICH MAY RESULT IN DRYNESS,DERM,CRACKING OF
SKIN.EYE:IRRIT,REDNESS.INGEST:NAUSEA,STOMACH DISCOMFORT.
Effects of Overexposure:IRRITI RESPIRATORY PASSAGES, DIZZINESS, NAUSEA,
DEFAT SKIN RESULTING IN DRYNESS,DERMATITIS,CRACKING OF SKIN.
REDNESS IN EYES, STOMACH DISCOMFORT.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:INHAL:REMOVE TO FRESH AIR.ASSIST BREATH IF NECESSARY.SEEK MED
HELP.SKIN:WASH THOROUGHLY W/SOAP/WATER.REMOVE CONTAMIN
CLOTH.INGEST:OBSERVE FOR SIGNS OF STOMACH DISCOMFORT/NAUSES.IF
SYMPTOMS PERSIST SEE K MED HELP.

=====
Fire Fighting Measures
=====

Flash Point:NP
Autoignition Temp:Autoignition Temp Text:NP
Lower Limits:NP
Upper Limits:NP
Extinguishing Media:NONE SPECIFIED BY MANUFACTU

RER. HMIS:USE ANY

APPROPRIATE FIRE EXTINGUISHING MEDIA FOR SURROUNDING
FIRE/MATERIALS.

Fire Fighting Procedures:NONE SPECIFIED BY MANUFACTURER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:STOP SPILL @SOURCE W/O RISK.CONTAIN/ELIMINATE
IGN SOURCES.SPILL AREA WILL BE SLICK.RECOVER ALL POSSIBLE MATL FOR
RECLAMATION.USE NON-FLAMM ABSORBENT MATL TO PICKUP REMAINDER OF
SP

ILL.ADVICE AUTHORITIE S IF PROD ENTER/MAY ENTER H2O
COURSES/DRAINS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:FOLLOW HEALTH & SAFETY INFO AS
PROVIDED ON THIS MSDS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR SHOULD BE USE IN AREAS WHERE VAPOR
CONCEN ARE EXCESSIVE DU

E TO HIGH TEMPS OR WHERE OIL MISTING OCCURS.

Ventilation:ADEQUATE VENTILATION IS REQUIRED WHERE EXCESSIVE HEATING OR
AGITATION MAY OCCUR TO MAINTAIN CONCEN BELOW EXPO LIMITS.

Protective Gloves:AS NEEDED TO PREVENT REP SKIN CONTACT.

Eye Protection:SAFTEY GLASSES OR FACE SHIELD.

Other Protective Equipment:AS NEEDED TO PREVENT REPEATED SKIN CONTACT.

Work Hygienic Practices:REUSE CONTAMIN CLOTHING ONLY AFTER CLEANING.

Supplemental Safety and Health

DISPO:NAT RESP CNTR 800-424-8802.PLACE IN APPRO
PRIATE DISPO FACILITY

ICW LOC REGS.FOLLOW LOC/STATE/FED REGS.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:NP

Melt/Freeze Pt:M.P/F.P Text:NP

Decomp Temp:Decomp Text:NP

Vapor Pres:NP

Vapor Density:NP

Spec Gravity:NP

pH:NP

Viscosity:NP

Evaporation Rate & Reference:NP

Solubility in Water:NP

Appearance and Odor:NP

Percent Volatiles by Volume:NP

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stabili

ty Indicator/Materials to Avoid: YES

STRONG OXIDIZERS.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: COMBUSTION PRODUCTS: CARBON DIOXIDE,
CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: BASED ON DATA AVAIL TO CRYSTAL LUBRICANTS PROD
CONTAINS NO SUBST SUBJ TO REPORT/PLAN REQMTS UNDER SARA TITLE
III. MATL CLASSIFIED AS OIL UNDER SEC 311 CWA. SPILLS ENTERING SUR
H₂O/ANY H₂O COURSE
S/SEWERS ENTER/LEAD TO SURF H₂O CAUSE SHEEN
REPORT TO (SUPPL)

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for
or the suitability of this information to their
particular situation.